

Product Description

TREMDrain® S offers the highest compressive strength available within the TREMDrain Series and consists of a nonwoven, needle-punched, polypropylene fabric, polystyrene core and polymeric film backing.

Basic Uses

The TREMDrain Series of mats are used with TREMproof® and Paraseal® waterproofing membranes serving both as a protection course and replacement for traditional pipe and stone drainage systems.

Features and Benefits

- TREMDrain Series Drainage and Protection Boards replace or eliminate the need for a separate protection course.
- Provide an uninterrupted flow plane and eliminate the opportunity for hydrostatic pressure to form against a wall.
- Lightweight and easy to install compared to conventional pipe and stone drainage.

Availability

Immediately available from your local Tremco Sales Representative, Tremco Distributor or Tremco Warehouse.

Packaging

4' x 50' (1.22 M x 15.8 M)

Storage

Store out of direct sunlight. Vertical storage recommended.

Limitations

- Not for use beneath sand-set vehicular pavers.
- Not to be used as an exposed or wearing surface. Limit UV exposure to a maximum of 14 days.

Installation

Refer to TREMDrain Series Application Instructions for specific application details. The techniques included may require modification to adjust to job-site conditions. Consult your local Tremco Sales Representative or Tremco Technical Service for specific design requirements.

Warranty

Tremco warrants its Products to be free of defects in materials but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of Tremco Product proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TREMDrain® S

Multi-Composite Drainage and Protection Boards

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	VALUES US	VALUES SI
Typical Applications		Under Slab, Split Slab	
Roll Length		50'	15.24 M
Roll Width		4'	1.22 M
Roll Weight		46 lb	21.3 kg
Recycled Content		>75%	
Fabric			
Material		Nonwoven Needle-punched Polypropylene	
Grab Tensile Strength	ASTM D4632	100 lbf	445 N
CRB Puncture	ASTM D6241	275 lb	1220 N
UV Resistance	ASTM D4355	70% / 500 hrs	
Grab Elongation	ASTM D4632	65%	
AOS	ASTM D4751	70 sieve	210 micron
Permittivity	ASTM D4491	2.4 sec ⁻¹	
Permeability	ASTM D4491	0.3 cm/sec	
Flow Rate	ASTM D4491	165 gpm/ft ²	6,724 Lpm/M ²
Root Barrier Fabric		None	
Core			
Material		Polystyrene	
Thickness	ASTM D1777	1/4"	6.35 mm
Compressive Strength	ASTM D1621 ASTM D6364	30,000 lb/ft ² 30,000 lb/ft ²	1,436 kPa 1,436 kPa
Flow Capacity per unit width	ASTM D4716	13 gpm/ft	161 Lpm/M

1119/TSDSDS-BG

3735 Green Rd
Beachwood OH 44122
216.292.5000 / 800.321.7906

1451 Jacobson Ave
Ashland OH 44805
419.289.2050 / 800.321.6357

220 Wicksteed Ave
Toronto ON M4H1G7
416.421.3300 / 800.363.3213

1445 Rue de Coulomb
Boucherville QC J4B 7L8
514.521.9555