



## CONCRETE CRACK SEAL

A uniformly blended latex emulsion, specially designed to adhere to all concrete surfaces. No mixing is required. Just pour from the bottle. Blends in with the natural color of concrete. **Use For:**

- Repairing cracks in concrete sidewalks, patios and driveways

Item No.	Package Size	Metric	Quantity
8640-15	5.5 oz. tube	163 mL	12/case
8640-00	1 qt. bottle	946 mL	12/case
8640-01	1 gal. bottle	3.8 L	4/case



## CONCRETE REPAIR

A weather-resistant, sanded acrylic and flexible crack-filler and sealer. Helps prevent water and ice damage to concrete & masonry surfaces. Dries to a textured finish to blend with surrounding surface. Apply with standard caulking gun for 10 oz. size. **Use For:**

- Repairing cracks in concrete, masonry and stucco
- Ideal for vertical surfaces

Item No.	Package Size	Metric	Quantity
8620-13	5.5 oz. tube	163 mL	12/case
8620-10	10 oz. tube	296 mL	12/case



## MORTAR REPAIR

A sanded acrylic formula that adheres to brick, block, stone and concrete surfaces. Texture and color blends with the surrounding mortar. On the 10 oz. caulk tube the square applicator tip is designed to smooth mortar joints.

**Use For:**

- Tuck-pointing and sealing mortar joints

Item No.	Package Size	Metric	Quantity
8620-05	5.5 oz. tube	163 mL	12/case
8620-09	10 oz. tube	296 mL	12/case



## STUCCO REPAIR

Fills and seals cracks in stucco up to 1/2" (12 mm) wide. Weather resistant formula provides excellent adhesion and flexibility. Sanded acrylic formula blends with the texture of the surrounding stucco surface. **Use For:**

- Vertical or horizontal stucco repair applications

Item No.	Package Size	Metric	Quantity
8650-05	5.5 oz. tube	163 mL	12/case
8650-10	10 oz. tube	296 mL	12/case



## BLACKTOP REPAIR

A weather-resistant crack-filler, provides excellent adhesion and minimal shrinkage. Helps prevent water and ice damage to blacktop surfaces. Dries to a textured black finish. Non-flammable. **Use For:**

- Repairing cracks in blacktop and asphalt surfaces including driveways, roofs and chimney flashings

Item No.	Package Size	Metric	Quantity
8630-15	5.5 oz. tube	163 mL	12/case
8630-10	10 oz. tube	296 mL	12/case



## FIREPLACE REPAIR MORTAR

A silicate based refractory cement caulk for tuck-pointing damaged fireplace mortar joints and repairing cracked or chipped firebricks in fireplaces and wood-burning stoves.

It provides superior adhesion and withstands temperatures of 2000° F (1093° C). **Use For:**

- Tuck-pointing damaged fireplace mortar joints and repairing cracked or chipped firebricks

*Meets the requirements of ASTM E 136*

Item No.	Package Size	Metric	Quantity
8620-21	10 oz. tube	296 mL	12/case

1992



January 1993 Introduces  
QUIKRETE® 1-800 consumer hotline

October 1994 Introduces  
Concrete Project Instruction Center

