

NXT® LEVEL SP

Refer to Data Sheet 35609
Grey: 9600-0050-21



NXT LEVEL DL

Refer to Data Sheet 029.2
Grey: 0907-0055-21/ 0907-2200-21
White: 0908-0055-22/0908-2200-22



This premium self-leveling overlay is suitable as a high-strength wear surface or underlayment. Surface can be polished in 24 hours revealing a medium-coarse aggregate with an appealing salt and pepper appearance.

FEATURES/BENEFITS:

- Durable, attractive and low maintenance cementitious wear-surface with a salt and pepper finish
- Ultimate compressive strength (over 7,000 PSI 48.3 MPa)
- Polishable to a finished wear-surface in as little as 24 hours
- Low-shrinkage
- Pourable and pumpable

PACKAGING:

50 lb (22.7 kg) bag; 56 bags per pallet

A cement-based, high quality, fast drying dual purpose self-leveling underlayment/interior decorative wear surface topping. For application over a wide variety of substrates including concrete, VCT, and tile. Can be placed from 1/16" to 1-1/4" (1.5 – 32 mm) in a single lift.

FEATURES/BENEFITS:

- Dual purpose; for use as an attractive interior wear surface or as a high performance underlayment
- Pourable and pumpable
- Can be topically stained or integrally colored to match specific design needs
- Can be polished
- Apply finished flooring in as soon as 6 hours

PACKAGING:

50 lb (25 kg) bag/56 bags per pallet
2,200 (998 kg) Supersack

Approximate Coverage	
Thickness	Coverage
1/4" (6 mm)	20 ft ² (1.9 m ²)
1/2" (12 mm)	10 ft ² (0.9 m ²)
3/4" (18 mm)	5.8 ft ² (0.5 m ²)
1" (25 mm)	4.7 ft ² (0.4 m ²)
2" (51 mm)	2.3 ft ² (0.2 m ²)

Approximate Coverage		
Thickness	Coverage as a Wear Surface	Coverage as an Underlayment
1/16" (1.5 mm)	96 ft ² (8.9 m ²)	100 ft ² (9.3 m ²)
1/8" (3 mm)	48 ft ² (4.5 m ²)	50 ft ² (4.6 m ²)
1/4" (6 mm)	24 ft ² (2.2 m ²)	25 ft ² (2.3 m ²)
1/2" (12 mm)	12 ft ² (1.1 m ²)	12.5 ft ² (1.2 m ²)
3/4" (18 mm)	8 ft ² (0.7 m ²)	8.3 ft ² (0.8 m ²)
1" (25 mm)	6 ft ² (0.6 m ²)	6.3 ft ² (0.6 m ²)
1-1/4" (32 mm)	4.8 ft ² (0.4 m ²)	5 ft ² (0.5 m ²)