

■ Sure-Seal, Sure-White, and Sure-Tough EPDM

■ FleeceBACK

■ Sure-Weld TPO

■ Multiple-Ply Systems

■ Sure-Flex PVC

■ Low-VOC Product

Sure-Weld TPO Bonding Adhesive

A high-strength, solvent-based contact adhesive that allows bonding of Sure-Weld membrane to various porous and non-porous substrates.

Coverage Rate: 60 square feet per gallon of finished surface.

Packaging: 5-gallon pail

Product Number: 302099

Shelf Life: 12 months



X-Tenda Coat XTRA Silicone Coating

A single-component, moisture-cured, fluid-applied silicone coating that is specially formulated to meet low-VOC requirements. Once cured, the silicone coating membrane offers excellent resistance to water intrusion, UV exposure, and natural weathering. It is excellent for waterproofing and restoring existing roof systems. Available in White, Light Gray, Dark Gray, Tan, Santa Fe Tan, and Terra Cotta.

Packaging: 5-gallon pail/50-gallon drum

Water Cut-Off Mastic



A one-component, low-viscosity, self-wetting, butyl-blend mastic used in conjunction with roofing and waterproofing systems. It is used as a sealing agent between various membranes and substrates for compression-type terminations.

Coverage Rate: 10' per tube, using a 7/16" bead.

Packaging: 25 Tubes/carton

Product Number: 319621

Shelf Life: 12 months unopened container



TPO Primer

A high-solids, clear polymer-based primer used to prepare TPO membrane prior to the application of Pressure-Sensitive (PS) products.

Coverage Rate: 200 – 250 square feet (one surface) per gallon.

Packaging: (6) 1-gallon cans

Product Number: 310471

Shelf Life: 12 months unopened can



Weathered Membrane Cleaner



Used to clean both new and in-service EPDM and TPO membranes prior to seaming or application of Pressure-Sensitive (PS) products. Helps to loosen and remove dirt and other contaminants from the surface of the membranes and leaves a suitable surface for application of adhesive or primer. Please refer to the Product Data Sheets for specific instructions for EPDM and TPO applications.

Coverage Rate: 400 square feet (one surface) per gallon.

Packaging:
(2) 1-gallon closed-top cans,
5-gallon closed-top pail
1-gallon cans

Product Number: 304066 5-gallon pail

Product Number: 302074



Universal Single-Ply Sealant



A 100%-solids, solvent-free, one-part, polyether sealant that provides a weathertight seal to a variety of building substrates.

Coverage Rate: 25' per tube or 600' per carton using a 1/4" bead.

Packaging: 24 Tubes/carton

Product Number: 310131

Shelf Life: 12 months unopened container (@ <90°F)



Low-VOC Membrane Cleaner



Use to clean both new and in-service, PVC, KEE HP, TPO, and EPDM membranes prior to the seaming process. Low-VOC Membrane Cleaner contains 100% EPA-exempted solvents and can be used in a wide variety of temperatures.

Packaging: 1-gallon can (2) & 5-gallon can

Product Number:
326160 1-gallon can (2)
326860 5-gallon can



** Certain restrictions apply, see Product Data Sheet.

* Not compliant in all CA counties