

# SAFETY DATA SHEET

Issuing Date 21-Jul-2015

Revision Date 2-Sep-2020

**Revision Number** 1

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

#### GHS product identifier

Product Names: Roller-flex, Primecoat, Sanded Primecoat, Vintique, Clearshield, Elasto-flex, CIFS® Wood Grain Glaze and Sealer

#### Other means of identification

Synonyms None

## Recommended use of the chemical and restrictions on use

Recommended Use	Water based acrylic coating
-----------------	-----------------------------

Uses advised against No information available

Supplier's details

Supplier Address Master Wall Inc. 6975 Flat Rock Road Midland, GA 31820 TEL: 706-569-0092

#### Emergency telephone number

Emergency Telephone Number 1-800-535-5053

## 2. HAZARDS IDENTIFICATION

# **Classification**

This chemical is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

Not classified

# GHS Label elements, including precautionary statements

**Emergency Overview** 

Signal Word Hazard Statements • None None

The product contains no substances which at their given concentration are considered to be hazardous to health
Appearance Off white Physical State Liquid. Odor Slight

#### **Precautionary Statements**

Prevention

None

General Advice

None

StorageNone

Disposal

None

#### Hazard Not Otherwise Classified (HNOC)

#### Not applicable

#### Other information

Harmful to aquatic life. Very toxic to aquatic life with long lasting effects.

80.77% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS			
Chemical Name	CAS-No	Weight %	Trade secret
Titanium dioxide	13463-67-7	5-10	*
Quartz	14808-60-7	0.1-1	*
Water	7732-18-5	25-45	*
Ground Limestone	1317-65-3	15-35	*
Acrylic Polymer		10-30	*

The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

#### Description of necessary first-aid measures

**Eye Contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin Contact Wash skin with soap and water.

Inhalation Move to fresh air.

Ingestion Clean mouth with water and afterwards drink plenty of water.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

#### **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available.

#### Specific Hazards Arising from the Chemical

No information available.

Explosion Data Sensitivity to Mechanical Impact Sensitivity to Static Discharge

None. None.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures			
Personal Precautions	Ensure adequate ventilation. Avoid sanding and grinding surfaces containing dried paint film.		
Environmental Precautions			
Environmental Precautions	Avoid release to the environment. Dispose of contents/container to an approved waste disposal plant. Collect spillage. See Section 12 for additional Ecological Information.		
Methods and materials for contain	ment and cleaning up		
Methods for Containment	Prevent further leakage or spillage if safe to do so.		
Methods for Cleaning Up	Pick up and transfer to properly labeled containers.		
	7. HANDLING AND STORAGE		
Precautions for safe handling			
Handling	Handle in accordance with good industrial hygiene and safety practice. Avoid sanding and grinding surfaces containing dried paint film.		
Conditions for safe storage, including any incompatibilities			
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place.		
Incompatible Products	None known based on information supplied.		
8. EX	POSURE CONTROLS / PERSONAL PROTECTION		

# **Control parameters**

# **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Limestone 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> (vacated) TWA: 15 mg/m <sup>3</sup> (vacated) TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> respirable dust TWA: 10 mg/m <sup>3</sup> total dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	30/(%SiO2+2) mg/m <sup>3</sup> TWA, Total Dust;250/%SiO2+5) mppcf TWA, respirable fraction; 10/(%SiO2+2) mg/m <sup>3</sup> TWA, respirable TWA: 0.1 mg/m <sup>3</sup> (vacated)	
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	TWA: 5 mg/m <sup>3</sup> , as oil mist, mineral STEL: TWA: 10 mg/m <sup>3</sup> , as oil mist, mineral	TWA: 5 mg/m³, as oil mist, mineral	-
Silicon dioxide 7631-86-9	10 mg/m <sup>3</sup>	20 mppcf TWA; ((80)/(% SiO2) mg/m³)	IDLH: 3000 mg/m <sup>3</sup> TWA: 6 mg/m <sup>3</sup>
Diuron 330-54-1	TWA: 10 mg/m <sup>3</sup>	(vacated) TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m³
Kaolin 1332-58-7	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust

Ethanolamine	STEL: 6 ppm	TWA: 3 ppm	IDLH: 30 ppm	
141-43-5	TWA: 3 ppm	TWA: 6 mg/m <sup>3</sup>	TWA: 3 ppm	
		(vacated) TWA: 3 ppm	TWA: 8 mg/m <sup>3</sup>	
		(vacated) TWA: 8 mg/m <sup>3</sup>	STEL: 6 ppm	
		(vacated) STEL: 6 ppm	STEL: 15 mg/m <sup>3</sup>	
		(vacated) STEL: 15 mg/m <sup>3</sup>		
Appropriate engineering controls				
Engineering Measures	Showers			
	Eyewash stations			
	Ventilation systems			
	ventilation systems			
Individual materian management and an annual materian equipment				
Individual protection measures, such as personal protective equipment				

Eye/Face Protection	No special protective equipment required.
Skin and Body Protection	No special protective equipment required.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

# Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical State Odor	Liquid. Slight.	Appearance Odor Threshold	Off white. No information available.
<u>Property</u> pH Melting Point/Range Boiling Point/Boiling Range	<u>Values</u> 8 - 10 No data available > 100 °C	<u>Remarks/ - Me</u> None known None known None known	thod
Flash Point Evaporation rate Flammability (solid, gas) Flammability Limits in Air upper flammability limit	No data available No data available No data available No data available	None known None known None known	
lower flammability limit Vapor Pressure Vapor Density Specific Gravity	No data available No data available No data available >1; No units, but stated a	None known None known at a given None known	
Water Solubility Solubility in other solvents Partition coefficient: n-octand Autoignition Temperature Decomposition Temperature	temperature Miscible with water No data available <b>bl/water</b> No data available No data available No data available	None known None known None known None known None known	
Viscosity Flammable Properties	120-130 K.U.	None known	
Explosive Properties Oxidizing Properties Other information	No data available No data available		
VOC Content (%) VOC (g/l)	No data available <100 g/l		

# **10. STABILITY AND REACTIVITY**

## **Reactivity**

No data available.

## **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### **Hazardous Polymerization**

Hazardous polymerization does not occur.

#### **Conditions to avoid**

None known based on information supplied.

#### **Incompatible materials**

None known based on information supplied.

#### Hazardous decomposition products

None known based on information supplied.

# **11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

**Product Information** 

Inhalation	There is no data available for this product.
Eye Contact	There is no data available for this product.
Skin Contact	There is no data available for this product.
Ingestion	There is no data available for this product.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization Mutagenic Effects Carcinogenicity	No information available. No information available. The table below indicates whether each agency has listed any ingredient as a carcinogen. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur
	from exposure to this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B		Х
Quartz	A2	Group 1	Known	Х

## ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

#### IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans NTP: (National Toxicity Program) Known - Known Carcinogen

# OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration Hazard	No information available.

# Numerical measures of toxicity- ProductAcute Toxicity80.77%

80.77% of the mixture consists of ingredient(s) of unknown toxicity. > 5000 mg/kg; (ATE)

# **12. ECOLOGICAL INFORMATION**

## Ecotoxicity

LD50 Oral

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Propylene glycol 57-55-6	EC50 96 h: = 19000 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 51600 mg/L static (Oncorhynchus mykiss) LC50 96 h: 41 - 47 mL/L static (Oncorhynchus mykiss) LC50 96 h: = 51400 mg/L static (Pimephales promelas) LC50 96 h: = 710 mg/L (Pimephales promelas)	EC50 = 710 mg/L 30 min	EC50 24 h: > 10000 mg/L (Daphnia magna) EC50 48 h: > 1000 mg/L Static (Daphnia magna)
2,2,4-Trimethylpentane-1,3- diol monoisobutyrate 25265-77-4	EC50: 18.4 mg/L Pseudokirchneriella subcapitata 72 h	LC50 96 h: = 30 mg/L (Pimephales promelas)		LC50 96 h: > 95 mg/L (Daphnia magna)
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7		LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss)		EC50 48 h: > 1000 mg/L (Daphnia magna)
Silicon dioxide 7631-86-9	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)
2-Amino-2-methyl-1-propano I 124-68-5	EC50 72 h: = 520 mg/L (Desmodesmus subspicatus)	LC50 96 h: = 190 mg/L static (Lepomis macrochirus)		EC50 48 h: = 193 mg/L (Daphnia magna)
Ammonium hydroxide 1336-21-6		LC50 96 h: = 8.2 mg/L (Pimephales promelas)		EC50 48 h: = 0.66 mg/L (water flea) EC50 48 h: = 0.66 mg/L (Daphnia pulex)
Hexahydro-1,3,5-tris(2-hydro xyethyl)-S-triazine 4719-04-4	-	-	EC50 = 28.9 mg/L 15 min	-
Sodium nitrite 7632-00-0		LC50 96 h: = 0.19 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: 0.092 - 0.13 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: 0.4 - 0.6 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: 0.65 - 1 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 2.3 mg/L flow-through (Pimephales promelas) LC50 96 h: = 20 mg/L static (Pimephales promelas)		

#### Coatings

	I			
Diuron 330-54-1	EC50 72 h: < 0.1 mg/L static (Pseudokirchneriella subcapitata) EC50 96 h: = 0.0007 mg/L static (Pseudokirchneriella subcapitata) EC50 96 h: = 0.022 mg/L (Desmodesmus subspicatus) EC50 72 h: = 0.036 mg/L static (Desmodesmus subspicatus)	static (Oncorhynchus mykiss) LC50 96 h: 13.4-15 mg/L flow-through (Pimephales promelas) LC50 96 h: 13.4-15 mg/L static (Pimephales promelas) LC50 96 h: 2.3-3.3 mg/L static (Lepomis macrochirus) LC50 96 h: = 14.7 mg/L (Oncorhynchus mykiss) LC50 96 h: = 2.9 mg/L (Cyprinus carpio) LC50 96 h: = 4 mg/L (Lepomis macrochirus)	EC50 = 16.38 mg/L 5 min	EC50 48 h: 6.3 - 13 mg/L Static (Daphnia magna) EC50 48 h: = 1.4 mg/L (Daphnia magna)
3-lodo-2-propynyl butylcarbamate 55406-53-6		LC50 96 h: 0.049-0.079 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: 0.05-0.089 mg/L (Oncorhynchus mykiss) LC50 96 h: 0.14-0.32 mg/L flow-through (Lepomis macrochirus) LC50 96 h: 0.18-0.23 mg/L flow-through (Pimephales promelas)		
Polyethylene glycol 25322-68-3		LC50 24 h: > 5000 mg/L (Carassius auratus)	EC50 = 100000 mg/L 15 min	
Ethanolamine 141-43-5	EC50 72 h: = 15 mg/L (Desmodesmus subspicatus)	LC50: 227 mg/L Pimephales promelas 96 h flow-through LC50: 3684 mg/L Brachydanio rerio 96 h static LC50: 300-1000 mg/L Lepomis macrochirus 96 h static LC50: 114-196 mg/L Oncorhynchus mykiss 96 h static LC50: >200 mg/L Oncorhynchus mykiss 96 h flow-through	EC50 = 12200 mg/L 2 h EC50 = 13.7 mg/L 30 min	EC50 48 h: = 65 mg/L (Daphnia magna)

Persistence and Degradability

No information available.

**Bioaccumulation** 

No information available.

Other Adverse Effects

No information available.

# **13. DISPOSAL CONSIDERATIONS**

Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

#### **Contaminated Packaging**

Do not re-use empty containers.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl-2-benzimidazole	U372	Included in waste streams:		U372
carbamate - 10605-21-7		K156, K158		
3-lodo-2-propynyl	(hazardous constituent - no			
butylcarbamate - 55406-53-6	waste number)			

# 14. TRANSPORT INFORMATION

DOT

Not regulated

# **15. REGULATORY INFORMATION**

International Inventories TSCA

All components of this product are either listed or are exempt on the TSCA inventory.

#### Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

## U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

## SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

#### U.S. State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Titanium dioxide	13463-67-7	Carcinogen
Quartz	14808-60-7	Carcinogen
Diuron	330-54-1	Carcinogen

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Limestone	Х	X	Х		Х
Titanium dioxide	Х	Х	Х	-	Х
Propylene glycol	Х	-	Х	-	Х
Quartz	Х	X	Х	-	Х
Petroleum distillates, hydrotreated heavy paraffinic				Х	

# U.S. EPA Label Information

# EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION				
NFPA_	Health Hazard 1	Flammability 0	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 1	Flammability 0	Physical Hazard 0	Personal Protection X
Prepared By	Master Wall Inc.			
	6975 Flat Rock Road			
	Midland, GA 31820 TEL: 706-569-0092			
Issuing Date	21-Jul-2			
Revision Date	21-Jul-2015			
Revision Note	Initial Release.			

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet