



METACAULK® FIRESTOP SEALANTS

Metacaulk® 1000

Intumescent, water-based firestop sealant

Code	Description	Qty.
66640	10.3 oz. cartridge	12
66303	30 oz. cartridge	12
66312	20.2 oz. foil pack	12
66309	5 gal. caulk grade	1

APPLICATION • Will prevent the spread of fire through joint openings and through-penetrations • No dilution or mixing required • Can be used in areas exposed to vibration and movement • Use in fire-rated gypsum wallboard partitions, concrete walls or floors, wood floors and concrete or corrugated steel deck floor/ceiling assemblies

RECOMMENDED FOR • Metal pipes • Insulated pipes • Fiberglass & plastic pipes • Wall construction joints • Power & telephone cables • HVAC ducts



FEATURES

- UL Classified systems up to 4 hrs.
- Class 1 W Rating
- Highly intumescent
- Excellent freeze-thaw
- For interior use - paintable
- VOC compliant - CDPH Standard Method v1.2
- 3 year shelf life
- STC rating 62
- Tested in accordance with ASTM E814 (UL 1479) & ASTM E1966 (UL 2079)
- Tested to ASTM G21 standard
- Complies to UL required Accelerated Aging and High Humidity Testing
- Color: Red



*FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® piping systems and products made with TempRite® Technology. The FBC System Compatible Logo, FBC®, FlowGuard Gold®, BlazeMaster®, Corzan® and TempRite® are trademarks of Lubrizol Advanced Materials, Inc. or its affiliates.