

PRODUCT DATA SHEET

Sika® Joint Tape SA

Self-adhering polymeric rubberized tape with woven polyester facer

PRODUCT DESCRIPTION

Self-adhering polymeric rubberized tape with plastic release liner on underside and woven polyester facer on top side. Enhances the strength and durability of Sikalastic® roofing and waterproofing membranes at joints and angle changes.

USES

- Reinforcement of joints between cover boards and insulation
- Reinforcement of joints between plywood deck panels
- Reinforcement of joints and seams in metal roofing
- Stripping in of metal flanges to structural deck

CHARACTERISTICS / ADVANTAGES

- Self-adhering, no primer required for most applications
- Polyester facer allows positive resin/coating bond
- Stretches with membrane to accommodate thermal and structural movement
- Imparts additional strength and durability
- Conforms to substrate contours and flashing conditions

PRODUCT INFORMATION

Packaging	<ul style="list-style-type: none"> ▪ 3" w x 50', individually wrapped rolls and sold in cases (8 rolls to carton) ▪ 6" w x 50', individually wrapped rolls and sold in cases (4 rolls to carton)
Shelf Life	24 months
Storage Conditions	Store flat in original, unopened and undamaged sealed packaging in dry conditions. Do not expose to direct sunlight or other heat sources.
Appearance / Color	Off-white
Top surface	Polyester
Bottom Surface	Grey, adhesive with release liner
Thickness	30 mils

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet

Sika® Joint Tape SA
May 2023, Version 01.02
02094511800000018

SikaJointTapeSA-en-US-(05-2023)-1-2.pdf

