


SBS-MODIFIED BITUMEN MEMBRANES
COLPHENE®



COLPHENE BSW H

PRODUCT CODE

D00287



Scan QR code with
the SOPREMA toolbox
app for more information.

COLPHENE®

BSW H

COLPHENE BSW H is an SBS-modified bitumen waterproofing membrane for use in approved blind side/under slab waterproofing assemblies. COLPHENE BSW H is composed of a proprietary formulation of elastomeric styrene-butadiene-styrene (SBS) polymer modified bitumen and is reinforced with a tough, dimensionally stable non-woven polyester mat. COLPHENE BSW H is designed for horizontal blind side/under slab waterproofing applications. The topside is surfaced with fine mineral aggregate and the underside is surfaced with polyolefin burn-off film.

INSTALLATION

Prior to installation, unroll COLPHENE BSW H and allow to relax. Loose lay COLPHENE BSW H in desired position on approved prepared substrate. Once the membrane is in the desired location remove the release film on the DUO SELVEDGE side lap. Once the self-adhered portion of the lap is adhered, a heat welding device is used to seal the lap.

PRODUCT PROPERTIES

REINFORCEMENT	Non-woven Polyester
THICKNESS	140 mils (3.5 mm)
TOPSIDE	Sanded
UNDERSIDE	Polyolefin Film

APPLICATION



LOOSE LAID

RELATED PRODUCTS

COLPHENE BSW PROTECT'R
COLPHENE LIQUID MEMBRANE
COLPHENE BSW V