

## L&M DURACRETE™

Refer to Data Sheet 174.4

9-31-622-1574



L&M DURACRETE™ is a single component, polymer-reinforced, high-strength, cement-based patching and resurfacing mortar. L&M DURACRETE is designed to repair, slope, and level structurally sound interior and exterior concrete surfaces that are pitted, worn, scaled, or spalled.

### FEATURES/BENEFITS:

- Excellent abrasion resistance
- Excellent bond strength
- May be mixed with coarse aggregate
- Long lasting concrete repairs
- Versatile indoor and outdoor use

### PACKAGING:

50 lb (22.7 kg) bag

### APPROXIMATE COVERAGE

Nominal Thickness	Approximate Coverage
1/8" (3 mm)	42 ft <sup>2</sup> (3.9 m <sup>2</sup> )
1/4" (6 mm)	21 ft <sup>2</sup> (2.0 m <sup>2</sup> )
1/2" (12 mm)	11 ft <sup>2</sup> (1.0 m <sup>2</sup> )
1" (25 mm)	5.2 ft <sup>2</sup> (0.5 m <sup>2</sup> )
2" (50 mm)	2.6 ft <sup>2</sup> (0.2 m <sup>2</sup> )
3" (76 mm)	1.7 ft <sup>2</sup> (0.2 m <sup>2</sup> )
Slurry coat	50 ft <sup>2</sup> (4.6 m <sup>2</sup> )