

## SpecSeal<sup>®</sup> LC Endothermic Sealant

**SpecSeal<sup>®</sup> LC Endothermic Sealant** is a latex-based gun grade firestop sealant for construction joints and non-combustible penetrations. After application, LC Sealant cures to form a flexible seal against the propagation of fire. Under fire exposure, LC absorbs heat and releases water vapor resisting the progress of smoke and flame.

- Installer Friendly, easily applied with standard caulking gun
- Can be troweled on for larger applications
- Tested for up to 4 Hours of fire resistance when tested to ASTM E1966/UL2079, ASTM E814/UL1479, and CAN/ULC-S115
- Listed in over 80 UL<sup>®</sup> Tested Firestop Systems



ORDERING INFORMATION					
Catalog Number	UPC Number	Description	(UOM) Qty.	Case Qty.	
LC150	730573011300	Endothermic Sealant 10.1 Oz. Tube - 18.2 cu in. (300 ml)	1	12	
LC120	730573011331	Endothermic Sealant 20 Oz. Sausage - 36 cu. in. (592 ml)	1	12	
LC129	730573011317	Endothermic Sealant 29 Oz. Tube - 52 cu. in. (858 ml)	1	12	
LC155	730573011355	Endothermic Sealant 5 Gallon Pail - 1,155 cu. in. (19 liters)	1	1	

**TEST STANDARDS:** ASTM E814 (UL 1479), ASTM E1966, ASTM E90

■ Deep Red Color    
 Permanent Solution    
 ACOUSTICAL STC 61 (Relates to specific construction)    
 UL CERTIFIED    
 FM APPROVED

## SpeedFlex<sup>®</sup> SFJP SpeedFlex<sup>®</sup> Joint Profile System

**SpeedFlex<sup>®</sup> Joint Profile** partners with SpecSeal<sup>®</sup> spray-applied coatings to provide unsurpassed joint movement capabilities in standard gypsum board construction. SpeedFlex<sup>®</sup> Joint Profile eliminates the need for traditional forming materials allowing for reduced application times increasing productivity.

- Allows 100 % compression or extension
- Excellent remediation tool for cracked or deficient joints
- Cost effective alternative to traditional joint forming materials



ORDERING INFORMATION				
Catalog Number	UPC Number	Description	(UOM) Qty.	Case Qty.
SFJP40	730573081440	Joint Profile - 4" x 43.38"	1	150 per box
SFJP80	730573081457	Joint Profile - 8" x 43.38"	1	75 per box

**TEST STANDARDS:** ASTM E1966 (UL 2079), ASTM E1966, CAN/ULC S115

■ Brown Color    
 Permanent Solution    
 MOVEMENT +100% Maximum Movement Capability    
 UL CERTIFIED