

PRODUCT DESCRIPTION

Dymonic 100 is a high-performance, high-movement, single-component, medium-modulus, low-VOC, UV-stable, non-sag polyurethane sealant.



ALMOND



IVORY



ALUMINUM STONE



LIGHT BRONZE



ANODIZED ALUMINUM



LIMESTONE



BEIGE



NATURAL CLAY




BLACK



OFF WHITE



BRONZE




PRECAST WHITE



BUFF



REDWOOD TAN



DARK BRONZE



SANDALWOOD



GRAY



STONE



GRAY STONE



WHITE



HARTFORD GREEN

This guide only offers a general representation of our color offering. Colors viewed on a computer screen and then printed will vary and will never be an exact representation of the actual pigment. When matching is critical, please refer to our color card or sample color strips.

Tremco Commercial Sealants & Waterproofing | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Tremco Construction Products Group (CPG) brings together Tremco Incorporated's Commercial Sealants & Waterproofing and Roofing & Building Maintenance operating divisions; Dryvit Systems, Inc.; Nudura Inc.; Willseal; Weatherproofing Technologies, Inc. and Weatherproofing Technologies Canada, Inc.

Tremco® and Dymonic® are registered trademarks of Tremco Incorporated. Willseal is a registered trademark of Use of the ® symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.

Part of
 **TREMCO**
Construction Products Group