

SOPRASEAL® XPRESS G SCREWS

SOPRASEAL® Xpress G Screws are self-drilling screw fasteners specifically designed for the installation of SOPRASEAL® Xpress G boards. SOPRASEAL® Xpress G screws are #10-24 x 1-1/2 inch steel with an anti-corrosion coating. The screw heads are flat with a Phillips drive.

INSTALLATION

Fasteners should be installed using an 1800-2500 RPM screw gun.

SOPRASEAL XPRESS G SCREWS

PRODUCT CODE

D20963



Scan QR code with the SOPREMA toolbox app for more information.

SOPRASEAL® LT ADDITIVE

SOPRASEAL LT Additive is a liquid additive designed to be combined with SOPRASEAL LM 202 VP and SOPRASEAL LM 203. When blended with one of these products, it allows for application at temperatures as low as 25°F (-4°C).

INSTALLATION

Prior to installation, ensure that the substrate is free of frost and condensation. Follow all application instructions for SOPRASEAL LM 202 VP and SOPRASEAL LM 203. SOPRASEAL LT Additive can be applied in temperatures as low as 25°F (-4°C) without the use of additional heat. SOPRASEAL LT Additive must be protected from precipitation for a minimum of 24 hours and temperatures must remain at or above 25°F (-4°C) until the material has dried. Drying time varies depending on ambient and substrate temperatures, humidity, and the ability of the substrate to absorb water.

SOPRASEAL LT ADDITIVE

PRODUCT CODE

A503



Scan QR code with the SOPREMA toolbox app for more information.