

MasterSeal 900 Wht 452

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000322820	Date of first issue: 07/20/2020

SECTION 1. IDENTIFICATION

Product name : MasterSeal 900 Wht 452
Product code : 000000000057626888 000000000057626888

Manufacturer or supplier's details

Company name of supplier : Master Builders-Admixtures US,LLC
Address : 23700 CHAGRIN BLVD
Beachwood OH 44122
Emergency telephone : ChemTel: +1-813-248-0585 USA: +1-800-255-3924 Contract
Number MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

No need for classification according to GHS criteria for this product.

GHS label elements

The product does not require a hazard warning label in accordance with GHS criteria.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Titanium dioxide	13463-67-7	>= 25 - < 50
aluminium hydroxide	21645-51-2	>= 1 - < 3

SECTION 4. FIRST AID MEASURES

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.
Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.

In case of eye contact : Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

MasterSeal 900 Wht 452

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000322820	Date of first issue: 07/20/2020

Most important symptoms and effects, both acute and delayed : If symptoms persist, call a physician.
None known.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : water jet

Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.

Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides

Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.
Wear eye/face protection.
If exposed to high vapour concentration, leave area immediately.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.

Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.

Further information on storage : Keep only in the original container in a cool, dry, well-

MasterSeal 900 Wht 452

Version 1.0 Revision Date: 07/20/2020 SDS Number: 000000322820 Date of last issue: -
Date of first issue: 07/20/2020

age conditions ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.

Materials to avoid : No applicable information available.

No materials to be especially mentioned.

Further information on stor- : No decomposition if stored and applied as directed.
age stability

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIH TLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
aluminium hydroxide	21645-51-2	TWA value (Respirable fraction)	1 mg/m3	ACGIH TLV
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminum)	ACGIH

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate.
Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : General industrial hygiene practice.

MasterSeal 900 Wht 452

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000322820	Date of first issue: 07/20/2020

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	pasty
Color	:	ivory colour
pH	:	No data available
Boiling point	:	No applicable information available.
Flash point	:	> 450 °F / > 232 °C Method: Flash-Point by Pensky-Martens Closed Cup Tester. > 450 °F / > 232 °C
Evaporation rate	:	No applicable information available.
Flammability (solid, gas)	:	not determined
Self-ignition	:	not self-igniting
Upper explosion limit / Upper flammability limit	:	No applicable information available.
Lower explosion limit / Lower flammability limit	:	No applicable information available.
Vapor pressure	:	No applicable information available.
Relative vapor density	:	No applicable information available.
Relative density	:	No applicable information available.
Density	:	1.60 g/cm ³ (72 °F / 22 °C) 13.35 lb/USg (72 °F / 22 °C)
Bulk density	:	1,800 - 2,400 kg/m ³
Solubility(ies)	:	
Water solubility	:	insoluble
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	No applicable information available.
Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as pre-scribed/indicated.
Viscosity	:	
Viscosity, dynamic	:	No applicable information available.
Viscosity, kinematic	:	No applicable information available.

MasterSeal 900 Wht 452

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000322820	Date of first issue: 07/20/2020

Explosive properties	:	Not explosive Not explosive Not explosive Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Sublimation point	:	No applicable information available.
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. No hazards to be specially mentioned.
Conditions to avoid	:	See SDS section 7 - Handling and storage.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

MasterSeal 900 Wht 452

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000322820	Date of first issue: 07/20/2020

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Components:****Titanium dioxide:**

Partition coefficient: n-octanol/water : Remarks: not applicable

aluminium hydroxide:

Partition coefficient: n-octanol/water : Remarks: The value has not been determined because the substance is inorganic.

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not discharge into drains/surface waters/groundwater.

MasterSeal 900 Wht 452

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000322820	Date of first issue: 07/20/2020

Contaminated packaging : Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**US State Regulations****Pennsylvania Right To Know**Titanium dioxide
listed

13463-67-7

New Jersey Right To KnowTitanium dioxide
listed

13463-67-7

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:


TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

SECTION 16. OTHER INFORMATION**Further information**

MasterSeal 900 Wht 452

Version
1.0Revision Date:
07/20/2020SDS Number:
000000322820Date of last issue: -
Date of first issue: 07/20/2020

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	: Permissible exposure limit
ACGIH / TWA	: 8-hour, time-weighted average
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
OSHA P0 / TWA	: 8-hour time weighted average
OSHA Z-1 / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - In-

MasterSeal 900 Wht 452

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000322820	Date of first issue: 07/20/2020

ternational Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/20/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN

MasterSeal 900 Wht 452

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000322820	Date of first issue: 07/20/2020
