



## Starter Strips / Casing Beads



Designed to protect the raw edges of the board in Direct-Applied Exterior Finish Systems. Large perforations allow matrix to easily flow through and bond to substrate. Caulk all intersections, butt joints, ends and corners at time of installation.



### DEFS L-Stop Casing Bead

Provides casing against doors, windows and dissimilar materials.



Product Code	Finish Thickness	(A) Board Thickness	(B) Perforated Flange	Pieces per Box
SBL50E	1/16"	1/2"	1-3/4"	50
SBL58E	1/16"	5/8"	1-3/4"	50
SBL100E	1/16"	1"	1-3/4"	50



### DEFS L-Stop Casing Bead with Splice

Provides casing against doors, windows and dissimilar materials. Splice allows for splice connection and alignment.



Product Code	Finish Thickness	(A) Board Thickness	(B) Perforated Flange	Pieces per Box
DE/LB50E	1/16"	1/2"	1-1/2"	50
DE/LB58E	1/16"	5/8"	1-1/2"	50



### DEFS 45 Degree L-Bead

Trim component used to finish around window and door penetrations as a backing for perimeter sealant application.

Product Code	Finish Thickness	(A) 45° L	(B) Perforated Flange	Pieces per Box
DE/LB-45	1/16"	1/2"	1-3/4"	50



### DEFS Muddable J-Bead

Product Code	Finish Thickness	(A) Board Thickness	(B) Perforated Flange	(C) Return Flange	Pieces per Box
MJB50E	1/16"	1/2"	1-1/8"	1/4"	50
MJB58E	1/16"	5/8"	1-1/8"	1/4"	50