



JS160H Mastic

Description

JS160H Mastic is a rubberized blend of premium grade bituminous and synthetic resins used for sealing detail cuts and membrane terminations on Protecto Wrap Company's waterproofing and flashing membranes. JS160H Mastic is VOC Compliant.

Composition

SBS Modified Rubberized Asphalt

Technical

| | |
|--------------------------|-----------|
| Adhesion to steel | Excellent |
| Adhesion to concrete | Excellent |
| Adhesion to membrane | Excellent |
| Shelf Life (minimum) | 1 Year |
| Tack free Time (minutes) | 30 |

Precautions

Extremely flammable. Contains volatile solvents. Keep away from heat, sparks and flame during transportation, storage, handling and application. Do not store in direct sunlight. Warm container must be cooled before opening to reduce vapor pressure. Release pressure slowly when opening. Keep container closed when not in use. Vapor may migrate to sources of ignition. Do not smoke, weld, generate sparks or use flame near container. Wear appropriate clothing, gloves, and properly fitted respirator (NIOSH/MSHA) during application. Vapor may be irritating and may be harmful or fatal if swallowed. Do not take internally. Guard against contact with skin and eyes. Precautions also apply to emptied containers. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

In case of headache, irritation, or other symptoms of overexposure, move from affected area. Wash contacted area with hand cleaner, followed by soap and water. Avoid further overexposure. If symptoms persist, contact physician. Flush eyes immediately with running water for 15 minutes and get medical attention. If ingested, contact physician immediately. Do not induce vomiting.

Carefully clean up with mineral spirits, xylene, toluene, or acetone.



Premium Building Products
That Protect

Packaging

JS160H Mastic is available in the following sizes:

10.5 Fluid Oz. Tube

1 Gallon Can

5 Gallon Can

Coverage

10.5 Fluid Oz. Tube = Approximately 32 lineal feet (based upon ¼" bead)

1 Gallon = Approximately 200 lineal feet (based upon a 2" 60-mil, wet-film, troweled-bead)

PROTECTO WRAP COMPANY
1955 South Cherokee Street
Denver, CO 80223
(303) 777-3001 • (800) 759-9727
FAX (303) 777-9273
www.protectowrap.com