

CETGUARD ACTIVATOR

CLEANING & RE-ACTIVATING SOLUTION

DESCRIPTION

CETGUARD ACTIVATOR is clear aromatic blended solvent.

APPLICATIONS

CETGUARD ACTIVATOR is used to clean and re-activate the transition area of existing cured in-place membranes at tie-ins, repairs and between staged coats of resin. CETGUARD ACTIVATOR may also be used as solvent for cleaning metal and plastic surfaces prior to resin application, or for cleaning spills, tools and equipment.

PACKAGING

CETGUARD ACTIVATOR is supplied in 3.78 L (1-gallon) resealable metal cans.

COVERAGE

Consumption will vary depending upon application and use.

STORAGE

Always store in cool and dry location. Do not store in direct sunlight or in temperatures above 25°C (77°F). Flammable, keep away from heat, sparks, open flame.

APPLICATION CONDITIONS

Refer to the CETGUARD technical data sheets for recommendations on specific applications.

APPLICATION

CETGUARD ACTIVATOR should be wiped on the in-place membrane, allowed 20-minutes evaporation time, and over-coated within 60-minutes of application. CETGUARD ACTIVATOR should only be applied over an area that can be over-coated within a 60-minute period. Re-apply CETGUARD ACTIVATOR as required to assure proper reactivation of all transition areas.

SAFETY RECOMMENDATIONS

Refer to product Safety Data Sheet (SDS) prior to use or handling.

DISPOSAL

CETGUARD ACTIVATOR is considered a hazardous material and must be handled as such, in accordance with local, state and federal regulations. Refer to product Safety Data Sheet (SDS) for additional information, and prior to use or handling.

DISCLAIMER

NO WARRANTY, EXPRESS OR IMPLIED, IS MADE IN THIS DOCUMENT. THE PRODUCT IS NOT CLAIMED TO BE MERCHANTABILITY OR FIT FOR ANY PARTICULAR PURPOSE. User and certified CETCO Approved Applicators determine suitability only. See individual CETCO product data sheets, SDS sheets, guide specifications and details for complete information regarding the suitability, application and handling of CETCO products.

North America: 847.851.1800 | 800.527.9948 | www.cetco.com

UPDATED: JANUARY 2018

© 2018 Minerals Technologies Inc. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.cetco.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

FORM: TDS_CETGUARD_ACTIVATOR_AM_EN_201801_V1



CETCO