

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Page: 1/13

Revision: September 14, 2020

1 Identification

- · Product identifier
- · Trade name: Pecora Deck 806 Top Coat
- · Other means of identification: No other identifiers
- · Recommended use and restriction on use
- · Recommended use: Pedestrian and Vehicular Deck Coating System
- · Restrictions on use: No relevant information available.
- Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Pecora Corporation 165 Wambold Road Harleysville, PA 19438 215-723-6051

· Emergency telephone number:

CHEMTREC

1-800-424-9300 (US/Canada)

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapor.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

- Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:







GHS02 GHS07 GHS08

- · Signal word: Warning
- · Hazard statements:

H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

H361 Suspected of damaging fertility or the unborn child.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

(Cont'd. on page 2)





Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 806 Top Coat

	(Cont'd. of page	e 1)
P241	Use explosion-proof electrical/ventilating/lighting/equipment.	
P242	Use only non-sparking tools.	
P243	Take precautionary measures against static discharge.	
P261	Avoid breathing dust/fume/gas/mist/vapors/spray	
P264	Wash thoroughly after handling.	
P272	Contaminated work clothing must not be allowed out of the workplace.	
P280	Wear protective gloves/protective clothing/eye protection.	
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with	
	water/shower.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses	s. if
	present and easy to do. Continue rinsing.	,
P308+P313	IF exposed or concerned: Get medical advice/attention.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P363	Wash contaminated clothing before reuse.	
P370+P378	In case of fire: Use foam, powder, or carbon dioxide for extinction.	
P403+P235	Store in a well-ventilated place. Keep cool.	
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional/national/international	ı
	regulations.	•
	3	

· Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

Component	ts:	
14807-96-6	Talc	<20
98-56-6	4-chloro-α,α,α-trifluorotoluene	<10
	 Flam. Liq. 3, H226 Carc. 2, H351 Skin Sens. 1B, H317 	
	Eye Irrit. 2B, H320	
108-32-7	Propylene carbonate	<10
C4740 0F C	Eye Irrit. 2A, H319Solvent naphtha (petroleum), light arom.	<10
04/42-95-0	 ♦ Flam. Liq. 3, H226 ♦ Asp. Tox. 1, H304 	<10
556-67-2	Octamethylcyclotetrasiloxane	<10
	Flam. Liq. 3, H226Repr. 2, H361	
13463-67-7	Titanium dioxide	<10
128-37-0	2,6-di-tert-butyl-p-cresol	<19
91-20-3	Naphthalene Flam. Sol. 2, H228 Carc. 2, H351 Acute Tox. 4, H302	<10
526-73-8	1,2,3-trimethylbenzene	<19
		(Cont'd. on page





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 806 Top Coat

	(Cont	'd. of page 2)
	 ♦ Flam. Liq. 3, H226 ♦ STOT RE 2, H373; Asp. Tox. 1, H304 ↑ STOT SE 3, H335-H336 	
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate Skin Sens. 1, H317	<1%
95-63-6	1,2,4-trimethylbenzene Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	<1%
100-41-4	Ethylbenzene Flam. Liq. 2, H225 Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332 Eye Irrit. 2B, H320	<1%

· Additional information:

For the wording of the listed Hazard Statements, refer to section 16.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

· Description of first aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Wash with soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Most important symptoms and effects, both acute and delayed:

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Causes serious eye irritation.

Allergic reactions

· Danger:

Suspected of causing cancer. Route of exposure: Inhalation.

Suspected of damaging fertility or the unborn child.

Indication of any immediate medical attention and special treatment needed:

Treat symptomatically.

Contains 4-chloro- α , $\dot{\alpha}$, α -trifluorotoluene, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate. May produce an allergic reaction.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

Extinguishing media

(Cont'd. on page 4)



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Page: 4/13

Revision: September 14, 2020

Trade name: Pecora Deck 806 Top Coat

· Suitable extinguishing agents:

Foam

Sand

Carbon dioxide

Fire-extinguishing powder

Gaseous extinguishing agents

Water fog / haze

- · For safety reasons unsuitable extinguishing agents: Water stream.
- · Special hazards arising from the substance or mixture

Flammable liquid and vapor.

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective equipment as required.

Keep away from ignition sources.

Take precautionary measures against static discharge.

Environmental precautions

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Methods and material for containment and cleaning up

Towel or mop up material and collect in a suitable container.

For larger spills, add non-combustible inert binding material, then sweep up and discard.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling

· Precautions for safe handling:

Open and handle receptacle with care.

Keep out of reach of children.

Avoid contact with the eyes and skin.

Keep away from open flame or other ignition sources.

Information about protection against explosions and fires:

Flammable liquid and vapor.

Protect against electrostatic charges.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

· Conditions for safe storage, including any incompatibilities

· Requirements to be met by storerooms and receptacles:

(Cont'd. on page 5)

(Cont'd. of page 3)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 806 Top Coat

(Cont'd. of page 4)

Store in cool, dry conditions in well-sealed receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

•	· Control parameters · Components with limit values that require monitoring at the workplace:	
14807-96-6 Talc		
PEL (USA)	Long-term value: 20 mppcf ppm	
I LL (OOA)	(containing <1% Quartz)	
REL (USA)	Long-term value: 2* mg/m³ *respirable dust; and <1% Quartz	
TLV (USA)	Long-term value: 2* mg/m³ *as respirable fraction; E	
EL (Canada)	Long-term value: 2 *0.1 f/cc mg/m³ resp. *if contains asbestos : ACGIH A1, IARC 1	
EV (Canada)	Long-term value: 2* mg/m³, 2 f/cc ppm *respirable	
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable	
556-67-2 Octan	nethylcyclotetrasiloxane	
WEEL (USA)	Long-term value: 10* ppm *OARS WEEL	
13463-67-7 Tita	nium dioxide	
PEL (USA)	Long-term value: 15* mg/m³ *total dust	
REL (USA)	See Pocket Guide App. A	
TLV (USA)	Long-term value: 10 mg/m³	
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction; IARC 2B	
EV (Canada)	Long-term value: 10 mg/m³ total dust	
LMPE (Mexico)	Long-term value: 10 mg/m³ A4	
128-37-0 2,6-di-tert-butyl-p-cresol		
REL (USA)	Long-term value: 10 mg/m³	
TLV (USA)	Long-term value: 2* mg/m³ *as inhalable fraction and vapor	
EL (Canada)	Long-term value: 2 mg/m³ vapour and inhalable aerosol	





Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 806 Top Coat

EV (Canada)	Long-term value: 2 mg/m³ (Cont'd. of page 5)		
LV (Cariada)	inhalable, vapour and aerosol		
LMPE (Mexico)	Long-term value: 2 mg/m³		
(A4, IFV		
91-20-3 Naphth	alene		
PEL (USA)	Long-term value: 50 mg/m³, 10 ppm		
REL (USA)	Short-term value: 75 mg/m³, 15 ppm		
	Long-term value: 50 mg/m³, 10 ppm		
TLV (USA)	Long-term value: 52 mg/m³, 10 ppm Skin; BEI		
EL (Canada)	Long-term value: 10 ppm Skin; IARC 2B		
EV (Canada)	Short-term value: 78 mg/m³, 15 ppm		
, , ,	Long-term value: 52 mg/m³, 10 ppm		
LMPE (Mexico)			
	Long-term value: 10 ppm		
F00 70 0 4 0 0 4	A4, PIEL		
	trimethylbenzene		
REL (USA)	Long-term value: 125 mg/m³, 25 ppm		
TLV (USA)	Long-term value: 123 mg/m³, 25 ppm		
	imethylbenzene		
REL (USA)	Long-term value: 125 mg/m³, 25 ppm		
TLV (USA)	Long-term value: 123 mg/m³, 25 ppm		
100-41-4 Ethylk			
PEL (USA)	Long-term value: 435 mg/m³, 100 ppm		
REL (USA)	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm		
TLV (USA)	Long-term value: 87 mg/m³, 20 ppm BEI		
EL (Canada)	Long-term value: 20 ppm IARC 2B		
EV (Canada)	Short-term value: 540 mg/m³, 125 ppm		
LMPE (Mexico)	Long-term value: 435 mg/m³, 100 ppm Long-term value: 20 ppm		
, ,	h biological limit values:		
_	100-41-4 Ethylbenzene		
	BEI (USA) 0.7 g/g creatinine		
	Medium: urine		
Time: end of shift at end of workweek			
Para	ameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)		
-			
	lium: end-exhaled air		
	e: not critical ameter: Ethyl benzene (semi-quantitative)		
	(Cont'd. on page 7)		



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 806 Top Coat

(Cont'd. of page 6)

Page: 7/13

- Exposure controls
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Avoid breathing mist, vapors, or spray.

Pregnant women should strictly avoid inhalation or skin contact.

- · Engineering controls: No relevant information available.
- Breathing equipment:

Not required under normal conditions of use.

Use suitable respiratory protective device in case of insufficient ventilation.

A NIOSH approved dust respirator should be used for operations generating dust.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· Body protection: Protective work clothing

9 Physical and chemical properties

· Limitation and supervision of exposure into the environment

Avoid release to the environment.

· Danger of explosion:

· Risk management measures No special requirements.

· Information on basic physical a	and chemical properties
· Appearance: Form: Color: · Odor: · Odor threshold:	Viscous liquid. According to product specification Not determined. Not determined.
· pH-value: · Melting point/Melting range: · Boiling point/Boiling range:	Not determined. Not determined. Not determined.
· Flash point:	43.3 °C (109.9 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.

Product does not present an explosion hazard.

(Cont'd. on page 8)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 806 Top Coat

(Cont'd. of page 7)

· Explosion limits

Lower: Not determined.

Upper: Not determined.

Oxidizing properties: Non-oxidizing.

· Vapor pressure: Not determined.

· Density:

Relative density: 1.18

Vapor density: Not determined. Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not determined.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity

Dynamic: Not determined.

Kinematic: Not determined.

· VOC content: <100 g/L

• Other information No relevant information available.

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· Possibility of hazardous reactions

Flammable liquid and vapor.

Reacts with oxidizing agents.

- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

Hydrocarbons

Silicon oxides.

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6800 mg/kg (rat)

(Cont'd. on page 9)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 806 Top Coat

		(Cont'd. of page 8)
Dermal	LD50	>3400 mg/kg (rab)
128-37-	0 2,6-0	li-tert-butyl-p-cresol
Oral	LD50	>6000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
91-20-3	•	
Oral	LD50	490 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rat)

- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Causes serious eye irritation.
- · Sensitization:

Contains 4-chloro- α , α , α -trifluorotoluene, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate. May produce an allergic reaction.

anorgio rodottori.				
· IARC (Inter	· IARC (International Agency for Research on Cancer):			
98-56-6	4-chloro-α,α,α-trifluorotoluene	2B		
13463-67-7	Titanium dioxide	2B		
91-20-3	Naphthalene	2B		
100-41-4	Ethylbenzene	2B		
· NTP (Nation	NTP (National Toxicology Program):			
91-20-3 Na	91-20-3 Naphthalene			
OSHA-Ca (Occupational Safety & Health Administration):				
None of the ingredients are listed.				

· Probable route(s) of exposure:

Ingestion.

Eve contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Suspected of causing cancer. Route of exposure: Inhalation.
- · Reproductive toxicity: Suspected of damaging fertility or the unborn child.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity

Harmful to aquatic life with long lasting effects.

98-56-6 4-cl	98-56-6 4-chloro-α,α,α-trifluorotoluene	
EC50 (dynai	EC50 (dynamic) 3 mg/kg (zebra fish)	
556-67-2 Oc	556-67-2 Octamethylcyclotetrasiloxane	
LC50	LC50 >22 mg/l (Oncorhynchus mykiss)	
EC50	EC50 >15 mg/l (daphnia)	
128-37-0 2,6-di-tert-butyl-p-cresol		

(Cont'd. on page 10)



(Cont'd. on page 11)



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 806 Top Coat

		(Cont'd. of page 9)
LC50	1.1 mg/l (fish)	
EC50	0.48 mg/l (daphnia)	
91-20-3 Naph	91-20-3 Naphthalene	
LC50	1-10 mg/l (daphnia)	
41556-26-7 bi	41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	
LC50	0.97 mg/l (lepomis macrochirus)	

- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- · Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information	
· UN-Number	
· DOT	NA1993
· ADR/RID/ADN, IMDG, IATA	UN1263
· UN proper shipping name	
· DOT	Combustible liquid, n.o.s. (4-chloro- α , α , α -trifluorotoluene, Solvent naphtha (petroleum), ligh arom.)
· ADR/RID/ADN, IMDG, IATA	PAINT
· Transport hazard class(es)	
· DOT	
a.el To.ele(O)	
· Class	3
· Label	3



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 806 Top Coat

(Cont'd. of page 10)

Page: 11/13

· ADR/RID/ADN



· Class 3 (F1)

· Label

· IMDG. IATA



· Class 3 · Label 3

· Packing group

· DOT, ADR/RID/ADN, IMDG, IATA

· Environmental hazards

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

Hazard identification number (Kemler code): 30
 EMS Number: F-E,S-E

• Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· **DOT** Classified as combustible under US DOT regulations.

Labeling is only required for single packages ≥119 US

gal / 450 L.

· ADR/RID/ADN



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· IMDG



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

·IATA



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each / 10 L net.



Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 806 Top Coat

(Cont'd. of page 11)

Page: 12/13

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

Reference to talc not applicable to product, as product contains no asbestiform fibers.

Reference to titanium dioxide is based on unbound respirable particles and is not applicable to the product

as supplied.	as supplied.		
14807-96-6	14807-96-6 Talc		
98-56-6	4-chloro-α,α,α-trifluorotoluene		
13463-67-7	Titanium dioxide		
91-20-3	Naphthalene		
100-41-4	Ethylbenzene		
· Chemicals	known to cause developmental toxicity for females:		
None of the	ingredients are listed.		
· Chemicals	known to cause developmental toxicity for males:		
None of the	None of the ingredients are listed.		
· Chemicals known to cause developmental toxicity:			
None of the ingredients are listed.			

· EPA (Environmental Protection Agency):

(
91-20-3	Naphthalene	C, CBD	
526-73-8	1,2,3-trimethylbenzene	II	
95-63-6	1,2,4-trimethylbenzene	П	
100-41-4	Ethylbenzene	D	

· IARC (International Agency for Research on Cancer):

98-56-6	4-chloro-α,α,α-trifluorotoluene	2B
13463-67-7	Titanium dioxide	2B
91-20-3	Naphthalene	2B
100-41-4	Ethylbenzene	2B

· Canadian Domestic Substances List (DSL):

All ingredients are listed or exempt.

(Cont'd. on page 13)



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Safety Data Sheet

Revision: September 14, 2020

Trade name: Pecora Deck 806 Top Coat

(Cont'd. of page 12)

Page: 13/13

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Flam. Sol. 2: Flammable solids - Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

Carc. 2: Carcinogenicity - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtel.com