

Product Submittal Sheet

Technical Services: 888-437-3244 Engineering Services: 877-832-3206

Sales: 800-543-7140 clarkdietrich.com

DEFS L-Stop Casing Bead

Provides casing against doors, windows and dissimilar materials

Designed to protect the raw edges of the board in Direct-Applied Exterior Finish Systems (DEFS). Two rows of large perforations allow the base coat mixture to easily flow through and bond to the substrate. Weep holes provide drainage away from the substrate. ClarkDietrich Keylock™ Splice connectors are available for alignment and as a base for sealant. Caulk all intersections, butt joints, ends, and corners at the time of installation.

Applications: DEFS

Product Data & Ordering Information:

Froduct Data & Ordering information.				
Product Code	Finish	Board	Perforated	PCS/Box
	Thickness	Thickness	Flange	
SBL50E	1/16"	1/2"	1-3/4"	50
SBL58E	1/16"	5/8"	1-3/4"	50
SBL100E	1/16"	1"	1-3/4"	50

ASTM & Code Standards

Product Specifications


- ASTM D1784 Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- ASTM D4216 (Cell class 13244C) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- ASTM D638 Standard Test Methods for Tensile Properties of Plastics
- · ASTM D790 Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials
- ASTM D256 Standard Test Methods for Determing the Izod Pedulum Impact Resistance of **Plastics**
- ASTM D648 Standard Test Methods for Deflection Tempurature of Plastics Under Flexural Load in the Edgewise Position
- ASTM D696 Standard Test Methods for Coefficient of Linear Thermal Expansion of Plastics Between -30 Degrees Celsius and 30 Degrees Celsius Vitreous Silicia Dilatometer
- SDS & Product Certification Information is available at www.clarkdietrich.com/SupportDocs

Storage:

Address:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

07.24.00 (Exterior Insulation & Finish Systems)





Project Information	Contractor Information	Architect Information
Name:	Name:	Name:

Fax:

Contact: Contact: Phone: Phone: Fax: