



COLPHENE 180 SP

COLPHENE 180 SP is an SBS-modified bitumen base ply for use in approved multi-ply membrane waterproofing assemblies. COLPHENE 180 SP is composed of a proprietary formulation of elastomeric styrene-butadiene-styrene (SBS) polymer modified bitumen and is reinforced with tough, dimensionally stable non-woven polyester mat. The topside is surfaced with fine mineral aggregate and underside is surfaced with polyolefin burn-off film to optimize heat welding.

PRODUCT CODE: 01219

DIMENSIONS: 49.2 ft (15.0 m) x 39.4 in (1.0m)

THICKNESS: 87 mils (2.2 mm)



COLPHENE 180 SANDED

COLPHENE 180 Sanded is an SBS-modified bitumen base ply for use in approved multi-ply membrane waterproofing assemblies. COLPHENE 180 Sanded is composed of a proprietary formulation of elastomeric styrene-butadiene-styrene (SBS) polymer modified bitumen and is reinforced with tough, dimensionally stable non-woven polyester mat. The topside and underside are surfaced with fine mineral aggregate to facilitate cold adhesive and hot asphalt applications.

PRODUCT CODE: 01207

DIMENSIONS: 49.2 ft (15.0 m) x 39.4 in (1.0m)

THICKNESS: 87 mils (2.2 mm)



COLPHENE 180 FR GR

COLPHENE 180 FR GR is an SBS-modified bitumen cap ply for use in approved multiply waterproofing assemblies. COLPHENE 180 FR GR is composed of a proprietary formulation of elastomeric styrene-butadiene-styrene (SBS) polymer modified bitumen and is reinforced with tough, dimensionally stable non-woven polyester mat. The topside is surfaced with ceramic coated granules and the underside is surfaced with fine mineral aggregate to facilitate cold adhesive and hot asphalt applications.

PRODUCT CODE: 01227

DIMENSIONS: 32.8 ft (10.0 m) x 39.4 in (1.0m)

THICKNESS: 157 mils (4.0 mm)