



EUCLID CHEMICAL

# EUCO CONCRETE FLOOR CLEANER

## CONCRETE SURFACE SALT AND LAITANCE REMOVER

### DESCRIPTION

**EUCO CONCRETE FLOOR CLEANER** is a heavy duty diammonium citrate cleaner that is highly effective at removing laitance and surface salts from concrete floors. This residue is often encountered after curing blankets have been removed from the concrete surface. Without removal of the laitance and salts and proper cleaning of the concrete floor, future applications of surface treatments such as liquid densifiers will not perform properly. EUCO CONCRETE FLOOR CLEANER is formulated as a water based solution with low VOC's.

### PRIMARY APPLICATIONS

- Removes laitance and residual salts from concrete surfaces
- Ensures a clean floor for proper penetration and performance of liquid densifier applications

### FEATURES/BENEFITS

- High strength, effective formula
- Contractor-friendly water-based formulation
- Safer to use than other types of acidic cleaners

### TECHNICAL INFORMATION

Odor ..... ammonia  
 Specific gravity ..... 1.08 ±0.10  
 Weight/gal ..... 9.01 lbs/gal (1.08 kg/L)  
 pH ..... 6 (as packaged)  
 VOC content ..... ≤5 g/L

**Appearance:** Clear liquid

### PACKAGING

EUCO CONCRETE FLOOR CLEANER is packaged in 55 gal (208 L) drums and 5 gallon (18.9 L) pails.

### SHELF LIFE

2 years in original, unopened containers

### COVERAGE

Approximately 400 ft<sup>2</sup>/gallon (9.8 m<sup>2</sup>/L), depending on dilution rate.

### DIRECTIONS FOR USE

**Verify Required Dilution Rate:** Dilute a sample of EUCO CONCRETE FLOOR CLEANER to a 1:1 ratio (by volume) with water. Apply diluted sample to concrete area to be tested. Test effectiveness of EUCO CONCRETE FLOOR CLEANER. Additional dilution rates may be required as necessary.

**Surface Salt and Laitance Removal:** Apply EUCO CONCRETE FLOOR CLEANER to floor using sprayers, automatic floor scrubbers, or other conventional methods. For cleaning and removal of surface salts and laitance, allow EUCO CONCRETE FLOOR CLEANER to dwell on the floor for 15 minutes\*. Redistribute puddles during this soak time. Add more product if necessary. After dwell time, remove salts and laitance by scrubbing the floor with water and brushes. Neutralize the EUCO CONCRETE FLOOR CLEANER with the following solution: Dissolve 1.0 lb of baking soda in 5 gal (18.9 L) of water. For use in an autoscrubber, add this solution to an additional 50 gal (189 L) of water in the scrubber tank. Wash the area with this neutralizing solution, followed by a final rinse with clean water to flush residue and any debris from the floor. \* **Times are approximate. More or less dwell time may be needed for the desired result. Excessive dwell time can result in etching of the concrete surface.**

MISCELLANEOUS

EUCO CONCRETE FLOOR CLEANER

MASTER FORMAT #:  
03 01 30.51

## CLEAN-UP

Clean tools and equipment with water.

## PRECAUTIONS/LIMITATIONS

- Always wear protective clothing (rubber gloves, eye protection, respirator, etc.). Consult the MSDS before using.
- Protect adjacent concrete slabs and polished and painted surfaces, metal and glass from exposure to EUCO CONCRETE FLOOR CLEANER.
- Do not track EUCO CONCRETE FLOOR CLEANER onto an area that is not presently being treated. Any tracked material should be removed immediately.
- Storage: EUCO CONCRETE FLOOR CLEANER is unusable if allowed to freeze. Store between 50°F to 90°F (10°C to 32°C).
- In all cases, consult the Safety Data Sheet before use.

**Caution:** While the EUCO CONCRETE FLOOR CLEANER is reacting on the concrete, there may be a mild to heavy ammonia odor; a respirator equipped with an appropriate cartridge for ammonia should be used.

Rev. 01.19

**WARRANTY:** The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.