

We maintain only the highest standards in the materials, production techniques and quality control measures used to manufacture our fasteners, assuring consistent, optimum quality in every fastener.


FASTENER TERMINOLOGY SUFFIX

K = Knurled X = Collated C = 100 count
 B = Black SD = Washer M = 1000 count
 E = Ramguard TH = Top Hat


ADVANTAGES

ITW Ramset powder actuated fasteners are specifically fabricated to meet the exacting requirements of toughness and durability that enable them to penetrate dense concrete and structural quality steel. All Ramset fasteners with .300 head will fit into tools with 8mm barrels.


SELECTION CHART

BLACK TRACK PINS		SHANK LENGTH		R25 / RA27	SA270	XT540	COBRA	MASTER CARTON QTY
	PART NUMBER	IN.	(MM)					
		1506B	3/4	(19.1)


Shank diameter = .145 Head diameter = .300

PLATED PINS		SHANK LENGTH		R25 / RA27	SA270	XT540	COBRA	MASTER CARTON QTY
	PART NUMBER	IN.	(MM)					
		1503K	1/2 Knurled	(12.7)
	1506	3/4	(19.1)	5000
	1508	1	(25.4)	5000
	1510	1-1/4	(31.8)	1000
	1512	1-1/2	(38.1)	1000
	1514	2	(50.8)	800
	1516	2-1/2	(63.5)	800
	1524	3	(76.2)	600

Shank diameter = .145 Head diameter = .300

WASHERED PINS		SHANK LENGTH		R25 / RA27	SA270	XT540	COBRA	MASTER CARTON QTY
	PART NUMBER	IN.	(MM)					
		1506SD	3/4	(19.1)
	1508SD	1	(25.4)	1000
	1510SD	1-1/4	(31.8)	1000
	1512SD	1-1/2	(38.1)	1000
	1514SD	2	(50.8)	1000
	1516SDC	2-1/2	(63.5)	600
	1524SDP*	3	(76.2)	600

**Square washer indicates 3" pin has been installed Shank diameter = .145 Head diameter = .300*

RAMGUARD PINS		SHANK LENGTH		R25 / RA27	SA270	XT540	COBRA	MASTER CARTON QTY
	PART NUMBER	IN.	(MM)					
		1516E	2-1/2	(63.5)
	1516SDE	2-1/2	(63.5)	600
	1524SDE*	3	(76.2)	600

*Shank diameter = .145 *Square washer indicates 3" pin has been installed *1500 Series Coated with RamGuard Head diameter = .300*