

AIR & VAPOR BARRIERS
SOPRASOLIN®



SOPRASOLIN HD

PRODUCT CODE

D16600/D1660009/D1660006/
D1660004/D1660003



Scan QR code with
the SOPREMA toolbox
app for more information.

SOPRASOLIN®

HD

SOPRASOLIN HD is a multi-purpose self-adhered air and vapor barrier composed of a proprietary high quality, SBS-modified bitumen membrane with an aluminum film facer. The foil facer provides heat reflectivity, fire resistance, dimensional stability, puncture resistance and high tear resistance. In addition, SOPRASOLIN HD has an exceptional 12 month UV exposure. SOPRASOLIN HD is used as a self-adhered air and vapor barrier on vertical masonry, concrete, glass faced gypsum and plywood sheathing. SOPRASOLIN HD is also used as a flashing membrane for doors, windows and transitions.

INSTALLATION

SOPRASOLIN HD may be applied to approved substrates primed with a compatible primer specifically approved by SOPREMA® for self-adhered membrane applications. Unroll, position and cut or shape SOPRASOLIN HD to needed dimensions. Set the roll by removing the release film 8 to 12 inches and adhere that exposed bitumen portion to the substrate. Once placed, remove the remaining release film by pulling at a low angle diagonal to the sheet. Press the membrane firmly with a roller and remove any air pockets.

PRODUCT PROPERTIES

THICKNESS	40 mils (1.0 mm)
TOPSIDE	Polyolefin/Aluminum Composite Film
UNDERSIDE	Release Film

APPLICATION



SELF
ADHERED

RELATED PRODUCTS

ELASTOCOL STICK
ELASTOCOL STICK H2O
ELASTOCOL STICK ZERO