

# SAFETY DATA SHEET

Issue Date 24-Apr-2015

Revision Date 10-May-2015

Version 2

## **1. IDENTIFICATION**

Product identifier Product Name

Henry 203 Roll Roofing Adhesive

Other means of identification Product Code Synonyms

HE203 None

Recommended use of the chemical and restrictions on useRecommended UseSealant.Uses advised againstNo information available

Details of the supplier of the safety data sheet Manufacturer Address HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Company Contact: Technical Services Telephone Number: 800-486-1278 Web Site: www.henry.com www.ca.henry.com

# Emergency telephone number

Emergency Telephone

CHEMTREC: 800-424-9300 CHEMTREC: 703-527-3887 CANUTEC: 613-966-6666

# 2. HAZARDS IDENTIFICATION

## Classification


#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute toxicity - Inhalation (Gases)	Not classified
Acute toxicity - Inhalation (Vapors)	Not classified
Acute toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Not classified
Skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Flammable liquids	Category 3

#### Label elements

#### **Emergency Overview**



#### **Precautionary Statements - Prevention**

Wear protective gloves/protective clothing/eye protection/face protection Keep away from heat/sparks/open flames/hot surfaces. - No smoking Wash face, hands and any exposed skin thoroughly after handling

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention IF INHALED: Call a POISON CENTER or doctor if you feel unwell In case of fire: Use Water spray, fog or regular foam for extinction

Hazards not otherwise classified (HNOC)

Not applicable

Other Information Harmful to aquatic life with long lasting effects

Unknown acute toxicity

29.97% of the mixture consists of ingredient(s) of unknown toxicity

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

## Substance

Chemical Name	CAS No.	Weight-%	Trade Secret
Petroleum Asphalt	8052-42-4	60-100	*
Calcium carbonate	1317-65-3	5-15	*
Stoddard solvent	8052-41-3	10 - 30	*
1,2,4 Trimethylbenzene	95-63-6	0.1 - 1	*
QUARTZ	14808-60-7	<0.1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

## Description of first aid measures

Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids Consult a physician.		
Skin contact	Wash skin with soap and water.		
Inhalation	Remove to fresh air.		
Ingestion	Clean mouth with water and drink afterwards plenty of water.		
Most important symptoms and	d effects, both acute and delayed		
Symptoms	Drowsiness.		
Indication of any immediate m	edical attention and special treatment needed		
Note to physicians	Treat symptomatically.		
	5. FIRE-FIGHTING MEASURES		
Sensitivity to Static Discharge None.			
Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.			
6. ACCIDENTAL RELEASE MEASURES			
Personal precautions, protecti	Personal precautions, protective equipment and emergency procedures		
Personal precautions	Ensure adequate ventilation, especially in confined areas.		
Environmental precautions			

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

# 7. HANDLING AND STORAGE

# Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice.

## Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials

Strong oxidizing agents.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### **Exposure Guidelines**

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum Asphalt	TWA: 0.5 mg/m <sup>3</sup> benzene soluble	-	Ceiling: 5 mg/m <sup>3</sup> fume 15 min
8052-42-4	aerosol fume, inhalable fraction		
Calcium carbonate	-	TWA: 15 mg/m <sup>3</sup> total dust	TWA: 10 mg/m <sup>3</sup> total dust
1317-65-3		TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> respirable dust
		(vacated) TWA: 15 mg/m <sup>3</sup> total	
		dust	
		(vacated) TWA: 5 mg/m <sup>3</sup> respirable	
		fraction	
Stoddard solvent	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m <sup>3</sup>
8052-41-3		TWA: 2900 mg/m <sup>3</sup>	Ceiling: 1800 mg/m <sup>3</sup> 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m <sup>3</sup>
		(vacated) TWA: 525 mg/m <sup>3</sup>	
1,2,4 Trimethylbenzene	-	-	TWA: 25 ppm
95-63-6			TWA: 125 mg/m <sup>3</sup>
QUARTZ	TWA: 0.025 mg/m <sup>3</sup> respirable	(vacated) TWA: 0.1 mg/m <sup>3</sup>	IDLH: 50 mg/m <sup>3</sup> respirable dust
14808-60-7	fraction	respirable dust	TWA: 0.05 mg/m <sup>3</sup> respirable dust
		: (30)/(%SiO2 + 2) mg/m <sup>3</sup> TWA	
		total dust	
		: (250)/(%SiO2 + 5) mppcf TWA	
		respirable fraction	
		: (10)/(%SiO2 + 2) mg/m <sup>3</sup> TWA	
		respirable fraction	

#### Appropriate engineering controls

**Engineering Controls** 

#### Showers Eyewash stations Ventilation systems.

#### Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective gloves and protective clothing.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state	liquid
Appearance	paste
Color	black

Odor Odor threshold Petroleum distillates No information available

Property pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas) Flammability Limit in Air Upper flammability limit: Lower flammability limit:	ValuesNo information availableNo information available>= 150 °C40 °CNo information availableNo information available9%1%	<u>Remarks</u>	• Method
Vapor pressure Vapor density Relative density Water solubility Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties	No information available No information available 0.9 - 1.3 No information available No information available No information available No information available >100 mm2/s No information available No information available No information available	@ 40 °C	
Other Information Softening point Molecular weight VOC Content (%) Density Bulk density	No information available No information available No information available No information available No information available		

# **10. STABILITY AND REACTIVITY**

# Reactivity

No data available

<u>Chemical stability</u> Stable under recommended storage conditions. <u>Possibility of Hazardous Reactions</u> None under normal processing. <u>Conditions to avoid</u> Extremes of temperature and direct sunlight. <u>Incompatible materials</u> Strong oxidizing agents. <u>Hazardous Decomposition Products</u> None known based on information supplied.

# **11. TOXICOLOGICAL INFORMATION**

# Information on likely routes of exposure

Product Information	No data available
Inhalation	May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.

Ingestion

No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum Asphalt 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
1,2,4 Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m <sup>3</sup> (Rat)4 h
QUARTZ 14808-60-7	= 500 mg/kg (Rat)	-	-

#### Information on toxicological effects

Symptoms

Vapors may cause drowsiness and dizziness.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicity Carcinogenicity	No information No information No information			
Chemical Name	ACGIH	IARC	NTP	OSHA
Petroleum Asphalt 8052-42-4	-	Group 2B	-	Х
QUARTZ 14808-60-7	A2	Group 1	Known	Х
Reproductive toxicity STOT - single exposure STOT - repeated exposure Aspiration hazard	No information available. No information available. No information available. No information available.			

## Numerical measures of toxicity - Product Information

ATEmix (oral)	5,602.00
ATEmix (dermal)	5,602.00
ATEmix (inhalation-gas)	99,999.00
ATEmix (inhalation-dust/mist)	14.01
ATEmix (inhalation-vapor)	99,999.00

# **12. ECOLOGICAL INFORMATION**

## Ecotoxicity

49.4 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

# Persistence and degradability

Not readily biodegradable.

## **Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Petroleum Asphalt 8052-42-4	>6
1,2,4 Trimethylbenzene 95-63-6	3.63

Other adverse effects Ozone No information available Not applicable

# **13. DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Disposal	of	wastes
----------	----	--------

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

# 14. TRANSPORT INFORMATION

DOT	Not regulated (If shipped in NON BULK packaging by ground transport)
TDG_	Not regulated
<u>IATA</u> UN/ID no. Proper shipping name Hazard Class Packing Group	UN1999 Tars, Liquid 3 III
IMDG UN/ID no. Proper shipping name Hazard Class Packing Group Description	UN1999 Tars, Liquid 3 III May be transported as non-hazardous in accordance with IMDG 2.3.2.5

## **15. REGULATORY INFORMATION**

All components used in this product are on the TSCA Inventory and the Canadian DSL.

#### International Inventories

Complies
Complies
Complies
Does not comply
Complies
Complies
Complies
Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances AICS - Australian Inventory of Chemical Substances

## US Federal Regulations

## <u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA	311/312	Hazard	Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

## **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

#### US State Regulations

#### California Proposition 65

This product contains chemicals known to the state of California to cause birth defects or other reproductive harm

#### U.S. State Right-to-Know Regulations

#### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection X

24-Apr-2015 10-May-2015

**Revision Note** No information available

Disclaimer

**Issue Date** 

**Revision Date** 

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### End of Safety Data Sheet