

STRiON:FORTIFY

IMPREGNATING HARDENER, DENSIFIER, DUSTPROOFER

**Convergent Concrete
Technologies, LLC**

Specialty Chemical Concrete Treatments

Headquarters:

115 North 1380 West
Orem, Utah 84057
USA

Call Customer Service:

1-801-375-2280
or Toll Free 1-866-375-2280

For Chemical/Medical Emergencies:

Infotrac 1-800-535-5053
Outside USA 1-352-323-3500

Email us:

info@convergentconcrete.com

Visit us online:

www.convergentconcrete.com



PRODUCT DESCRIPTION

STRiON:FORTIFY uses a groundbreaking new silica-free technology to create the most user-friendly concrete densifier that has ever been available. The resulting concrete surface offers everything you'd want in a densifier: hard, dense, easy to polish or burnish, dustproof, and simple to clean. Yet its application process is near-foolproof. Through its sheer simplicity, STRiON:FORTIFY saves time and money by eliminating misapplication mistakes.

Not only is it remarkably easy to apply, but it can be applied at temperatures as low as 25°F—and no rinsing is required, making it not only simple but also easy on the environment. It can be applied to freshly placed concrete and tilt-up construction slabs, and it can also be used on existing concrete surfaces and cementitious overlays as well.

STRiON:FORTIFY creates an extremely hard surface that is less porous, yet breathable. When applied to new concrete, its small molecules thoroughly penetrate the surface and an ionic reaction creates insoluble calcium-silicate hydrates. This makes concrete more abrasion-resistant, which allows abrasive tooling to create a superior polish and makes maintenance easier throughout the concrete's long life.

KEY BENEFITS

- Extremely simple application, with no rinsing required
- Hardens concrete and terrazzo while preserving the surface's natural look
- Penetrates, with no film to lift or peel off, and allows abrasive tooling to work more effectively
- May be applied in temperatures as low as 25°F
- Does not contribute to surface ASR or surface crazing
- Resists dusting, making concrete easier to maintain
- VOC compliant, may contribute to LEED points (IEQ credit)

Call Customer Service:

1-801-375-2280
or Toll Free 1-866-375-2280

For Chemical/Medical Emergencies:

Infotrac 1-800-535-5053
Outside USA 1-352-323-3500

Email us:

info@convergentconcrete.com

Visit us online:

www.convergentconcrete.com

**USES**

Power-Troweled Concrete, Tilt-Up Construction Slabs, Grocery Stores, Parking Garages, Fire Stations, Sidewalks, Driveways, Loading Docks, Aircraft Hangars, Automotive Dealerships, Shipping Terminals, Vehicle Maintenance Areas, Office Buildings, Healthcare Facilities, Cafeterias/Restaurants, Correctional Institutions, Retail & Shopping Centers, Schools, Stadiums, Veterinary Clinics, Common Areas, Laboratories, Lobbies, Mechanical Rooms, Mezzanines, Manufacturing Facilities, Warehouses, Storage, Distribution Centers, Food Processing Plants, Textile Mills, Wastewater Treatment Plants, Pharmaceutical Plants, Electronic Facilities, Cold Storage/Freezers, Beverage Bottling Plants, Chemical Processing Plants, etc.

APPLICATION

May be applied as low as 25°F. Using a sprayer, apply STRiON:FORTIFY evenly on the surface. Keep the surface wet with product for at least 20 minutes, adding more product where needed. If product is being used during the polishing process, apply after the last cutting step, then wait until the concrete is no longer wet on the surface. You can then continue grinding and polishing to the intended final surface profile and desired finish.

On existing concrete, clean surface before application to remove any dirt, laitance, curing compounds or coatings that may prevent STRiON:FORTIFY from penetrating the surface. Do not use citrus or acidic cleaners. If acidic or d-limonene cleaners have been used, neutralize the surface using an alkaline cleaner (TSP, Tide laundry detergent, etc.). A slight residue may occur after application. If it does, it removes very easily with water.

The surface is ready for use when dry to touch.

**It may be necessary to spray water on hot concrete with a surface temperature above 90°F (32°C) to cool the surface prior to application so STRiON:FORTIFY does not flash-dry on the surface. Proceed with product application once the surface is dry.*

**Before application, always do a small test sample in a less-visible area to be sure there are no variables or contaminants in the substrate that may be incompatible with this product.*

ESTIMATED COVERAGE

Machine-troweled: 450-650 ft² per gallon (11-16 m² per liter)

**Coverage rate will vary with concrete porosity and environmental conditions.*

CLEAN UP

Use soap and water to clean tools and equipment. Although STRiON:FORTIFY is non-toxic and environmentally safe, use up or dry out extra material and dispose of it according to local regulations. Do not pour into sewer systems or storm drains.

MAINTENANCE

Clean with Pentra-Clean™ (CR), Pentra-Clean™ (DC) or neutral pH cleaners as needed. If additional protection or gloss is desired, apply Pentra-Finish™ (HG), or Pentra-Guard® (EXT). Consult a Convergent Concrete Representative for further information.

Call Customer Service:

1-801-375-2280

or Toll Free 1-866-375-2280

For Chemical/Medical Emergencies:

Infotrac 1-800-535-5053

Outside USA 1-352-323-3500

Email us:

info@convergentconcrete.com

Visit us online:

www.convergentconcrete.com

**SAFETY/HEALTH INFORMATION**

KEEP OUT OF REACH OF CHILDREN.

Do not drink. If swallowed, do not induce vomiting; drink two glasses of water and call a physician. Wear goggles and gloves. If splashed in eyes, rinse eyes immediately with clean water and call a physician if irritation persists. Clean skin with soap and water. CAUTION: Surfaces wet with STRiON may be slippery. Additional precautions, safety information and first aid treatments are contained in the Safety Data Sheet.

PROPERTIES

Form: Liquid

Color: Clear - Colorless

Odor: Slight to none

Concentration: 10-12%

Specific Gravity: 1.044 @ 68°F

pH: 6.6

VOC Content: <50g/L

Flash Point: N/A

Freeze Point: 25°F (-3.8°C)

Shelf Life: 1 year in unopened, sealed container

PACKAGING

1-Gal Jug • 3.785 L

5-Gal Pail • 18.93 L

55-Gal Drum • 208.20 L

275-Gal Tote (IBC) • 1040 L

LIMITATIONS

STRiON:FORTIFY will not bridge or fill cracks or voids and will not salvage honeycombed or structurally unsound surfaces. Not suitable for asphalt, non-cement surfaces or painted surfaces.

If STRiON:FORTIFY comes into contact with glass, fabric, metal, or painted surfaces, immediately wipe contaminated surfaces with a damp cloth, then wipe dry with a second clean cloth.

Make certain the most current versions of the STRiON:FORTIFY Product Data Sheet and SDS are being used. Call Customer Service (1-866-375-2280) or visit our website (www.convergentconcrete.com) to find additional tips, guidelines and specifications. Proper application is the responsibility of the user. Field visits by Convergent Concrete Personnel are for the purpose of making technical recommendations only and not for supervising or providing quality control on the job site.

Call Customer Service:

1-801-375-2280
or Toll Free 1-866-375-2280

For Chemical/Medical Emergencies:

Infotrac 1-800-535-5053
Outside USA 1-352-323-3500

Email us:

info@convergentconcrete.com

Visit us online:

www.convergentconcrete.com



WARRANTY

The product and application information contained herein is offered in good faith and we believe it to be accurate. However, since conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent. Convergent Concrete Technologies, LLC's sole warranty is that our products will meet our specifications at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

CONVERGENT CONCRETE TECHNOLOGIES, LLC. SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. CONVERGENT DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Refer to www.convergentconcrete.com for latest Technical Data Sheet and SDS.

STRiON™ is a trademark of Advanced Concrete Technologies, LLC ("ADVAN") and sub-licensed to Convergent Concrete Technologies, LLC, under a non-exclusive co-brand/technology license. All rights reserved. ADVANCED CONCRETE TECHNOLOGIES, LLC makes no claim as to the product performance or product shown to be other than as warranted.



UNIQUE STRENGTHS, UNMATCHED PERFORMANCE™