

# 3M™ Dual Lock™ Reclosable Fasteners and Applications

Product	Stem Density (per sq/in)	Adhesive	Color	3M Liner	Engaged Thickness	Temperature Resistance	Substrates				Use	Markets										
							Metals (Al & SS)	Glass	Plastics (Acrylic, PC, ABS)	Powder Coated Paints		Low Surface Energy (PP, PE)	Indoor/Outdoor	Aerospace & Rail	Appliance & Electronics	Design & Construction	Furniture & Upholstery	General Industrial	Marine & Specialty Vehicle	POP, Display & Signage		
SJ3540	250	Rubber	Black	White, 5mil (0.13mm) Polyolefin	0.23 in (5.7mm)	120°F (49°C)	■		■	■	■	Indoor				■	■		■			
SJ3541	400						■		■	■	■	Indoor/Outdoor	■	■	■	■	■	■				■
SJ3542	170						■		■	■	■	Indoor/Outdoor	■	■	■	■	■	■	■	■	■	■
SJ3550	250	White Acrylic	Black	Clear, 4mil (0.10mm) Polyolefin	0.23 in (5.7mm)	200°F (93°C)	■	■	■	●	●	Indoor/Outdoor	■	■	■	■	■	■	■			
SJ3551	400						■	■	■	●	●	Indoor/Outdoor	■	■	■	■	■	■	■	■	■	
SJ3552	170						■	■	■	●	●	Indoor/Outdoor	■	■	■	■	■	■	■	■	■	
SJ3558	250	White Acrylic	Clear*	Clear, 4mil (0.10mm) Polyolefin	0.23 in (5.7mm)	200°F (93°C)	■	■	■	●	●	Indoor/Outdoor		■	■	■	■	■	■			
SJ3560	250	Clear Acrylic	Clear	Clear, 4mil (0.10mm) Polyolefin	0.23 in (5.7mm)	220°F (104°C)	■	■	■	●	●	Indoor/Outdoor		■	■	■	■	■	■			
SJ3561	400						■	■	■	●	●	Indoor/Outdoor		■	■	■	■	■	■	■	■	
SJ3562	170						■	■	■	●	●	Indoor/Outdoor		■	■	■	■	■	■	■	■	
SJ3550CF	250	Clear Acrylic	Black	Clear, 4mil (0.10mm) Polyolefin	0.23 in (5.7mm)	220°F (104°C)	■	■	■	●	●	Indoor/Outdoor		■	■	■	■	■	■			
SJ3551CF	400						■	■	■	●	●	Indoor/Outdoor		■	■	■	■	■	■	■	■	
SJ3552CF	170						■	■	■	●	●	Indoor/Outdoor		■	■	■	■	■	■	■	■	
SJ3870	250	Modified Acrylic	Black	Red, 4.5mil (0.11mm) Polyolefin	0.24 in (6.1mm)	140°F (60°C)	■		■	■	●	Indoor/Outdoor				■	■		■			
SJ3871	400						■		■	■	●	Indoor/Outdoor				■	■		■	■		
SJ3872	170						■		■	■	●	Indoor/Outdoor				■	■		■	■		
SJ3782	250	Low Surface Energy Acrylic	Black	Brown, 83# Polykraft	0.16 in (4.1mm)	120°F (49°C)	■		■	■	■	Indoor/Outdoor		■	■	■	■	■	■			
SJ3440	250	None	Black	No Liner	0.15 in (3.86mm)	220°F (104°C)	▲	▲	▲	▲	▲	Indoor/Outdoor			▲	▲	▲	▲	▲			
SJ3441	400						▲	▲	▲	▲	▲	Indoor/Outdoor			▲	▲	▲	▲	▲	▲	▲	
SJ3442	170						▲	▲	▲	▲	▲	Indoor/Outdoor			▲	▲	▲	▲	▲	▲	▲	
SJ3443	400	Non-woven backing with no adhesive	Black	No Liner	0.28 in (7.1mm)	220°F (104°C)	▲	▲	▲	▲	▲	Indoor/Outdoor			▲	▲	▲	▲	▲			
SJ3444	170						▲	▲	▲	▲	▲	Indoor/Outdoor			▲	▲	▲	▲	▲	▲	▲	
SJ3445	250						▲	▲	▲	▲	▲	Indoor/Outdoor			▲	▲	▲	▲	▲	▲	▲	
SJ3460	250	None	Clear	No Liner	0.15 in (3.86mm)	220°F (104°C)	▲	▲	▲	▲	▲	Indoor/Outdoor		▲	▲	▲	▲	▲	▲			
SJ3463	400	Piece Part Circle†	Black	No Liner	0.20 in** (5.1mm)	220°F (104°C)	■		■	■	■	Indoor/Outdoor		■	■	■	■	■	■			
SJ3481	400	Rigid Strip†	Black	No Liner	0.20 in** (5.1mm)	220°F (104°C)	▲	▲	▲	▲	▲	Indoor/Outdoor		▲	▲	▲	▲	▲	▲			
SJ4570	Low Profile/Thin	Low Surface Energy Acrylic	Clear	Brown, 83# Polykraft	0.098 in (2.489mm)	158°F (70°C)	■		■	■	■	Indoor/Outdoor		■	■	■	■	■	■			
SJ4575			Black				■		■	■	■	Indoor/Outdoor		■	■	■	■	■	■	■	■	
SJ4580		Clear Acrylic	Clear	Red, 4.5mil (0.11mm) Polyolefin	0.12 in (3.0mm)	200°F (93°C)	■	■	■	●	●	Indoor/Outdoor		■	■	■	■	■	■			

\*Clear fastener utilizes a white adhesive giving the product a white appearance \*\*Single thickness; not engaged †No adhesive

- Best Suggested Product
- Primer Recommended
- ▲ Performance Dependent on the Selected Attachment Method

Many of our 3M™ Dual Lock™ Reclosable Fasteners feature 3M™ VHB™ Tape which adds extraordinary holding power and aging properties through a range of environmental impacts; non-adhesive product also available.

Mix and match stem densities (stems per square inch) to customize for the strength requirements of your project.

Stem Density (per sq/in) Combinations	
<b>Strongest</b>	250:400
<b>Stronger</b>	250:250 or 170:400
<b>Strong</b>	170:250
<b>Not Recommended</b>	170:170 or 400:400

Interchangeable Strength Combinations			Self-Mating
Type 400	Type 250	Type 170	Low Profile