



# HE572 - BLUESKIN SPRAY PREP - AEROSOL

Last Rev Date: 02/13/2017

Physical Properties		
Application Temperature 10°F to 104°F	<b>Drying Time (Set through)</b> 20 minutes	Service Temperature, cured bead -40°F to 158° F
Color Clear amber	Flammability Wet-Flammable, Dry-Burns	Solids By Weight 35%
Drying Time (Initial set) 3 minutes		

#### Description

**HE572 - BLUESKIN SPRAY PREP - AEROSOL** is a spray adhesive used to prepare construction surfaces for the application of **Blueskin® Self-Adhesive Membrane**.

#### Features:

- · Quick setting
- · Agressive tack provides adhesion of membrane
- Suitable for application at normal and low temperatures
- · Easily applied

# Usage

**HE572 - BLUESKIN SPRAY PREP - AEROSOL** is used as a spray adhesive for self-adhesive membranes such as **Blueskin® SA, WP200** or **RF200** when applied to masonry, concrete, wood, exterior grade gypsum board, DensGlass® and metal surfaces.

**Blueskin® Spray Prep** is ideal where a very fast drying adhesive is required. Convenient spray can application eliminates the need for brushes or rollers. Three minute tack time.

Designed for applications above -10°F.

**Limitations**: Solvent in product attacks polystyrene insulation. Avoid use where solvent odors may taint food or other susceptible products.

# Coverage

30 to 50 sq. ft./can depending on porosity and texture of surface.

## **Surface Preparation**

Surfaces must be dry and free from dust, dirt, grease, oil or other foreign matter.

## **Application**

Shake can vigorously until ball rattles freely. Apply a uniform film to a clean, dry surface. Allow adhesive to tack up for 3 minutes before applying **Henry Blueskin® Self-Adhesive Membrane**. Apply a firm pressure to the membrane to ensure firm contact with the substrate. After spraying, turn can upside down, point nozzle into refuse can or at paper and push spray head for about 2 seconds to clear valve. For clean-up or if valve clogs, remove from can and clean in paint thinner or mineral spirits.

#### **Precautions**

DO NOT THIN.

#### Cleanup

Clean up with mineral spirits.

#### Caution

**DANGER. EXTREMELY FLAMMABLE AEROSOL.** Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

**Prevention**: Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Keep containers tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Contaminated clothing should not be allowed out of the work place. Avoid breathing vapors, mists, and sprays. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection.

Response: In case of fire, use alcohol foam, carbon dioxide (CO2), or dry chemical to extinguish. IF ON SKIN: Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs; Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Storage: Store locked up. Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/containers in accordance with local/regional/national/international regulations.

See safety data sheet for further details regarding the safe use of this product.

KEEP OUT OF REACH OF CHILDREN.

FOR EXTERIOR USE ONLY, FOR INDUSTRIAL USE ONLY.

**WARNING:** This product contains detectable amounts of chemicals known to the State of California to cause cancer, and/or birth defects or other reproductive harm.

## **Product Sizes**

15OZ AEROSOL CAN (1.42 lb)

#### **Limited Warranty**

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. <u>DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY:</u> THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE.

MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.