



Tremco Commercial Sealants & Waterproofing
3735 Green Road
Beachwood, OH 44122
US: 800.852.9068
Canada: 800.363.3213
www.tremcosealants.com



September 30, 2020

To Whom It May Concern:

RE: TremPro 640—Green Building Product Information (LEED v4.1 Information)

Tremco Incorporated is an organization that is committed to quality, our employees, and our environment. We are responsive to both internal and external customers, and we pledge to treat everyone with good stewardship and respect.

Tremco Incorporated certifies the following for TremPro 640:

Building Product Disclosure and Optimization:

TremPro 640 is manufactured in Cleveland, Ohio.

No single extracted material is used to produce the majority of this product.

Recycled content for TremPro 640 is not available, and for the purposes of LEED reporting should be assumed to be zero.

Low Emitting Materials - VOC Content Information:

TremPro 640 is a coating with a VOC content of 193g/L equaling 16.08% as applied/mixed. As such, VOC levels are higher than the limits set by SCAQMD rule 1113.

Green Chemistry:

Tremco Incorporated is dedicated to the environment and prides itself on making its products as sustainable as possible. We are pleased to report that this product is produced without any Red List chemicals. As such, it can be used to assist in finishing projects aimed towards achieving a Living Building Challenge certification.



Tremco Commercial Sealants & Waterproofing
 3735 Green Road
 Beachwood, OH 44122
 US: 800.852.9068
 Canada: 800.363.3213
 www.tremcosealants.com

Manufacture Inventory (reported to 1000ppm):

Chemical Name or Role	CAS Number	Amount	GHS Hazard
Polyurethane Prepolymer		20-60%	Non-Hazardous
Calcium Carbonate (Limestone)	1317-65-3		
Plasticizer		<15%	Non-Hazardous
Titanium dioxide	13463-67-7		
Aluminum	7429-90-5		
Calcium oxide	1305-78-8		
Rheological Additive		<5%	Non-Hazardous
Hydrotreated heavy naphtha	64742-48-9		
UV Stabilizer		<1%	Non-Hazardous
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7		
4,4'-Methylene bis(phenylisocyanate)	101-68-8		
Hydrotreated heavy naphthenic distillate	64742-52-5		
Dibutyl tin dilaurate	77-58-7		
Sealant		<1%	Non-Hazardous
Tosyl isocyanate	4083-64-1		
Amorphous silica	7631-86-9		
Solvent		<1%	Non-Hazardous
Polymethylene polyphenyl isocyanate	9016-87-9		
Surface Active Agent		<1%	Non-Hazardous
Aluminum hydroxide	21645-51-2		
2,4-Toluene diisocyanate	584-84-9		
Aluminum oxide	1344-28-1		

Additional Information:

Should you have any questions or require additional information, please do not hesitate to contact Technical Services or your local Tremco Field Representative.

Sincerely,

Joe Kravetz
 Product Steward
 Compliance and Regulatory Affairs