L&M[™] AQUAPEL[™]

Refer to Data Sheet 173.6 8-28-551-1214/8-28-551-1214/ 8-28-551-1210/8-28-551-1211



 $L\&M^{\mathbb{M}}$ AQUAPEL^{\mathbb{M}} is a new generation, 100% reactive, waterborne silane-siloxane sealer.

L&M AQUAPEL PLUS™

Refer to Data Sheet 173.5 8-28-553-1219/8-28-553-1218



L&M AQUAPEL PLUS^m is a sealer designed for increased long-term protection on porous concrete, elevated structural traffic bearing concrete slabs, and on normal concrete with severe exposure to salt and water.

FEATURES/BENEFITS:

- Easy to apply
- Protects against salt and water intrusion
- Improves the life of concrete
- Prevents pop-outs, pitting, scaling, and spalling
- Low VOC

FEATURES/BENEFITS:

- Easy to apply, high solids formulation
- Protects against salt and water intrusion
- Use on horizontal or vertical surfaces
- Improves the life of concrete
- Prevents pop-outs, pitting, scaling, and spalling
- Low VOC

PACKAGING:

5 gal (18.9 L)

55 gal (208 L)

PACKAGING:

4 x 1 gal (3.8 L) 5 gal (18.9 L) 55 gal (208 L)

APPROXIMATE COVERAGE

Additional coats may be necessary under certain porous conditions. Typical coverage rates, depending upon substrate porosity and anticipated conditions are:

Brick	100-125 ft²/gal (2.4-3.1 m²/L)
Porous surfaces	125-150 ft²/gal (3.1-3.7 m²/L)
Broom finish	125-175 ft²/gal (3.1-4.3 m²/L)
Smooth concrete	150-200 ft²/gal (3.7-4.9 m²/L)
Densified concrete	200-300 ft²/gal (4.9-7.3 m²/L)



APPROXIMATE COVERAGE

Additional coats may be necessary under certain porous conditions. Typical coverage rates, depending upon substrate porosity and anticipated conditions are:

Porous surfaces	125-150 ft²/gal (3.1-3.7 m²/L)
Broom finish	125-175 ft²/gal (3.1-4.3 m²/L)
Smooth concrete	150-200 ft²/gal (3.7-4.9 m²/L)
Densified concrete	200-300 ft²/gal (4.9-7.4 m²/L)

