

The listed systems are typical applications only. Please refer to the volume of your 3M specification guide for your specific application or use the 3M System Selector available at 3M.com/firestop

Fire Barrier Water Tight Sealants & Tape

3M™ Fire Barrier Water Tight Sealant 3000 WT

3M™ Fire Barrier Water Tight Sealant 3000 WT Intumescent Sealant forms an effective barrier to fire and water in through penetrations. This high-performance sealant helps prevent water and moisture intrusion while protecting buildings and their occupants by preventing the spread of fire, smoke and toxic gas.

- Intumescent silicone for use in systems with a firestop rating up to 4 hours when tested in accordance with ASTM E 814 (UL1479)
- Meets UL Water Leakage Test, W Rating: Class 1 requirements for systems tested in accordance with ANSI/UL 1479
- Helps prevent moisture and water migration through a building
- Minimizes noise transfer: STC-rating of 53 when tested in STC 54-rated wall assembly
- Excellent weathering properties
- Ideal for fast-track construction
- Easy application with standard caulking gun or pneumatic pump
- Excellent bonding
- Gray color with black flecks



FIRE BARRIER	SMOKE SEAL	WATER BARRIER	SOUND BARRIER
UP TO 4 HOUR Fire Protection	L RATED Meets Optional L Requirements	UL CLASS 1W Rating UL Water Leakage	STC 53 In STC 54-rated Wall Assembly



3M™ Fire Barrier Water Tight Sealant 1000 NS and 3M™ Fire Barrier Water Tight Sealant 1003 SL

3M™ Fire Barrier Water Tight Sealant 1000 NS (non-slump) and 3M™ Fire Barrier Water Tight Sealant 1003 SL Silicone Sealant (self-leveling) are ready to use, one-component silicone elastomers. Both cure upon exposure to atmospheric humidity to form a flexible seal. Both sealants remain elastomeric and are weather resistant. They bond to most common construction materials.

- Firestop tested up to 3 hours in accordance with ASTM E 814 (UL 1479)
- Joint System Fire Resistance tested in accordance with ASTM E 1966 (UL 2079)
- Meets UL Water Leakage Test, W Rating: Class 1 requirements
- Minimizes noise transfer: STC-rating of 56 when tested in STC 56-rated wall assembly
- ±25% dynamic joint movement capability
- Excellent adhesion
- Cures upon exposure to atmospheric humidity
- Applied with conventional caulking equipment
- Re-enterable/repairable
- Aids in the prevention of moisture and water migration through a building
- Light gray color



FIRE BARRIER	WATER BARRIER	SMOKE SEAL	SOUND BARRIER	ELASTOMERIC
UP TO 3 HOUR Fire Protection	UL CLASS 1W Rating UL Water Leakage	L RATED Meets Optional L Requirements	STC 56 In STC 56-rated Wall Assembly	± 25% Movement Capability



3M™ Fire and Water Barrier Tape FWBT

3M™ Fire and Water Barrier Tape is a self-adhered membrane that provides a tough, elastomeric coating. This product has a unique pressure sensitive adhesive that aggressively sticks and stays stuck to a wide variety of substrates at both high and low temperatures, and will even adhere to damp surfaces.

- Up to 4-hour fire protection in construction joints per ASTM E 1966 (UL 2079)
- Up to 3-hour fire protection in perimeter joints per ASTM E 2307
- Up to 2-hour fire protection in through-penetration applications per ASTM E 814 (UL 1479)
- Elastic material maintains performance with up to ±50% movement capabilities
- Can be installed in temperatures as low as 0°F (18°C) and as high as 120°F (49°C)



Construction Joint Spray & Sealants (cont.)

3M™ Fire Barrier Water Tight Sealant 1000 NS and 3M™ Fire Barrier Water Tight Sealant 1003 SL

3M™ Fire Barrier Water Tight Sealant 1000 NS (non-slump) and 3M™ Fire Barrier Water Tight Sealant 1003 SL Silicone Sealant (self-leveling) are ready to use, one-component silicone elastomers. Both cure upon exposure to atmospheric humidity to form a flexible seal. Both sealants remain elastomeric and are weather resistant. They bond to most common construction materials.

- Firestop tested up to 3 hours in accordance with ASTM E 814 (UL 1479)
- Joint System Fire Resistance tested in accordance with ASTM E 1966 (UL 2079)
- Meets UL Water Leakage Test, W Rating: Class 1 requirements
- Minimizes noise transfer: STC-rating of 56 when tested in STC 56-rated wall assembly
- ±25% dynamic joint movement capability
- Excellent adhesion
- Cures upon exposure to atmospheric humidity
- Applied with conventional caulking equipment
- Re-enterable/repairable
- Aids in the prevention of moisture and water migration through a building
- Light gray color



FIRE BARRIER	WATER BARRIER	SMOKE SEAL	SOUND BARRIER	ELASTOMERIC
UP TO 3 HOUR Fire Protection	MEETS CLASS 1W Rating UL Water Leakage	L RATED Meets Optional L Requirements	STC 56 In STC 56-rated Wall Assembly	± 25% Movement Capability

3M™ Fire Barrier Watertight Spray



3M™ Fire Barrier Watertight Spray is a sprayable, moisture-curing hybrid siliconized polymer that forms a tough, elastomeric coating. This material is used to firestop perimeter joints (curtain wall) and construction joints.

- Up to 3-hour fire protection in construction joints per ASTM E 1966 (UL 2079)
- Up to 3-hour fire protection in perimeter joints per ASTM E 2307
- Elastic material maintains performance with up to ±10% movement capabilities
- Paintable with primer
- Broad range of applications (extensive portfolio of tested and listed building and perimeter joint systems)
- Improved spraying pattern: applied with conventional airless spray equipment
- Robust jobsite formula (freeze/thaw resistant and uniform seal formation in hot or cold conditions)











































Ordering Information















3M™ Fire Barrier Rated Foam FIP 1-Step

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
FIP 1-Step	Firestop Foam Up to 2-hr Penetration Firestop	12.85 oz.		 Cartridge	0-00-51115-54925-0	1/Cs	Each
Mixing Nozzles	Mixing Nozzles	—	—	Nozzle	0-00-51115-54933-0	5/Cs	Bag
Albion® Manual Dispenser Gun	Manual gun for 3M™ Fire Rated Foam FIP 1-Step	—	—	Gun	0-00-76308-14612-2	1/Cs	Each
Albion® Power Dispenser Gun	Power gun for 3M™ Fire Rated Foam FIP 1-Step	—	—	Gun	0-00-76308-14610-8	1/Cs	Each
	18V Li-ion Battery	—	—	Battery	0-00-76308-14614-6	1/Cs	Each

3M™ Fire Barrier Sealants

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
CP 25WB+	Up to 4-hr Penetration Firestop	10.1 oz.		 Tube	0-00-51115-11638-4	12/Cs	Each
	Up to 4-hr Penetration Firestop	20 oz.		 Sausage	0-00-51115-11642-1	10/Cs	Each
	Up to 4-hr Penetration Firestop	27 oz.		 Cartridge	0-00-51115-11641-4	6/Cs	Each
	Up to 4-hr Penetration Firestop	2 gal.		 Pail	0-00-51115-11639-1	1/Cs	Each
	Up to 4-hr Penetration Firestop	5 gal.		 Pail	0-00-51115-11640-7	1/Cs	Each
IC 15WB+	Up to 3-hr Penetration Firestop	10.1 oz.		 Tube	0-00-51115-16557-3	12/Cs	Each
	Up to 3-hr Penetration Firestop	20 oz.		 Sausage	0-00-51115-16560-3	10/Cs	Each
	Up to 3-hr Penetration Firestop	4.5 gal.		 Pail	0-00-51115-16558-0	1/Cs	Each
FD 150+	Up to 3-hr Penetration/4-hr Joint Firestop	10.1 oz.		 Tube	0-00-51115-11574-5	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	20 oz.		 Sausage	0-00-51115-11634-6	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	28 oz.		 Cartridge	0-00-51115-11602-5	6/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	4.5 gal.		 Pail	5-00-51115-11575-7	1/Cs	Each
FD 150+	Up to 3-hr Penetration/4-hr Joint Firestop	10.1 oz.		 Tube	0-00-51115-18812-1	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	20 oz.		 Sausage	0-00-51115-18810-7	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	28 oz.		 Cartridge	0-00-51115-18811-4	6/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	4.5 gal.		 Pail	0-00-51115-18813-8	1/Cs	Each
FD 150+	Up to 3-hr Penetration/4-hr Joint Firestop	10.1 oz.		 Tube	0-00-51115-16564-1	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	20 oz.		 Sausage	0-00-51115-16567-2	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	28 oz.		 Cartridge	0-00-51115-16566-5	6/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	4.5 gal.		 Pail	0-00-51115-16565-8	1/Cs	Each

3M™ Fire Barrier Water Tight Sealants and Spray (W-Rated)

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
3000 WT 	Intumescent Silicone (Up to 4-hr Penetration Firestop)	10.1 oz.		 Tube	0-00-51115-16593-1	12/Cs	Each
	Intumescent Silicone (Up to 4-hr Penetration Firestop)	20 oz.		 Sausage	0-00-51115-18788-9	12/Cs	Each
	Intumescent Silicone (Up to 4-hr Penetration Firestop)	4.5 gal.		 Pail	5-00-51115-16594-3	1/Cs	Each
1000 NS 	Non-slump Silicone (Up to 3-hr Penetration/Joint Firestop)	10.1 oz.		 Tube	0-00-51115-11535-6	12/Cs	Each
	Non-slump Silicone (Up to 3-hr Penetration/Joint Firestop)	20 oz.		 Sausage	0-00-51115-18790-2	12/Cs	Each
	Non-slump Silicone (Up to 3-hr Penetration/Joint Firestop)	4.5 gal.		 Pail	5-00-51115-11537-5	1/Cs	Each