

### L&M™ CHEM HARD™

Refer to Data Sheet 175.0  
8-04-151-1171 / 8-04-151-1169



L&M™ CHEM HARD™, chemically reacts with soft free lime and calcium carbonate compounds in concrete to densify and create, chemically resistant surfaces.

#### FEATURES/BENEFITS:

- Low VOC and low odor
- Easy to apply
- Economical
- Seals, hardens, and densifies concrete surfaces

#### PACKAGING:

5 gal (18.9 L)  
55 gal (208 L)

#### APPROXIMATE COVERAGE

Two coats recommended 300 ft<sup>2</sup>/gal (7.3 m<sup>2</sup>/L)



### L&M LION HARD™

Refer to Data Sheet 174.7  
8-04-165-2081 / 8-04-165-2080



L&M LION HARD™ is a low VOC, environmentally friendly lithium silicate concrete floor densifier, hardener, and sealer. This product penetrates bare concrete surfaces and transforms them into dust free floors that get better with age.

#### FEATURES/BENEFITS:

- Low VOC and low odor
- Easy to apply
- Environmentally-friendly
- Seals, hardens, and densifies concrete surfaces

#### PACKAGING:

5 gal (18.9 L)  
55 gal (208 L)

#### APPROXIMATE COVERAGE

Typical Application Rates: Coverage dependent upon surface texture and porosity. Typical rate is 600-800 ft<sup>2</sup>/gal (14.7-19.6 m<sup>2</sup>) on hard troweled, dense concrete. One coat normally recommended. For best results on porous concrete surfaces, apply second coat after the first coat has dried completely and any dried residue has been removed.

Polished concrete: Apply two coats, the first at 400-600 ft<sup>2</sup>/gal (9.8-14.7 m<sup>2</sup>/L) and the second at 600-800 ft<sup>2</sup>/gal (14.7-19.5 m<sup>2</sup>/L) for maximum hardness and surface durability, per instructions.

