# **CURING COMPOUNDS / CURING AND SEALING COMPOUNDS - SOLVENT BASED**

## L&M CURE W2™

Refer to Data Sheet 172.4 8-10-258-1087 / 8-10-258-1086



A water-based, emulsified wax, liquid membrane forming curing compound for freshly finished concrete. L&M<sup>™</sup> CURE W2<sup>™</sup> has a white pigment which reflects the sun's rays to help keep the concrete surface cooler, and helps maximize water retention.

#### **FEATURES/BENEFITS:**

- Good moisture retention properties
- Very low odor for interior applications
- Recommended for exterior pavements
- Water-borne, low VOC

### **PACKAGING:**

5 gal (19 L) 55 gal (208 L)

## L&M DRESS & SEAL™

Refer to Data Sheet 173.0 8-13-301-1019 / 8-13-301-1018 / 8-13-301-1021



A sprayable, acrylic copolymer that cures, seals, and dustproofs concrete. L&M DRESS & SEAL<sup>™</sup> is a tough impervious acrylic which retains moisture, curing the concrete for maximum hardness.

May be subject to Volatile Organic Compound sales restrictions at the state, county and/or city level. Please see TDS 280 at www.laticrete.com for further guidance.

### FEATURES/BENEFITS:

- Protects sound concrete from dusting when used as directed
- Easy to spray formula
- Excellent curing and sealing properties
- = Enhances the look of colored, stamped concrete

#### **PACKAGING:**

1 gal (3.8 L) 5 gal (19 L) 55 gal (208 L)



## APPROXIMATE COVERAGE

Surface porosity determines coverage rate. For best results:

Broom finishes	200 ft²/gal (4.9 m²/L)
Steel troweled	300 ft²/gal (7.3 m²/L)

#### APPROXIMATE COVERAGE

 

 Typical Coverage Rates (depending on texture and porosity)

 First coat, curing
 300-400 ft²/gal (7.4-9.8 m²/L)

 Second coat, sealing
 400-600 ft²/gal (9.8-14.7 m²/L)

 Stamped and patterned concrete
 300 ft²/gal (7.4 m²/L)

Exposed aggregate  $200 \text{ ft}^2/\text{gal} (4.9 \text{ m}^2/\text{L})$