SAFETY DATA SHEET



Issue Date 13-Aug-2015 Revision Date 01-Jan-2018 Version 1

1. IDENTIFICATION

Product identifier

Product Name PUMADEQ PRIMER 20

Other means of identification

Product Code HEPU869
UN/ID no UN1866
Synonyms None

Recommended use of the chemical and restrictions on use
Recommended Use Industrial Coatings

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address HENRY COMPANY

999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716

Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

Company Phone Number 800-486-1278

Emergency Telephone US and Canada only (toll-free) : 3E Company - 1-866-519-4752 (access code 334832)

US/Canada, all other countries: 3E Company - +1-760-476-3962 (access code 334832) Mexico (additional contact option): 3E Company - +52 55 41696225 (Code 334832)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

Label elements

Emergency Overview

Danger

Hazard statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
May cause respiratory irritation

Highly flammable liquid and vapor



Appearance viscous Physical state liquid Odor Strong Aromatic

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ ventilating / lighting/ / equipment Use only non-sparking tools
Take precautionary measures against static discharge Keep cool

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention If skin irritation or rash occurs: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove viction to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful if inhaled. Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable

Mixture

Chemical Name	CAS No	Weight-%
Methyl methacrylate *	80-62-6	40 - 70
Resin-polymer Blend *	Proprietary	15 - 40
Triethylene glycol dimethacrylate *	109-16-0	3 - 7

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice Immediate medical attention is required. In case of accident or unwellness, seek medical

advice immediately (show directions for use or safety data sheet if possible). If symptoms

persist, call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin contact Wash off immediately with soap and plenty of water. Wash contaminated clothing before

reuse. If skin irritation persists, call a physician.

Inhalation Remove to fresh air. If symptoms persist, call a physician. Artificial respiration and/or

oxygen may be necessary.

Ingestion Call a physician or poison control center immediately. Do not induce vomiting without

medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.

Self-protection of the first aider Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. May cause skin irritation. Redness. Coughing

and/ or wheezing.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO2, sand, earth, water spray or regular foam.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

In the event of fire and/or explosion do not breathe fumes. May cause sensitization in susceptible persons. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Flammable.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge May be ignited by heat, sparks or flames.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Burning produces heavy smoke.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Revision Date 01-Jan-2018

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas. Use personal protective equipment as required.

Keep people away from and upwind of spill/leak.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do

not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal

binder, sawdust). Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks,

flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be

grounded. Use personal protective equipment as required. Avoid breathing vapors or mists.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat,

sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static

electricity). Keep in properly labeled containers.

Incompatible materials Strong oxidizing agents. Strong acids. Strong bases. Amines. Halogens.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl methacrylate	STEL: 100 ppm	TWA: 100 ppm	IDLH: 1000 ppm
80-62-6	TWA: 50 ppm	TWA: 410 mg/m ³	TWA: 100 ppm
			TWA: 410 ma/m ³

NIOSH IDLH Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Controls Minimize exposure by partial enclosure of the operation or equipment and provide extract

ventilation at openings.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state liquid
Appearance viscous
Color Cloudy

viscous Odor Strong Aromatic Cloudy Odor threshold 0.34 ppm

Remarks • Method

Tag Closed Cup

@ 20 °C

<u>Property</u> <u>Values</u>

pH No information available

Melting point / freezing point

Boiling point / boiling range

-18 °C / 0 °F

101 °C / 213 °F

Flash point

12 °C / 53 °F

Evaporation rate3.1 (nBuOAc = 1) **Flammability (solid, gas)**No information available

Flammability Limit in Air

Upper flammability limit: 12.5% Lower flammability limit: 2.1% Vapor pressure 4.7

Vapor density No information available

Relative density 0.94

Water solubility

Solubility in other solvents

Partition coefficient

Autoignition temperature

Insoluble in water

No information available

No information available

Decomposition temperature >250 C

Kinematic viscosity

Dynamic viscosity

Explosive properties

Oxidizing properties

No information available
No information available
Not an explosive
Not applicable

Other Information

Softening point
Molecular weight
VOC Content (%)
Density
No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Amines. Halogens.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation May cause irritation.

Eye contact Irritating to eyes.

Skin contact Irritating to skin. Repeated or prolonged skin contact may cause allergic reactions with

susceptible persons.

Ingestion Based on available data, the classification criteria are not met.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl methacrylate 80-62-6	= 7900 mg/kg (Rat) = 7872 mg/kg (Rat)	> 5 g/kg (Rabbit)	= 4632 ppm (Rat) 4 h
Triethylene glycol dimethacrylate	= 10837 mg/kg (Rat)	-	-
109-16-0			

Information on toxicological effects

Symptoms May cause an allergic skin reaction. May cause redness and tearing of the eyes. May

cause skin irritation. Redness. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationBased on available data, the classification criteria are not met. **Germ cell mutagenicity**Based on available data, the classification criteria are not met.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Methyl methacrylate 80-62-6	-	Group 3	-	-
Resin-polymer Blend	-	Group 3	-	-

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause disorder and damage to the. Respiratory system. Eyes. Skin.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Chronic toxicity Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated

exposure.

Target Organ Effects Eyes, Respiratory system, Skin.

Aspiration hazard Based on available data, the classification criteria are not met.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 7,872.00 mg/kg

 ATEmix (dermal)
 5,005.00 mg/kg

 ATEmix (inhalation-vapor)
 4,632.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Methyl methacrylate	170: 96 h Pseudokirchneriella	243 - 275: 96 h Pimephales	69: 48 h Daphnia magna mg/L
80-62-6	subcapitata mg/L EC50	promelas mg/L LC50 flow-through	EC50
	-	125.5 - 190.7: 96 h Pimephales	
		promelas mg/L LC50 static 153.9 -	
		341.8: 96 h Lepomis macrochirus	
		mg/L LC50 static 79: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		flow-through 79: 96 h Oncorhynchus	
		mykiss mg/L LC50 static 170 - 206:	

HEPU869 - PUMADEQ PRIMER 20

96 h Lepomis macrochirus mg/L
LC50 flow-through 326.4 - 426.9: 96
h Poecilia reticulata mg/L LC50
II Foecilia Teticulata IIIg/E EC30
static

Persistence and degradability

No information available.

Bioaccumulation

Chemical Name	Partition coefficient
Methyl methacrylate 80-62-6	0.7

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesThis material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261). Disposal should be in accordance with applicable regional, national and local laws

and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001 U162

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl methacrylate	U162	Included in waste stream:	-	U162
80-62-6		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Methyl methacrylate	Toxic
80-62-6	Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no UN1866
Proper shipping name Resin solution

Hazard Class 3
Packing Group ||

Special Provisions 149, B52, IB2, T4, TP1, TP8
Description UN1866, Resin solution, 3, II

Emergency Response Guide 127

Number

TDG

UN/ID no UN1866
Proper shipping name Resin solution

Hazard Class
Packing Group

Description UN1866, Resin solution, 3, II

IATA

UN/ID no UN1866
Proper shipping name Resin solution

Hazard Class 3
Packing Group II
ERG Code 3L
Special Provisions A3

Description UN1866, Resin solution, 3, II

IMDG

UN/ID no UN1866
Proper shipping name Resin solution

Hazard Class 3
Packing Group

EmS-No F-E, S-E

Description UN1866, Resin solution, 3, II, (12°C c.c.)

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Methyl methacrylate - 80-62-6	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No

No

CWA (Clean Water Act)

Reactive Hazard

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Methyl methacrylate 80-62-6	1000 lb	-	-	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)

Methyl methacrylate	1000 lb	-	RQ 1000 lb final RQ
80-62-6			RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Methyl methacrylate	X	X	X
80-62-6			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0 Physical and Chemical

Properties -

HMIS Health hazards 2 Flammability 3 Physical hazards 0 Personal protection X

Issue Date13-Aug-2015Revision Date01-Jan-2018

Revision Note

No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet