

### L&M™ DRESS & SEAL WB 30™

Refer to Data Sheet 173.4  
8-13-303-1028/8-13-303-1030



L&M™ DRESS & SEAL WB 30™ formulation is a water-based, high solids acrylic copolymer solution that cures, seals and dustproofs concrete.

May be subject to Volatile Organic Compound sales restrictions at the state, county and/or city level. Please see TDS 280 at [www.laticrete.com](http://www.laticrete.com) for further guidance.

#### FEATURES/BENEFITS:

- Water-based formulation that protects sound concrete from dusting when used as directed
- Easy to spray formula
- Excellent curing and sealing properties
- Enhances the look of colored, stamped concrete

#### PACKAGING:

5 gal (18.9 L)  
55 gal (209 L)

### L&M LUMISEAL FX™

Refer to Data Sheet 172.5  
8-13-331-1909/8-13-331-1908/8-13-331-1903/8-23-331-1910



L&M LUMISEAL FX™ is a high solids, water-based, non-yellowing, bluish resistant curing and sealing compound. When used as a sealer, LUMISEAL FX is designed to provide an attractive medium gloss finish on concrete substrates.

#### FEATURES/BENEFITS:

- Easy to apply
- Low odor
- Excellent curing and sealing properties
- May be used indoors or outdoors
- May be used on FGS PERMASHINE polished concrete
- Compatible with previously sealed concrete

#### PACKAGING:

4 x 1 gal (3.8 L)  
5 gal (19 L)  
55 gal (208 L)

#### APPROXIMATE COVERAGE

Typical Coverage Rates  
(depending on texture and porosity)

First coat, curing	200-400 ft <sup>2</sup> /gal (4.9-9.8 m <sup>2</sup> /L)
Second coat, sealing	400-600 ft <sup>2</sup> /gal (9.8-14.6 m <sup>2</sup> /L)

#### APPROXIMATE COVERAGE

Typical Coverage Rates  
(depending on texture and porosity)

First coat	200-400 ft <sup>2</sup> /gal (4.8-9.8 m <sup>2</sup> /L)
Second coat	400-600 ft <sup>2</sup> /gal (9.8-14.7 m <sup>2</sup> /L)
Top coat for polished concrete:	800-1,000 ft <sup>2</sup> /gal (20 to 25 m <sup>2</sup> /liter)