# **EVAPORATION CONTROL/BONDING AGENT**

### L&M™ E-CON™

Refer to Data Sheet 172.9 8-22-454-2100/8-22-451-1204/8-22-451-1205 8-22-451-1202/8-22-451-1206



L&M™ E-CON™ is a concentrated, odorless, water-based polymer liquid that, when placed on fresh concrete, helps to control the rate of evaporation and extend workability. L&M E-CON is ideal for achieving superior quality flatwork in challenging conditions such as high and low temperatures, low humidity, high winds, and direct sunlight.

#### **L&M EVERBOND™**

Refer to Data Sheet 176.2 8-01-102-1007/8-01-102-1005



L&M EVERBOND™ is a versatile acrylic polymer emulsion that can be used either as a bonding adhesive or as an admixture that enhances portland cement-based mixes, giving these mixes improved flexural, tensile, and bond strength.

## **FEATURES/BENEFITS:**

- Low VOC/no odor
- Easy application
- Prevents surface crusting
- Reduces plastic shrinkage cracks

### **FEATURES/BENEFITS:**

- Excellent bond strength
- Versatile bonding agent
- Excellent freeze/thaw resistance
- Excellent flexural strength

### **PACKAGING:**

4 x 1 qt (1 L) 4 x 1 gal (3.8 L) 5 gal (18.9 L) 55 gal (208 L) 275 gal (1,040 L)

#### **PACKAGING:**

4 x 1 gal (3.8 L) 5 gal (18.9 L)

#### **APPROXIMATE COVERAGE**

 $200-400 \text{ ft}^2/\text{gal} (4.9-9.8 \text{ m}^2/\text{L}) \text{ after dilution}$ 

APPROXIMATE COVERAGE	
Roughened concrete	200-300 ft²/gal (4.9-7.4 m²/L)
Plaster or smooth	300-400 ft²/gal (7.4-9.8 m²/L)