

# DuPont™ ArmorSeal Sealant

## Gunnable Grade Sealant for Joints and Fastener Heads

### FEATURES/BENEFITS

#### Description

**For Professional Use Only.** DuPont™ ArmorSeal Sealant is a moisture-cured polyether sealant. The gunnable grade material is primarily utilized at panel edges, seams, and fastener heads to complete the air and water-resistive barrier and flashing layer within DuPont™ ArmorWall™ Systems. Follow DuPont specifications for coverage rates and application requirements.

#### Product Benefits:

- Elastomeric moisture curing sealant
- Unique chemistry allows for +/-50% joint movement
- Designed to not stain porous substrates
- No out-gassing on green concrete
- Helps protect against UV-induced discoloration
- Paintable within twenty-four hours of application regardless of weather conditions or temperature

#### Available Sizes

- DuPont™ ArmorSeal Sealant is available as 20 oz (591 ml) tubes in a 20 pack carton.

#### Technical Data:

DuPont™ ArmorSeal Sealant, when used in approved DuPont™ ArmorWall™ Systems, complies with the following:

- ASTM C920 Type S, Grade NS, Class 50, Uses NT, T, I, G, & A
- AAMA 802.3-08 Type II Back Bedding Compound
- USDA Accepted



### PRODUCT CHARACTERISTICS

Characteristic	Value
Size	20oz (591 ml) tube
Package	20 pack carton
Color	Black
Typical Application	Seams and Fasteners
Estimated Coverage	~1.5 tubes per panel

### TYPICAL JOINT APPLICATION SIZES

Joint Width - inches (mm)	Joint Depth - inches (mm)
1/4 - 1/2 (6 - 13)	1/4 (6)
1/2 - 3/4 (13 - 19)	1/4 - 3/8 (6 - 10)
3/4 - 1 (19 - 25)	3/8 - 1/2 (10 - 13)
1 - 2 (25 - 50)	1/2 (13)

### PRODUCT PREPARATION AND APPLICATION

Remove any and all surface contaminants that may prevent adhesions. Cured sealant can be removed via scraping. For best gunnability and tooling maintain sealant at room temperatures. Apply sealant to a test surface to assess for adequate adhesion. Gun sealant with a smooth and continuous bead. Tool within fifteen minutes of application to ensure seal.

#### Warranty

Ten-year limited warranty may be applicable when used as a component in the DuPont™ ArmorWall™ System. Visit [www.ArmorWall.DuPont.com](http://www.ArmorWall.DuPont.com) or contact your DuPont representative for details.

## PROPERTIES

### Typical Physical Properties for DuPont™ ArmorSeal Sealant

Property	Value
Tensile Strength	225 psi
Lap Shear (rate = 1" per minute)	275 psi
Elongation	275%
Tack Free Time	<1 Hour @ 77°F / 50% RH
Skin Time	<30 min. @ 77°F / 50% RH
Sag	Non-sagging
Hardness	45-50
UV Ratings (2000 hours UV-A)	No change in appearance or physical properties (ASTM G26)
High Temperature Resistance	Up to 300°F for short periods of time
Low Temperature Flexibility	Properties retained to -75°F
Corrosive Properties	Non-corrosive
Staining Properties	Non-staining

## HANDLING

**WARNING: For Professional Use Only** – Read and follow the entire Handling section and the Safety Data Sheets carefully before use. The information below is designed to protect the user and allow for safe use and handling of DuPont™ ArmorSeal Brand products. Follow all applicable federal, state, local and employer regulations.

### Handling and Use

- Causes skin and eye irritation. May cause an allergic skin reaction. Wear impervious gloves such as vinyl to minimize contact with skin. Wear safety glasses or goggles to avoid eye contact.
- Please refer to the Safety Data Sheet for first aid information.
- Controlled conditions, 70°F (21°C) with 50% relative humidity, results in twelve month shelf life for sausage. High temperatures and relative humidity may reduce shelf life.

### Product Limitations

- Some cleaners and solvents may not be compatible with this product. It is recommended to perform a field adhesion test prior to application to surfaces other than those found within the DuPont™ ArmorWall™ System.

**CAUTION: KEEP OUT OF REACH OF CHILDREN.**



For more information visit us at  
[armorwall.dupont.com](http://armorwall.dupont.com)  
or call 1-800-448-9835

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.