
Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

CCW-704

Synonyms

Solvent-based rubberized bitumen mastic

Chemical Family

Mastic

Product Use

Detailing mastic for use with waterproofing membrane

Restrictions on Use

For industrial use only.

Manufacturer Information

Carlisle Coatings and Waterproofing, Inc.
900 Hensley Lane
Wylie, TX 75098
www.carlisleccw.com

Phone Numbers:

Medical Emergency
CHEMTREC (USA): 800-424-9300

MSDS Assistance; 972-442-6545
Technical Assistance: 888-229-2199
Customer Service: 888-229-0199

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 3

Skin Corrosion/Irritation - Category 2

Carcinogenicity - Category 2

Reproductive Toxicity - Category 1B

Specific Target Organ Toxicity - Single Exposure - Category 2 (liver, kidneys, thymus)

Specific Target Organ Toxicity - Single Exposure - Category 3

GHS Label Elements

Symbol(s)



Signal Word

Danger

Safety Data Sheet

Material Name: CCW-704

Product #305360

Hazard Statement(s)

Flammable liquid and vapor
Causes skin irritation
Suspected of causing cancer
May damage fertility or the unborn child
May cause damage to organs
May cause respiratory irritation. May cause drowsiness or dizziness

Precautionary Statement(s)

Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Keep container tightly closed
Keep away from heat/sparks/open flame/hot surfaces - No smoking
Ground/Bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Take precautionary measures against static discharge
Use only non-sparking tools
Use only outdoors or in a well-ventilated area
Wear protective gloves/protective clothing/eye protection/face protection
Do not breathe dust/fume/gas/mist/vapours/spray
Wash thoroughly after handling
Do not eat, drink or smoke when using this product

Response

In case of fire: Use appropriate media to extinguish
If exposed or concerned: Call a POISON CENTER or doctor/physician
IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor if you feel unwell
IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse
Specific treatment (see label)

Storage

Store in a well-ventilated place. Keep container tightly closed
Keep cool
Store locked up

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Other Hazards

No additional information available.

Safety Data Sheet

Material Name: CCW-704

Product #305360

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
8052-42-4	Asphalt	0-45
64742-93-4	Asphalt, oxidized	0-45
68955-27-1	Distillates, petroleum, petroleum residues vacuum	0-45
64741-56-6	Residues, petroleum, vacuum	0-45
64742-95-6	Solvent naphtha, petroleum, light aromatic	10-30
98-82-8	Cumene	0.1-1
95-63-6	Benzene, 1,2,4-trimethyl-	3-7
1330-20-7	Xylenes (o-, m-, p- isomers)	0.1-1
1317-65-3	Limestone	10-30
14808-60-7	Silica, crystalline	0.1-1
68953-58-2	Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	5-10

Section 4 - FIRST AID MEASURES

Description of Necessary Measures

If exposed or concerned: Call a POISON CENTER or doctor/physician.

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin

Wash exposed skin with soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs, get medical advice/attention.

Eyes

Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Safety Data Sheet

Material Name: CCW-704

Product #305360

Ingestion

Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor if you feel unwell.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Most Important Symptoms/Effects

Acute

Causes skin irritation. May cause damage to the kidneys, liver, thymus. May cause respiratory irritation. May cause drowsiness or dizziness.

Delayed

Suspected of causing cancer. May damage fertility or the unborn child.

Note to Physicians

Contains ASPHALT.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Use carbon dioxide, regular dry chemical, regular foam or water.

Unsuitable Extinguishing Media

None known.

Special Hazards Arising from the Chemical

Flammable liquid and vapor. Vapors are heavier than air and may travel a considerable distance to a source of ignition and flashback.

Hazardous Combustion Products

Oxides of carbon, hydrocarbons

Fire Fighting Measures

Ground/Bond container and receiving equipment. Take precautionary measures against static discharge. Avoid inhalation of material or combustion by-products.

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Remove all sources of ignition. Avoid inhalation of material or combustion by-products. Ventilate affected area. Absorb with earth, sand or other non-combustible material and transfer to container. Dispose in accordance with all applicable regulations.

Safety Data Sheet

Material Name: CCW-704

Product #305360

Environmental Precautions

Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep container tightly closed. Keep away from heat/sparks/open flame/hot surfaces - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin and clothing. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. KEEP OUT OF REACH OF CHILDREN.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed

Keep cool

Store locked up

Store below 100 F. Keep away from heat and ignition sources. Keep away from incompatible materials. Do not cut, puncture, or weld on or near this container.

Incompatible Materials

Strong oxidizing agents

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Asphalt	8052-42-4	
ACGIH:	0.5 mg/m ³ TWA as benzene soluble aerosol fume, inhalable fraction	
NIOSH:	5 mg/m ³ Ceiling fume 15 min	
Mexico:	5 mg/m ³ TWA LMPE-PPT	10 mg/m ³ STEL [LMPE-CT]
Hydrogen sulfide	7783-06-4	
ACGIH:	1 ppm TWA	5 ppm STEL
NIOSH:	10 ppm Ceiling 10 min; 15 mg/m ³ Ceiling 10 min	
	100 ppm IDLH	
Europe:	5 ppm TWA; 7 mg/m ³ TWA	10 ppm STEL; 14 mg/m ³ STEL

Safety Data Sheet

Material Name: CCW-704

Product #305360

OSHA (US):	20 ppm Ceiling	
Mexico:	10 ppm TWA LMPE-PPT; 14 mg/m ³ TWA LMPE-PPT	
	15 ppm STEL [LMPE-CT]; 21 mg/m ³ STEL [LMPE-CT]	
Cumene	98-82-8	
ACGIH:	50 ppm TWA	
NIOSH:	50 ppm TWA; 245 mg/m ³ TWA	900 ppm IDLH (10% LEL)
	Potential for dermal absorption	
Europe:	20 ppm TWA; 100 mg/m ³ TWA	50 ppm STEL; 250 mg/m ³ STEL
	Possibility of significant uptake through the skin	
OSHA (US):	50 ppm TWA; 245 mg/m ³ TWA	
	prevent or reduce skin absorption	
Mexico:	50 ppm TWA LMPE-PPT; 245 mg/m ³ TWA LMPE-PPT	
	75 ppm STEL [LMPE-CT]; 365 mg/m ³ STEL [LMPE-CT]	
	Skin - potential for cutaneous absorption	
Benzene, 1,2,4-trimethyl-	95-63-6	
NIOSH:	25 ppm TWA; 125 mg/m ³ TWA	
Europe:	20 ppm TWA; 100 mg/m ³ TWA	
Xylenes (o-, m-, p- isomers)	1330-20-7	
ACGIH:	100 ppm TWA	150 ppm STEL
Europe:	50 ppm TWA (pure); 221 mg/m ³ TWA (pure)	
	Possibility of significant uptake through the skin	
	100 ppm STEL (pure); 442 mg/m ³ STEL (pure)	
OSHA (US):	100 ppm TWA; 435 mg/m ³ TWA	
Mexico:	100 ppm TWA LMPE-PPT; 435 mg/m ³ TWA LMPE-PPT	
	150 ppm STEL [LMPE-CT]; 655 mg/m ³ STEL [LMPE-CT]	

Safety Data Sheet

Material Name: CCW-704

Product #305360

Limestone	1317-65-3	
NIOSH:	10 mg/m ³ TWA total dust; 5 mg/m ³ TWA respirable dust	
OSHA (US):	15 mg/m ³ TWA total dust; 5 mg/m ³ TWA respirable fraction	
Mexico:	10 mg/m ³ TWA LMPE-PPT	20 mg/m ³ STEL [LMPE-CT]
Silica, crystalline	14808-60-7	
ACGIH:	0.025 mg/m ³ TWA respirable fraction	
NIOSH:	0.05 mg/m ³ TWA respirable dust	50 mg/m ³ IDLH respirable dust
OSHA (US):	((30)/(%SiO ₂ + 2) mg/m ³ TWA) total dust; ((250)/(%SiO ₂ + 5) mppcf TWA) respirable fraction; ((10)/(%SiO ₂ + 2) mg/m ³ TWA) respirable fraction	
Mexico:	0.1 mg/m ³ TWA LMPE-PPT respirable fraction	

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Provide adequate ventilation. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear safety glasses or safety goggles, with a faceshield, as appropriate.

Skin Protection

Wear chemical resistant clothing and rubber boots when potential for contact with the material exists.

Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Protective Materials

Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Black paste	Physical State	liquid
Odor	Petroleum	Color	Black
Odor Threshold	Not available	pH	Not available

Safety Data Sheet

Material Name: CCW-704

Product #305360

Melting Point	Not available	Boiling Point	308 - 355 °F
Freezing point	Not available	Evaporation Rate	10 - 20 % volatile
Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	Not available	Flash Point	108 °F
Lower Explosive Limit	1.9 %	Decomposition	Not available
Upper Explosive Limit	12.6 %	Vapor Pressure	3 mmHg
Vapor Density (air=1)	4.2	Specific Gravity (water=1)	Not available
Water Solubility	Negligible	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Solubility (Other)	Not available
Density	1.24 (relative)	VOC	200 g/L

Other Information

No additional information available.

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

Incompatible Materials

Strong oxidizing agents

Hazardous decomposition products

Oxides of carbon, hydrocarbons

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May cause respiratory irritation. May cause drowsiness or dizziness.

Skin Contact

Causes skin irritation.

Material Name: CCW-704

Product #305360

Eye Contact

May cause mild eye irritation.

Ingestion

May be harmful if swallowed.

Acute and Chronic Toxicity**Component Analysis - LD50/LC50**

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Asphalt (8052-42-4)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >2000 mg/kg

Asphalt, oxidized (64742-93-4)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >2000 mg/kg

Distillates, petroleum, petroleum residues vacuum (68955-27-1)

Oral LD50 Rat 4320 mg/kg

Dermal LD50 Rabbit >2000 mg/kg

Residues, petroleum, vacuum (64741-56-6)

Oral LD50 Rat 4320 mg/kg

Dermal LD50 Rabbit >2000 mg/kg

Hydrogen sulfide (7783-06-4)

Inhalation LC50 Rat 0.99 mg/L 1 h

Solvent naphtha, petroleum, light aromatic (64742-95-6)

Oral LD50 >3000 mg/kg

Dermal LD50 >3160 mg/kg

Inhalation LC50 Rat 3400 ppm 4 h

Cumene (98-82-8)

Oral LD50 Rat 1400 mg/kg

Dermal LD50 Rabbit 12300 µL/kg

Inhalation LC50 Rat >3577 ppm 6 h

Benzene, 1,2,4-trimethyl- (95-63-6)

Oral LD50 Rat 3280 mg/kg

Dermal LD50 Rabbit >3160 mg/kg

Inhalation LC50 Rat 18 g/m³ 4 h

Xylenes (o-, m-, p- isomers) (1330-20-7)

Oral LD50 Rat 3500 mg/kg

Dermal LD50 Rabbit >4350 mg/kg

Inhalation LC50 Rat 29.08 mg/L 4 h

Limestone (1317-65-3)

Oral LD50 Rat 6450 mg/kg

Silica, crystalline (14808-60-7)

Oral LD50 Rat 500 mg/kg

Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite (68953-58-2)

Oral LD50 Rat >5000 mg/kg

Inhalation LC50 Rat >12.6 mg/L 4 h

Safety Data Sheet

Material Name: CCW-704

Product #305360

Immediate Effects

Causes skin irritation. May cause damage to the kidneys, liver, thymus. May cause respiratory irritation. May cause drowsiness or dizziness.

Delayed Effects

Suspected of causing cancer. May damage fertility or the unborn child.

Irritation/Corrosivity Data

Causes skin irritation. May cause respiratory irritation. May cause mild eye irritation.

Respiratory Sensitization

No data available.

Dermal Sensitization

No data available.

Component Carcinogenicity

Asphalt	8052-42-4
ACGIH:	A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free)
IARC:	Monograph 103 [2013]; Supplement 7 [1987] (extracts of steam-refined and air-refined); Monograph 35 [1985] (Group 2B (possibly carcinogenic to humans))
DFG:	Category 2 (considered to be carcinogenic for man, aerosol and vapor)
OSHA:	Present
Asphalt, oxidized	64742-93-4
IARC:	Monograph 103 [2013] (and their emissions during roofing) (Group 2A (probably carcinogenic to humans))
OSHA:	Present
Residues, petroleum, vacuum	64741-56-6
IARC:	Monograph 103 [2013] (Group 2B (possibly carcinogenic to humans))
OSHA:	Present
Polycyclic aromatic hydrocarbons	130498-29-2
NTP:	Reasonably Anticipated To Be A Human Carcinogen
OSHA:	Present

Safety Data Sheet

Material Name: CCW-704

Product #305360

Cumene	98-82-8
IARC:	Monograph 101 [2012] (Group 2B (possibly carcinogenic to humans))
NTP:	Reasonably Anticipated To Be A Human Carcinogen
DFG:	Category 3B (could be carcinogenic for man)
OSHA:	Present
Xylenes (o-, m-, p-isomers)	1330-20-7
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable))
Silica, crystalline	14808-60-7
ACGIH:	A2 - Suspected Human Carcinogen
IARC:	Monograph 100C [2012]; Monograph 68 [1997] (Group 1 (carcinogenic to humans))
NTP:	Known Human Carcinogen (respirable size)
DFG:	Category 1 (causes cancer in man, alveola fraction)
OSHA:	Present (respirable size)

Germ Cell Mutagenicity

No data available.

Tumorigenic Data

No data available

Reproductive Toxicity

May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

kidneys, liver, thymus

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

No data available.

Medical Conditions Aggravated by Exposure

No data available.

Safety Data Sheet

Material Name: CCW-704

Product #305360

Additional Data

This product contains crystalline silica, which is a known carcinogen. However, this component is bound by the polymer portion of the sealant. The only way this component would be released is through incineration.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Avoid release to the environment.

Component Analysis - Aquatic Toxicity

Asphalt, oxidized	64742-93-4
Algae:	EC50 72 h Pseudokirchneriella subcapitata 56 mg/L IUCLID
Distillates, petroleum, petroleum residues vacuum	68955-27-1
Fish:	LC50 96 h Brachydanio rerio 48 mg/L [semi-static]
Residues, petroleum, vacuum	64741-56-6
Fish:	LC50 96 h Brachydanio rerio 48 mg/L [semi-static]
Hydrogen sulfide	7783-06-4
Fish:	LC50 96 h Lepomis macrochirus 0.0448 mg/L [flow-through]; LC50 96 h Pimephales promelas 0.016 mg/L [flow-through]
Solvent naphtha, petroleum, light aromatic	64742-95-6
Fish:	LC50 96 h Oncorhynchus mykiss 9.22 mg/L
Invertebrate:	EC50 48 h Daphnia magna 6.14 mg/L IUCLID
Cumene	98-82-8
Fish:	LC50 96 h Pimephales promelas 6.04 - 6.61 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 4.8 mg/L [flow-through];

Safety Data Sheet

Material Name: CCW-704

Product #305360

	LC50 96 h Oncorhynchus mykiss 2.7 mg/L [semi-static]; LC50 96 h Poecilia reticulata 5.1 mg/L [semi-static]
Algae:	EC50 72 h Pseudokirchneriella subcapitata 2.6 mg/L EPA
Invertebrate:	EC50 48 h Daphnia magna 0.6 mg/L IUCLID; EC50 48 h Daphnia magna 7.9 - 14.1 mg/L [static] EPA
Benzene, 1,2,4-trimethyl-	95-63-6
Fish:	LC50 96 h Pimephales promelas 7.19 - 8.28 mg/L [flow-through]
Invertebrate:	EC50 48 h Daphnia magna 6.14 mg/L IUCLID
Xylenes (o-, m-, p-isomers)	1330-20-7
Fish:	LC50 96 h Pimephales promelas 13.4 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 2.661 - 4.093 mg/L [static]; LC50 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L; LC50 96 h Lepomis macrochirus 13.1 - 16.5 mg/L [flow-through]; LC50 96 h Lepomis macrochirus 19 mg/L; LC50 96 h Lepomis macrochirus 7.711 - 9.591 mg/L [static]; LC50 96 h Pimephales promelas 23.53 - 29.97 mg/L [static]; LC50 96 h Cyprinus carpio 780 mg/L [semi-static]; LC50 96 h Cyprinus carpio >780 mg/L; LC50 96 h Poecilia reticulata 30.26 - 40.75 mg/L [static]
Invertebrate:	EC50 48 h water flea 3.82 mg/L; LC50 48 h Gammarus lacustris 0.6 mg/L

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Other Toxicity

No additional information available.

Safety Data Sheet

Material Name: CCW-704

Product #305360

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Shipping Name: Combustible liquid, n.o.s.

Hazard Class: Combustible liquid

UN/NA #: NA1993

Packing Group: III

Required Label(s): None

Additional information: Special Provisions (172.102): IB3, T1, T4, TP1

IATA Information:

UN#: UN1993

IMDG Information:

UN#: UN1993

TDG Information:

UN#: UN1993

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Hydrogen sulfide	7783-06-4
SARA 302:	500 lb TPQ
SARA 313:	1 % de minimis concentration
CERCLA:	100 lb final RQ; 45.4 kg final RQ
OSHA (safety):	1500 lb TQ
SARA 304:	100 lb EPCRA RQ
Cumene	98-82-8
SARA 313:	1 % de minimis concentration

Safety Data Sheet

Material Name: CCW-704

Product #305360

CERCLA:	5000 lb final RQ; 2270 kg final RQ
Benzene, 1,2,4-trimethyl-	95-63-6
SARA 313:	1 % de minimis concentration
Xylenes (o-, m-, p- isomers)	1330-20-7
SARA 313:	1 % de minimis concentration
CERCLA:	100 lb final RQ; 45.4 kg final RQ

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes **Chronic Health:** Yes **Fire:** Yes **Pressure:** No **Reactivity:** No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Asphalt	8052-42-4	Yes	Yes	Yes	Yes	Yes
Asphalt, oxidized	64742-93-4	No	No	No	Yes	No
Hydrogen sulfide	7783-06-4	Yes	Yes	Yes	Yes	Yes
Polycyclic aromatic hydrocarbons	130498-29-2	No	No	Yes	Yes	Yes
Cumene	98-82-8	Yes	Yes	Yes	Yes	Yes
Benzene, 1,2,4-trimethyl-	95-63-6	No	Yes	Yes	Yes	Yes
Xylenes (o-, m-, p- isomers)	1330-20-7	Yes	Yes	Yes	Yes	Yes
Limestone	1317-65-3	No	Yes	Yes	Yes	Yes
Silica, crystalline	14808-60-7	No	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer

Cumene	98-82-8
Carc:	carcinogen , 4/6/2010
Silica, crystalline	14808-60-7
Carc:	carcinogen , 10/1/1988 (airborne particles of respirable size)

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Safety Data Sheet

Material Name: CCW-704

Product #305360

Hydrogen sulfide	7783-06-4
	1 %
Cumene	98-82-8
	1 %
Benzene, 1,2,4-trimethyl-	95-63-6
	0.1 %
Silica, crystalline	14808-60-7
	1 %

Component Analysis - Inventory

Asphalt (8052-42-4)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Asphalt, oxidized (64742-93-4)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	No

Distillates, petroleum, petroleum residues vacuum (68955-27-1)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	No	No	No	Yes	No	Yes	No	No

Residues, petroleum, vacuum (64741-56-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Hydrogen sulfide (7783-06-4)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Safety Data Sheet

Material Name: CCW-704

Product #305360

Polycyclic aromatic hydrocarbons (130498-29-2)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
No	No	No	No	No	No	No	No	No	No	No	Yes

Solvent naphtha, petroleum, light aromatic (64742-95-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Cumene (98-82-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Benzene, 1,2,4-trimethyl- (95-63-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Xylenes (o-, m-, p- isomers) (1330-20-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Limestone (1317-65-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	NSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Silica, crystalline (14808-60-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Safety Data Sheet

Material Name: CCW-704

Product #305360

Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite (68953-58-2)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	No

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 2* Fire: 2 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 2 Fire: 2 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

Revision Date: June 1, 2018

Revision Note: General Update

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Safety Data Sheet

Material Name: CCW-704

Product #305360

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, CCWI Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use