

WATERPROOFING/SOUND CONTROL/ANTI-FRACTURE MEMBRANE

LATAPOXY® WATERPROOF FLASHING MORTAR

Refer to Data Sheet 070.0
0024-0001-2



A 3-component epoxy-based flashing to waterproof seams, gaps, or joints between a substrate, metal and PVC pipes, drains, and flashing.

FEATURES/BENEFITS:

- For use under ceramic tile, stone, or brick
- For rapid installations that require a fast-curing waterproof flashing
- Easy to apply using a trowel

PACKAGING:

3.5 gal (13.2 L) pail with 2 Part A 1.4 lbs. (0.65 kg),
2 Part B 1.15 lbs (0.5 kg) and 2 Part C 5.5 lbs. (2.5 kg);
48 units per pallet

Approximate Coverage

45 ft²/unit (4.2 m²) at 1/8" (3 mm) thick,
depending on application

BLUE 92 ANTI-FRACTURE MEMBRANE AND CRACK SUPPRESSION KIT

Refer to Data Sheets 647.0, 648.0, and WPAF.5
9200-0001-2/9200-0001-2-4



A 2-part system that forms a flexible, full-coverage membrane that reduces crack transmission from the substrate to floor finishes.

FEATURES/BENEFITS:

- Easy to install; cleans up with water
- EXTRA heavy service rating per ASTM C627 (TCNA)
- Passes ANSI A118.12 anti-fracture performance up to 1/8" (3 mm)

PACKAGING:

Kit: 2 gallon (7.6 L) jug of liquid, 1 each 15" (38 cm) wide roll of Waterproofing/Anti-Fracture Fabric packed together in one carton; 36 cartons per pallet.

Full Unit: 5 gallon (19 L) pail liquid; 1 carton Waterproofing/Anti-Fracture Fabric, packed separately, 36 units per pallet.

Approximate Coverage

75 linear ft/unit (23 m) at 15" (37.5 cm) wide
300 ft² (28 m²) per full unit

MICROBAN 



LATAPOXY® WATERPROOF FLASHING MORTAR

Refer to Data Sheet 070.0
0024-0001-2



An epoxy-based 3 component, trowel applied, waterproofing and vapor barrier membrane. LATAPOXY® Waterproof Flashing Mortar can be used to waterproof seams, gaps or joints between a variety of substrates and metal and PVC pipe penetrations or flashing. It is specifically designed to be used under adhered masonry veneer, stone, or brick for rapid installations which require a fast curing waterproof flashing. LATAPOXY Waterproof Flashing Mortar is flexible, easy to apply and will allow for rapid installations.

FEATURES/BENEFITS:

- Easy to apply using a trowel
- Adheres to metal and PVC pipes, drains, and flashing
- Waterproof seam between flashing and adjacent waterproofing materials

PACKAGING:

3.5 gallon pail with 2 LATAPOXY Waterproof Flashing Mortar Part A 1.4 lbs (0.65 kg), 2 LATAPOXY Waterproof Flashing Mortar Part B 1.15 lbs (0.5 kg), and 2 LATAPOXY Waterproof Flashing Mortar Part C 5.5 lbs (2.5 kg); 48 units per pallet

Approximate Coverage

45 ft²/unit (4.2 m²) at 1/8" (3 mm) thick, depending on application

MVIS™ LIGHTWEIGHT MORTAR

Refer to Data Sheet 060.1
9369-0030-22



MVIS™ Lightweight Mortar is a lightweight, high performance multi-use, polymer fortified adhesive mortar. MVIS Lightweight Mortar offers tremendous utility including non-sag wall installations.

FEATURES/BENEFITS:

- Incredible non-sag performance, including large and/or heavy thin brick, stone, masonry veneer, or tile
- Lightweight formula. A 30 lb (13.6 kg) bag provides the same coverage as a 50 lb (22.7 kg) bag of traditional mortar
- Exceeds ANSI A118.4, 118.11 & 118.15 requirements
- Bonds to many suitable substrates

PACKAGING:

30 lb (13.6 kg) bag; 56 bags per pallet; White

Approximate Coverage Per 30 lb (13.6 kg) bag

NOTCHED TROWEL	COVERAGE
1/4" x 3/8" (6 x 9 mm)	60 - 70 ft ² (5.6 - 6.5 m ²)
1/2" x 1/2" (12 x 12 mm)	40 - 47 ft ² (3.7 - 4.4 m ²)
Adhered Masonry Veneer Application Method	30 - 35 ft ² (2.8 - 3.2 m ²)

