

MasterSeal HLM 5000SPGR

Version 1.0 Revision Date: 07/31/2020 SDS Number: 000000260790 Date of last issue: -
Date of first issue: 07/31/2020

SECTION 1. IDENTIFICATION

Product name : MasterSeal HLM 5000SPGR
Product code : 000000000055356262 000000000055356262

Manufacturer or supplier's details

Company name of supplier : Master Builders-Admixtures US,LLC
Address : 23700 CHAGRIN BLVD
Beachwood OH 44122
Emergency telephone : ChemTel: +1-813-248-0585 USA: +1-800-255-3924 Contract
Number MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Aspiration hazard : Category 1
FLAMMABLE LIQUIDS : 3
Skin corrosion/irritation : 2
Serious eye damage/eye irritation : Category 1
Reproductive toxicity : 1B
Reproductive toxicity : 1B
Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)
Short-term (acute) aquatic hazard : 3
Long-term (chronic) aquatic hazard : 3

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapour.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H304 May be fatal if swallowed and enters airways.

MasterSeal HLM 5000SPGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/31/2020	000000260790	Date of first issue: 07/31/2020

H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H360 May damage fertility or the unborn child.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust or mist.
P273 Avoid release to the environment.
P243 Take action to prevent static discharges.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P241 Use explosion-proof [electrical/ ventilating/ lighting/ .?] equipment.
P270 Do not eat, drink or smoke when using this product.
P264 Wash face, hands and any exposed skin thoroughly after handling.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P242 Use only non-sparking tools.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/ doctor/
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P405 Store locked up.
P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

MasterSeal HLM 5000SPGR

Version 1.0 Revision Date: 07/31/2020 SDS Number: 000000260790 Date of last issue: -
 Date of first issue: 07/31/2020

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
talca	14807-96-6	>= 25 - < 50
Asphalt	8052-42-4	>= 10 - < 15
calcium oxide	1305-78-8	>= 7 - < 10
Stoddard solvent	8052-41-3	>= 7 - < 15
Solvent naphtha (petroleum), light arom.	64742-95-6	>= 3 - < 5
1,2,4-trimethylbenzene	95-63-6	>= 3 - < 5
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 3 - < 5
Distillates (petroleum), hydrotreated light naphthenic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 oF (19cSt at 40 oC). It contains relatively few normal paraffins.]	64742-53-6	>= 1 - < 3
Diethylbenzene	25340-17-4	>= 0.2 - < 0.3
dibutyltin dilaurate	77-58-7	>= 0.2 - < 0.3

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
 Consult a physician.
 Show this material safety data sheet to the doctor in attendance.
 Symptoms of poisoning may appear several hours later.
 Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
 If on skin, rinse well with water.
 If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
 In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 Continue rinsing eyes during transport to hospital.
 Remove contact lenses.
 Protect unharmed eye.

MasterSeal HLM 5000SPGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/31/2020	000000260790	Date of first issue: 07/31/2020

If swallowed	:	Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.
Notes to physician	:	Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Foam Dry powder Carbon dioxide (CO ₂)
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

MasterSeal HLM 5000SPGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/31/2020	000000260790	Date of first issue: 07/31/2020

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : no smoking
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep container tightly closed and in a well-ventilated place.
Keep away from heat.
Avoid all sources of ignition: heat, sparks, open flame.
- Materials to avoid : Segregate from foods and animal feeds.
- Further information on storage stability : No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dibutyltin dilaurate	77-58-7	TWA value	0.1 mg/m ³ (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m ³ (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m ³ (tin (Sn))	NIOSH
		PEL	0.1 mg/m ³ (tin (Sn))	29 CFR 1910.1000

MasterSeal HLM 5000SPGR

Version
1.0Revision Date:
07/31/2020SDS Number:
000000260790Date of last issue: -
Date of first issue: 07/31/2020

				(Table Z-1)
		TWA value	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m3 (Tin)	OSHA Z-1
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH
		TWA	0.1 mg/m3 (Tin)	OSHA P0
		TWA	0.1 mg/m3 (Tin)	NIOSH REL
1,2,4-trimethylbenzene	95-63-6	TWA value	25 ppm	ACGIHTLV
		REL value	25 ppm 125 mg/m3	NIOSH
		TWA value	25 ppm 125 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	25 ppm 125 mg/m3	NIOSH REL
		TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	OSHA P0
calcium oxide	1305-78-8	TWA value	2 mg/m3	ACGIHTLV
		REL value	2 mg/m3	NIOSH
		PEL	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	2 mg/m3	ACGIH
		TWA	2 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
Asphalt	8052-42-4	TWA value (Inhalable fraction)	0.5 mg/m3 (benzene solubles)	ACGIHTLV
		Ceil_Time (fumes/smok e)	5 mg/m3	NIOSH
		TWA value (Inhalable fume)	0.5 mg/m3 (benzene solubles)	ACGIHTLV
		TWA (Fume, inhalable fraction)	0.5 mg/m3 (benzene soluble aerosol)	ACGIH
		C (Fumes)	5 mg/m3	NIOSH REL
talc	14807-96-6	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV

MasterSeal HLM 5000SPGR

Version 1.0 Revision Date: 07/31/2020 SDS Number: 000000260790 Date of last issue: -
 Date of first issue: 07/31/2020

		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m ³	OSHA P0
		TWA (Respirable)	2 mg/m ³	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
Stoddard solvent	8052-41-3	TWA value	100 ppm	ACGIHTLV
		REL value	350 mg/m ³	NIOSH
		Ceil_Time	1,800 mg/m ³	NIOSH
		PEL	500 ppm 2,900 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 525 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA	100 ppm	ACGIH
		TWA	350 mg/m ³	NIOSH REL
		C	1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,900 mg/m ³	OSHA Z-1
		TWA	100 ppm 525 mg/m ³	OSHA P0
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA value (Inhalable fraction)	5 mg/m ³	ACGIHTLV
		TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	OSHA P0
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Distillates (petroleum), hydrotreated light naphthenic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 oF (19cSt at 40 oC). It contains relatively few normal	64742-53-6	TWA value (Inhalable fraction)	5 mg/m ³	ACGIHTLV

MasterSeal HLM 5000SPGR

Version 1.0 Revision Date: 07/31/2020 SDS Number: 000000260790 Date of last issue: -
 Date of first issue: 07/31/2020

paraffins.]				
		REL value	350 mg/m3	NIOSH
		Ceil_Time	1,800 mg/m3	NIOSH
		REL value (Mist)	5 mg/m3	NIOSH
		STEL value (Mist)	10 mg/m3	NIOSH
		PEL (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL	500 ppm 2,000 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Avoid inhalation of dusts/mists/vapours.
Avoid contact with the skin, eyes and clothing.
Avoid prolonged and/or repeated contact with the skin.
Handle in accordance with good building materials hygiene and safety practice.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous

Color : black

MasterSeal HLM 5000SPGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/31/2020	000000260790	Date of first issue: 07/31/2020

Odor	:	strong, solvent
Odor Threshold	:	No data available
pH	:	neutral to slightly alkaline
Melting point	:	No applicable information available.
boiling temperature	:	approx. 307.99 - 700.00 °F / 153.33 - 371.11 °C
Flash point	:	120.00 °F / 48.89 °C
		Method: Flash-Point by Pensky-Martens Closed Cup Tester. 120 °F / 49 °C
Evaporation rate	:	No applicable information available.
Flammability (solid, gas)	:	Flammable.
Upper explosion limit / Upper flammability limit	:	7.0 %(V)
Lower explosion limit / Lower flammability limit	:	0.9 %(V)
Vapor pressure	:	No data available
Relative vapor density	:	Heavier than air.
Relative density	:	1.3
Density	:	approx. 1.3 g/cm ³ (approx. 68 °F / 20 °C)
Bulk density	:	1,800 - 2,400 kg/m ³
Solubility(ies)	:	
Water solubility	:	slightly soluble (68 °F / 20 °C)
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	No applicable information available.
Autoignition temperature	:	No data available
Decomposition temperature	:	Vapors may form explosive mixture with air. No decomposition if stored and handled as prescribed/indicated.
Viscosity	:	
Viscosity, dynamic	:	No applicable information available.
Viscosity, kinematic	:	No applicable information available.
Explosive properties	:	Not explosive Not explosive

MasterSeal HLM 5000SPGR

Version 1.0 Revision Date: 07/31/2020 SDS Number: 000000260790 Date of last issue: -
Date of first issue: 07/31/2020

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

Metal corrosion rate : Corrosive effects to metal are not anticipated.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed. Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

MasterSeal HLM 5000SPGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/31/2020	000000260790	Date of first issue: 07/31/2020

octanol/water Method: Partition coefficient (n-octanol/water), HPLC method.

Solvent naphtha (petroleum), light arom.:

Partition coefficient: n-octanol/water : log Pow: 3.17
Method: other (calculated)
GLP: no

1,2,4-trimethylbenzene:

Partition coefficient: n-octanol/water : log Pow: 3.63 (77 °F / 25 °C)
Method: other (calculated)

dibutyltin dilaurate:

Partition coefficient: n-octanol/water : log Pow: 3.17 (69.4 °F / 20.8 °C)
pH: 6.1 - 6.3
Method: Partition coefficient (n-octanol/water), Shake-flask method
GLP: yes

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with national, state and local regulations.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3

MasterSeal HLM 5000SPGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/31/2020	000000260790	Date of first issue: 07/31/2020

IATA-DGR

UN/ID No.	: UN 1263
Proper shipping name	: PAINT
Class	: 3
Packing group	: III
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355

IMDG-Code

UN number	: UN 1263
Proper shipping name	: PAINT
Class	: 3
Packing group	: III
Labels	: 3
EmS Code	: F-E, S-E
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

UN/ID/NA number	: UN 1263
Proper shipping name	: PAINT, COMBUSTIBLE LIQUID
Class	: C
Packing group	: III
Labels	: Combustible Liquid
ERG Code	: 128
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

1,2,4-trimethylbenzene	95-63-6
------------------------	---------

US State Regulations**Pennsylvania Right To Know**

cumene	98-82-8
talc	14807-96-6
calcium oxide	1305-78-8
1,2,4-trimethylbenzene	95-63-6
Asphalt	8052-42-4

MasterSeal HLM 5000SPGR

Version 1.0	Revision Date: 07/31/2020	SDS Number: 000000260790	Date of last issue: - Date of first issue: 07/31/2020
----------------	------------------------------	-----------------------------	--

Stoddard solvent 8052-41-3
 Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5
 listed

New Jersey Right To Know

talc 14807-96-6
 calcium oxide 1305-78-8
 1,2,4-trimethylbenzene 95-63-6
 Asphalt 8052-42-4
 Stoddard solvent 8052-41-3
 cumene 98-82-8
 Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5
 listedSpecial Hazard.

California Prop. 65

WARNING: This product can expose you to chemicals including cumene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH		H
FLAMMABILITY		M
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)

MasterSeal HLM 5000SPGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/31/2020	000000260790	Date of first issue: 07/31/2020

ACGIHTLV	:	American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	:	NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
29 CFR 1910.1000 (Table Z-1-A) / TWA value	:	Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	:	Permissible exposure limit
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIHTLV / STEL value	:	Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value	:	Time Weighted Average (TWA):
NIOSH / Ceil_Time	:	Ceiling Limit Value and Time Period (if specified):
NIOSH / REL value	:	Recommended exposure limit (REL):
NIOSH / STEL value	:	Short Term Exposure Limit (STEL):
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and

MasterSeal HLM 5000SPGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/31/2020	000000260790	Date of first issue: 07/31/2020

Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/31/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN