

The listed systems are typical applications only. Please refer to the volume of your 3M specification guide for your specific application or use the 3M System Selector available at [3M.com/firestop](http://3M.com/firestop)

# 3M™ Fire Protection Products

## 3M™ Fire Barrier Sealant CP 25WB+

3M™ Fire Barrier Sealant CP 25WB+ is a high-performance, intumescent latex-based sealant offering outstanding fire performance plus a non-halogen formula. Approved for the majority of caulk through penetration systems.

- Firestop tested up to 4 hours in accordance with ASTM E 814 (UL 1479)
- Acoustic barrier: STC-Rating of 54 when tested in a STC 54-rated wall assembly
- Provides L-Rating (smoke seal)
- Water based: easy cleanup and routine disposal with no special handling
- Intumescent: expands when heated to seal around items consumed by fire
- Re-enterable/repairable
- Halogen-free and no-sag formulation
- Over 600 tested and listed systems
- One-part system: no mixing or measuring required
- Fast-drying: tack-free in approximately 10–15 minutes
- Paintable (best results obtained after 72 hour cure)
- Red color widely recognized as a firestop for inspections
- High caulk rate: 1000g/min. with 1/4 in. nozzle opening
- Documented aging properties

Not for use with CPVC pipe.




FIRE BARRIER



SMOKE SEAL



SOUND BARRIER



## 3M™ Fire Barrier Sealant FD 150+

3M™ Fire Barrier Sealant FD 150+ is the economical alternative to costly firestopping applications. Used to firestop metal pipes or cables through concrete or gypsum, and in dynamic head-of-wall systems.

- Firestop tested up to 3 hours in accordance with ASTM E 814 (UL 1479)
- Fire Resistive Joint System tested up to 4 hours in accordance with ASTM E 1966 (UL 2079)
- Water based acrylic latex: easy cleanup and routine disposal
- Safe, solvent-free: fully cured, continuous seal with ±19% dynamic joint movement capability
- Single-part formulation
- Remains pliable allowing for normal pipe movement
- Fast-drying: tack-free in approximately 30–60 minutes
- Paintable (best results obtained after 72 hour cure)
- Excellent adhesion: multi-viscosity grade offers excellent caulking properties
- Available in limestone gray, blue and red

Not for use with CPVC pipe.



FIRE BARRIER



SMOKE SEAL



SOUND BARRIER





ELASTOMERIC











































# Ordering Information















## 3M™ Fire Barrier Rated Foam FIP 1-Step

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
FIP 1-Step	Firestop Foam Up to 2-hr Penetration Firestop	12.85 oz.		 Cartridge	0-00-51115-54925-0	1/Cs	Each
Mixing Nozzles	Mixing Nozzles	—	—	Nozzle	0-00-51115-54933-0	5/Cs	Bag
Albion® Manual Dispenser Gun	Manual gun for 3M™ Fire Rated Foam FIP 1-Step	—	—	Gun	0-00-76308-14612-2	1/Cs	Each
Albion® Power Dispenser Gun	Power gun for 3M™ Fire Rated Foam FIP 1-Step	—	—	Gun	0-00-76308-14610-8	1/Cs	Each
	18V Li-ion Battery	—	—	Battery	0-00-76308-14614-6	1/Cs	Each

## 3M™ Fire Barrier Sealants

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
CP 25WB+	Up to 4-hr Penetration Firestop	10.1 oz.		 Tube	0-00-51115-11638-4	12/Cs	Each
	Up to 4-hr Penetration Firestop	20 oz.		 Sausage	0-00-51115-11642-1	10/Cs	Each
	Up to 4-hr Penetration Firestop	27 oz.		 Cartridge	0-00-51115-11641-4	6/Cs	Each
	Up to 4-hr Penetration Firestop	2 gal.		 Pail	0-00-51115-11639-1	1/Cs	Each
	Up to 4-hr Penetration Firestop	5 gal.		 Pail	0-00-51115-11640-7	1/Cs	Each
IC 15WB+	Up to 3-hr Penetration Firestop	10.1 oz.		 Tube	0-00-51115-16557-3	12/Cs	Each
	Up to 3-hr Penetration Firestop	20 oz.		 Sausage	0-00-51115-16560-3	10/Cs	Each
	Up to 3-hr Penetration Firestop	4.5 gal.		 Pail	0-00-51115-16558-0	1/Cs	Each
FD 150+	Up to 3-hr Penetration/4-hr Joint Firestop	10.1 oz.		 Tube	0-00-51115-11574-5	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	20 oz.		 Sausage	0-00-51115-11634-6	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	28 oz.		 Cartridge	0-00-51115-11602-5	6/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	4.5 gal.		 Pail	5-00-51115-11575-7	1/Cs	Each
FD 150+	Up to 3-hr Penetration/4-hr Joint Firestop	10.1 oz.		 Tube	0-00-51115-18812-1	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	20 oz.		 Sausage	0-00-51115-18810-7	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	28 oz.		 Cartridge	0-00-51115-18811-4	6/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	4.5 gal.		 Pail	0-00-51115-18813-8	1/Cs	Each
FD 150+	Up to 3-hr Penetration/4-hr Joint Firestop	10.1 oz.		 Tube	0-00-51115-16564-1	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	20 oz.		 Sausage	0-00-51115-16567-2	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	28 oz.		 Cartridge	0-00-51115-16566-5	6/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	4.5 gal.		 Pail	0-00-51115-16565-8	1/Cs	Each

## 3M™ Fire Barrier Water Tight Sealants and Spray (W-Rated)

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
3000 WT 	Intumescent Silicone (Up to 4-hr Penetration Firestop)	10.1 oz.		 Tube	0-00-51115-16593-1	12/Cs	Each
	Intumescent Silicone (Up to 4-hr Penetration Firestop)	20 oz.		 Sausage	0-00-51115-18788-9	12/Cs	Each
	Intumescent Silicone (Up to 4-hr Penetration Firestop)	4.5 gal.		 Pail	5-00-51115-16594-3	1/Cs	Each
1000 NS 	Non-slump Silicone (Up to 3-hr Penetration/Joint Firestop)	10.1 oz.		 Tube	0-00-51115-11535-6	12/Cs	Each
	Non-slump Silicone (Up to 3-hr Penetration/Joint Firestop)	20 oz.		 Sausage	0-00-51115-18790-2	12/Cs	Each
	Non-slump Silicone (Up to 3-hr Penetration/Joint Firestop)	4.5 gal.		 Pail	5-00-51115-11537-5	1/Cs	Each