

Issuing Date 25-Jan-2016

Revision Date 02-Nov-2021

Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name: MBB, MBB Plus, MBB Pump Grade, White MBB, Base Coat and Adhesive, Hardcoat Mortar, UltraBond

Other means of identification

Synonyms BBC

Recommended use of the chemical and restrictions on use

Recommended Use Bag mix adhesive and basecoat

Uses advised against No information available

Supplier's details

Supplier Address
Master Wall Inc.
6975 Flat Rock Road
Midland, GA 31820
TEL: 706-569-0092

Emergency telephone number

Emergency Telephone Number 1-800-535-5053

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 1
Skin Sensitization	Category 1
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 1A
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Specific Target Organ Toxicity (Repeated Exposure)	Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word Danger

Hazard Statements

- Causes skin irritation
- Causes serious eye damage
- May cause an allergic skin reaction
- May cause cancer
- May damage fertility or the unborn child
- May cause respiratory irritation
- May cause damage to organs through prolonged or repeated exposure
- Harmful to aquatic life with long lasting effects

**Appearance** Grey.**Physical State** Solid (powder).**Odor** None.**Precautionary Statements****Prevention**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Wash face, hands and any exposed skin thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- If exposed or concerned: Get medical attention/advice
- Specific treatment (see supplemental instructions on the administration of antidotes on this label)

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Immediately call a POISON CENTER or doctor/physician.

Skin

- IF ON SKIN: Wash with plenty of soap and water.
- Take off contaminated clothing and wash before reuse.
- If skin irritation or rash occurs: Get medical advice/attention.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Storage

- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable.

Other information

Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

37.51419% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms

BBC

Chemical Name	CAS-No	Weight %	Trade secret
Quartz	14808-60-7	30-60	*
Portland cement	65997-15-1	10-30	*
Silica	7631-86-9	3 -7	*
Calcium oxide	1305-78-8	1-5	*
Aluminum oxide	1344-28-1	1-5	*
Calcium sulfate	7778-18-9	1-5	*
Limestone	1317-65-3	1-5	*
Flue dust, zinc-refining	69012-63-1	1-5	*
Iron oxide	1309-37-1	0.1-1	*
Silica, fused	60676-86-0	0.1-1	*
Titanium dioxide	13463-67-7	< 0.1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures
General Advice

Show this safety data sheet to the doctor in attendance.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Do not rub affected area. Get medical attention.

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an allergic skin reaction. If skin irritation or rash occurs: Get medical advice/attention.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur.

Ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects Burning. Itching. Rashes. Hives. Coughing and/ or wheezing.

Indication of immediate medical attention and special treatment needed, if necessary
Notes to Physician

May cause sensitization of susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

Explosion Data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment as required. Refer to Section 8. Evacuate personnel to safe areas.

Environmental Precautions

Environmental Precautions Avoid release to the environment. Dispose of contents/container to an approved waste disposal plant. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible Products Acids. Oxidizing agents. Metals. Metal salts.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	30/(%SiO ₂ +2) mg/m ³ TWA, Total Dust;250/(%SiO ₂ +5) mppcf TWA, respirable fraction; 10/(%SiO ₂ +2) mg/m ³ TWA, respirable TWA: 0.1 mg/m ³ (vacated)	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Portland cement 65997-15-1	TWA: 1 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction TWA: 50 mppcf <1% Crystalline silica	IDLH: 5000 mg/m ³ TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Silica 7631-86-9	-	(vacated) TWA: 6 mg/m ³ <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO ₂) mg/m ³ TWA	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³
Calcium oxide 1305-78-8	TWA: 2 mg/m ³	TWA: 5 mg/m ³ (vacated) TWA: 5 mg/m ³	IDLH: 25 mg/m ³ TWA: 2 mg/m ³
Aluminum oxide 1344-28-1	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	-

Calcium sulfate 7778-18-9	TWA: 10 mg/m ³ inhalable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Limestone 1317-65-3	-	TWA: 15 mg/m ³ TWA: 5 mg/m ³ (vacated) TWA: 15 mg/m ³ (vacated) TWA: 5 mg/m ³	TWA: 5 mg/m ³ respirable dust TWA: 10 mg/m ³ total dust
Flue dust, zinc-refining 69012-63-1	TWA: 0.05 mg/m ³ Pb TWA: 0.01 mg/m ³ Cd TWA: 0.002 mg/m ³ Cd respirable fraction	TWA: 50 µg/m ³ Pb Action Level: 30 µg/m ³ Pb Poison, See 29 CFR 1910.1025 Action Level: 2.5 µg/m ³ Cd	IDLH: 9 mg/m ³ Cd dust and fume IDLH: 100 mg/m ³ Pb TWA: 0.050 mg/m ³ Pb
Iron oxide 1309-37-1	TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ fume (vacated) TWA: 10 mg/m ³ fume	IDLH: 2500 mg/m ³ Fe dust and fume TWA: 5 mg/m ³ Fe dust and fume
Silica, fused 60676-86-0	-	(vacated) TWA: 0.1 mg/m ³ respirable dust : (80)/(% SiO ₂) mg/m ³ TWA TWA: 20 mppcf	-
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Skin and Body Protection Respiratory Protection

Tightly fitting safety goggles.
Long sleeved clothing. Impervious gloves.
If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Wear suitable gloves and eye/face protection. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Solid (powder).	Appearance	Grey.
Odor	None.	Odor Threshold	No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	8 - 10	None known
Melting Point/Range	No data available	None known
Boiling Point/Boiling Range	> 100 °C	None known
Flash Point	No data available	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available	
lower flammability limit	No data available	
Vapor Pressure	No data available	None known
Vapor Density	No data available	None known
Specific Gravity	>1.	None known
Water Solubility	Miscible with water	None known

Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known
Flammable Properties	Not flammable	
Explosive Properties	No data available	
Oxidizing Properties	No data available	
Other information		
VOC Content (%)	No data available	

10. STABILITY AND REACTIVITY

Reactivity

No dangerous reaction known under conditions of normal use.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

Acids. Oxidizing agents. Metals. Metal salts.

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide (CO). Carbon dioxide (CO₂).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Eye Contact

Skin Contact

Ingestion

The product itself has not been tested.

May cause irritation of respiratory tract.

Causes serious eye damage.

Irritating to skin. Prolonged contact may cause redness and irritation.

Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Quartz	-	-	-
Silica	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	>2.2 mg/L (Rat) 4 h
Calcium oxide	= 500 mg/kg (Rat)	-	-
Aluminum oxide	> 5000 mg/kg (Rat)	-	-

Calcium sulfate	> 3000 mg/kg (Rat)	-	-
Iron oxide	> 10000 mg/kg (Rat)	-	-
Carbon	10000 mg/kg (Rat)	-	-
Titanium dioxide	> 10000 mg/kg (Rat)	-	> 6820 mg/m ³
Potassium carbonate	>2000 mg/kg (Rat, OECD 401, REACH KEY)	>2000 mg/kg (Rat, REACH KEY)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Burning. Erythema (skin redness). Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing Coughing and/ or wheezing.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization May cause sensitization by skin contact.
Mutagenic Effects No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Quartz	A2	Group 1	Known	X
Silica		Group 3		
Flue dust, zinc-refining	A3 A2	Group 2A Group 1	Known Reasonably Anticipated	X
Iron oxide		Group 3		
Silica, fused		Group 3		
Titanium dioxide		Group 2B		X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to its Carcinogenicity to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity Contains a known or suspected reproductive toxin.

STOT - single exposure Respiratory system.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration Hazard No information available.

Numerical measures of toxicity - Product

Acute Toxicity 37.51419% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 6293 mg/kg; Acute toxicity estimate

LD50 Dermal 47406 mg/kg; Acute toxicity estimate

Inhalation

gas 193935

dust/mist 64.6 mg/L; Acute toxicity estimate

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Silica 7631-86-9	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)
Calcium oxide 1305-78-8		LC50 96 h: = 1070 mg/L static (Cyprinus carpio)		
Aluminum oxide 1344-28-1		LC50 96 h: > 100 mg/L semistatic (Salmo trutta)		LC50 48 h: > 100 mg/L (daphnia magna)
Calcium sulfate 7778-18-9		LC50 96 h: = 2980 mg/L static (Lepomis macrochirus) LC50 96 h: > 1970 mg/L static (Pimephales promelas)		EC50 120 h: = 3200 mg/L (Nitscheria linearis)

Persistence and Degradability No information available.

Bioaccumulation No information available.

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA

All components of this product are either listed or are exempt on the TSCA inventory.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Flue dust, zinc-refining	69012-63-1	1-5	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Flue dust, zinc-refining		X		

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Quartz	14808-60-7	Carcinogen
Flue dust, zinc-refining	69012-63-1	Carcinogen Developmental
Titanium dioxide	13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Quartz	X	X	X	-	X
Portland cement	X	X	X		X
Silica	X	X	X		
Calcium oxide	X	X	X		X
Aluminum oxide	X	X	X		X
Calcium sulfate	X	X	X		
Limestone	X	X	X		X
Flue dust, zinc-refining			X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION				
NFPA	Health Hazard 3	Flammability 0	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 3*	Flammability 0	Physical Hazard 0	Personal Protection X

**Indicates a chronic health hazard.*

Prepared By	Master Wall Inc. 6975 Flat Rock Road Midland, GA 31820 TEL: 706-569-0092
Issuing Date	25-Jan-2016
Revision Date	02-Nov-2021
Revision Note	Chromium Revision

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet