

MasterEmaco T 310Cl

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

SECTION 1. IDENTIFICATION

Product name : MasterEmaco T 310CI

Product code : 00000000051671384 00000000051671384

Manufacturer or supplier's details

Company name of supplier : Master Builders-Admixtures US,LLC

Address : 23700 CHAGRIN BLVD Beachwood OH 44122

Emergency telephone : ChemTel: +1-813-248-0585 USA: +1-800-255-3924 Contract

Number MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin corrosion/irritation : 2

Serious eye damage/eye

irritation

Category 1

Specific target organ toxicity:

- single exposure

: 3

Carcinogenicity (Inhalation) : 1A (Lung)

Specific target organ toxicity

- repeated exposure (Inhalation)

2 (Kidney, Immune system)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or re-

peated exposure.

H372 Causes damage to organs through prolonged or repeated

exposure if inhaled.



MasterEmaco T 310CI

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P201 Obtain special instructions before use.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe dust or mist.

P202 Do not handle until all safety precautions have been read and understood.

P270 Do not eat, drink or smoke when using this product. P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No applicable information available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
crystalline silica	14808-60-7	>= 25 - < 50
Cement, portland, chemicals	65997-15-1	>= 25 - < 50
Calcium sulphate	7778-18-9	>= 5 - < 15
Gypsum (Ca(SO4).2H2O)	13397-24-5	>= 0.3 - < 3
Limestone	1317-65-3	>= 0 - < 3
Silicon dioxide	7631-86-9	>= 0.1 - < 3
sodium nitrite	7632-00-0	>= 0.1 - < 0.2

SECTION 4. FIRST AID MEASURES

MBCC GROUP

MasterEmaco T 310Cl

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation.

May cause cancer.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

MasterEmaco T 310Cl

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

: Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Neutralize with acid.

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid formation of respirable particles.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Containers should be stored tightly sealed in a dry place.

Materials to avoid : Segregate from metals.

Segregate from acids and bases.

Segregate from oxidants.

Segregate from foods and animal feeds.

Further information on stor-

age stability

No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	



MasterEmaco T 310CI

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Silicon dioxide	7631-86-9	REL value	6 mg/m3	NIOSH
		TWA value	6 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA value	0.8 mg/m3	29 CFR 1910.1000 (Table Z-3)
		TWA (Dust)	20 Million parti- cles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
		TWA	6 mg/m3 (Silica)	NIOSH REL
Calcium sulphate	7778-18-9	TWA value (Inhalable fraction)	10 mg/m3	ACGIHTLV



MasterEmaco T 310CI

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

		REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Res- pirable)	5 mg/m3	NIOSH REL
		TWA (total) TWA (total dust)	10 mg/m3 15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Inhal- able particu- late matter)	10 mg/m3 (Calcium)	ACGIH
Gypsum (Ca(SO4).2H2O)	13397-24-5	TWA value (Inhalable fraction)	10 mg/m3	ACGIHTLV
		REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total) TWA (total	10 mg/m3 15 mg/m3	NIOSH REL OSHA Z-1



MasterEmaco T 310CI

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

I	1	dust)		I
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Inhal- able particu- late matter)	10 mg/m3 (Calcium)	ACGIH
Cement, portland, chemicals	65997-15-1	TWA value (Respirable fraction)	1 mg/m3	ACGIHTLV
		REL value (Total)	10 mg/m3	NIOSH
		REL value (Respirable)	5 mg/m3	NIOSH
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	50 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA (Respirable particulate matter)	1 mg/m3	ACGIH
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total) TWA (total	10 mg/m3 15 mg/m3	NIOSH REL OSHA Z-1
		dust) TWA (respir-	5 mg/m3	OSHA Z-1
		able fraction) TWA (Total	10 mg/m3	OSHA P0
		dust)		
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Dust)	50 Million parti- cles per cubic foot	OSHA Z-3
crystalline silica	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV



MasterEmaco T 310CI

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

REL value (Respirable dust)	0.05 mg/m3	NIOSH
TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
TWA (Res- pirable dust)	0.05 mg/m3	OSHA Z-1
TWA (respir- able)	10 mg/m3 / %SiO2+2	OSHA Z-3
TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
PEL (respir- able)	0.05 mg/m3	OSHA CARC
TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

Engineering measures : Provide local exhaust ventilation to maintain recommended

P.E.L.

Personal protective equipment

Respiratory protection : Breathing protection if dusts are formed.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Protective measures : Avoid contact with the skin, eyes and clothing.

Avoid inhalation of dusts.

In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene

and safety practice.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

MBCC GROUP

MasterEmaco T 310CI

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

Appearance : powder

Color : gray

Odor : mild

Odor Threshold : No data available

pH : 13 (68 °F / 20 °C)

(as aqueous solution)

Melting point : No applicable information available.

Flash point : does not flash

Flammability (solid, gas) : not flammable

Self-ignition : not self-igniting

Upper explosion limit / Upper

flammability limit

As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as

long as the product is used appropriately and in accordance

with the intended use.

Lower explosion limit / Lower

flammability limit

As a result of our experience with this product and our

knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance

with the intended use.

Bulk density

Solubility(ies)

: 1,350 kg/m3

Water solubility : insoluble (59 °F / 15 °C)

Partition coefficient: n-

octanol/water

The value has not been determined because the substance is

inorganic.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Self-heating substances : No data available

Molecular weight : No data available



MasterEmaco T 310CI

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac- : No decomposition if stored and applied as directed.

tions

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong bases

Strong acids
Hazardous decomposition : No hazardous decomposition products if stored and handled

products as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Chromate in this product has been reduced. Sensitization due

to chromate within stated shelf-live is unlikely.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.



MasterEmaco T 310CI

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled. May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

Product:

Biodegradability : Remarks: Not applicable for inorganic substances.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: The product will not be readily bioavailable due to

its consistency and insolubility in water.

Components:

crystalline silica:

Partition coefficient: n- : Remarks: not applicable

octanol/water

Cement, portland, chemicals:

Partition coefficient: n- : GLP: no

octanol/water Remarks: not applicable

Calcium sulphate:

Partition coefficient: n- : GLP: no

octanol/water Remarks: The value has not been determined because the

substance is inorganic.

Gypsum (Ca(SO4).2H2O):

Partition coefficient: n- : Remarks: The value has not been determined because the



MasterEmaco T 310Cl

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

octanol/water substance is inorganic.

Silicon dioxide:

Partition coefficient: n-

octanol/water

: Remarks: not applicable

sodium nitrite:

Partition coefficient: n-

octanol/water

Remarks: Study scientifically not justified.

Mobility in soil

Product:

Distribution among environ-

mental compartments

Remarks: Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater

is not expected.

The substance will not evaporate into the atmosphere from

the water surface.

Other adverse effects

Product:

Results of PBT and vPvB

assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or

very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

Additional ecological infor-

mation

There is a high probability that the product is not acutely

harmful to aquatic organisms.

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR



MasterEmaco T 310CI

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

Limestone	1317-65-3
Silicon dioxide	7631-86-9
Calcium sulphate	7778-18-9
Gypsum (Ca(SO4).2H2O)	13397-24-5
Cement, portland, chemicals	65997-15-1
crystalline silica	14808-60-7

New Jersey Right To Know

Limestone	1317-65-3
Calcium sulphate	7778-18-9
Cement, portland, chemicals	65997-15-1
crystalline silica	14808-60-7

California Prop. 65

WARNING: This product can expose you to chemicals including ethylene oxide, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION


Further information

MasterEmaco T 310Cl

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

29 CFR 1910.1000 (Table Z- : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000

3)

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

3) / TWA value

29 CFR 1910.1001-1050 / : OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):

TWA value

ACGIH / TWA : 8-hour, time-weighted average
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):



MasterEmaco T 310Cl

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 08/06/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE



MasterEmaco T 310Cl

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/06/2020 000000259909 Date of first issue: 08/06/2020

, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN