

MasterProtect HB 200 Sandlewood Beige

Version 1.1 Revision Date: 07/06/2021 SDS Number: 000000875248 Date of last issue: 07/06/2021
Date of first issue: 07/06/2021

SECTION 1. IDENTIFICATION

Product name : MasterProtect HB 200 Sandlewood Beige
Product code : 000000000050567460 000000000050567460

Manufacturer or supplier's details

Company name of supplier : Master Builders-Admixtures US,LLC
Address : 23700 CHAGRIN BLVD
Beachwood OH 44122
Emergency telephone : ChemTel: +1-813-248-0585
National Emergency Telephone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Carcinogenicity (Inhalation) : Category 1A
Specific target organ toxicity - repeated exposure : Category 2 (Kidney)
Short-term (acute) aquatic hazard : Category 3
Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H350 May cause cancer by inhalation.
H373 May cause damage to organs (Kidney) through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/

MasterProtect HB 200 Sandewood Beige

Version 1.1 Revision Date: 07/06/2021 SDS Number: 000000875248 Date of last issue: 07/06/2021
 Date of first issue: 07/06/2021

face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No applicable information available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 20 - < 30
Titanium dioxide	13463-67-7	>= 10 - < 20
ethylene glycol	107-21-1	>= 1 - < 5
Mica group minerals	12001-26-2	>= 1 - < 5
Quartz (SiO ₂)	14808-60-7	>= 0.1 - < 1
diuron	330-54-1	< 0.1
3-iodo-2-propynyl butylcarbamate	55406-53-6	< 0.1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.
- In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do NOT induce vomiting.

MasterProtect HB 200 Sandewood Beige

Version 1.1 Revision Date: 07/06/2021 SDS Number: 000000875248 Date of last issue: 07/06/2021
Date of first issue: 07/06/2021

Most important symptoms and effects, both acute and delayed : May cause cancer by inhalation.
May cause damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : water jet

Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.

Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides

Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water.
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.

Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.
Wear eye/face protection.
If exposed to high vapour concentration, leave area immediately.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Large spills should be collected mechanically (remove by pumping) for disposal.
Pick up with inert absorbent material (e.g. sand, earth etc.).
Spilled product should be disposed in accordance with all

MasterProtect HB 200 Sandewood Beige

Version 1.1 Revision Date: 07/06/2021 SDS Number: 000000875248 Date of last issue: 07/06/2021
 Date of first issue: 07/06/2021

applicable government regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid aerosol formation.
 Avoid inhalation of mists/vapours.
 Avoid skin contact.
 Avoid contact with eyes.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
 Protect from direct sunlight.
- Materials to avoid : No applicable information available.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethylene glycol	107-21-1	TWA (Vapor)	25 ppm	ACGIH
		STEL (Vapor)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m ³	ACGIH
Limestone	1317-65-3	C	50 ppm 125 mg/m ³	OSHA P0
		REL value (Respirable)	5 mg/m ³	NIOSH
		REL value (Total)	10 mg/m ³	NIOSH
		PEL (Respirable fraction)	5 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Total dust)	15 mg/m ³	OSHA P0
		TWA (respir-	5 mg/m ³	OSHA P0

MasterProtect HB 200 Sandalwood Beige

Version 1.1 Revision Date: 07/06/2021 SDS Number: 000000875248 Date of last issue: 07/06/2021
 Date of first issue: 07/06/2021

		able dust fraction)		
		TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
Mica group minerals	12001-26-2	TWA value (Respirable fraction)	3 mg/m ³	ACGIH TLV
		REL value (Respirable)	3 mg/m ³	NIOSH
		TWA value (Respirable dust)	3 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA (Respirable particulate matter)	3 mg/m ³	ACGIH
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	3 mg/m ³	NIOSH REL
		TWA (respirable dust fraction)	3 mg/m ³	OSHA P0
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (Total dust)	10 mg/m ³	OSHA P0
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : light protective clothing

MasterProtect HB 200 Sandewood Beige

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2021
1.1	07/06/2021	000000875248	Date of first issue: 07/06/2021

- Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.
- Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : brown
- Odor : sweetish
slight odour
- pH : neutral to slightly alkaline
- Melting point : No applicable information available.
- Boiling point : 379.00 °F / 192.78 °C
401.00 °F / 205.00 °C
- Flash point : 200.01 °F / 93.34 °C
Method: closed cup
- Evaporation rate : No applicable information available.
- Flammability (solid, gas) : not highly flammable
Method: derived from flash point
- Self-ignition : not self-igniting
- Upper explosion limit / Upper flammability limit : No applicable information available.
-

MasterProtect HB 200 Sandewood Beige

Version 1.1 Revision Date: 07/06/2021 SDS Number: 000000875248 Date of last issue: 07/06/2021
Date of first issue: 07/06/2021

Lower explosion limit / Lower flammability limit	:	3.2 %(V) No applicable information available.
Vapor pressure	:	No applicable information available.
Relative vapor density	:	Heavier than air.
Relative density	:	No applicable information available.
Density	:	1.3500 g/cm ³ (68.00 °F / 20.00 °C) 1.4700 g/cm ³ (68.00 °F / 20.00 °C)
Solubility(ies)		
Water solubility	:	partly soluble (68.00 °F / 20.00 °C)
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	No applicable information available.
Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	5,600.000 mPa.s (73.40 °F / 23.00 °C)
Viscosity, kinematic	:	No applicable information available.
Explosive properties	:	Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Sublimation point	:	No applicable information available.
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	The product is stable if stored and handled as prescribed/indicated.
Conditions to avoid	:	See SDS section 7 - Handling and storage.

MasterProtect HB 200 Sandeewood Beige

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2021
1.1	07/06/2021	000000875248	Date of first issue: 07/06/2021

Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC	Group 1: Carcinogenic to humans	
	Quartz (SiO ₂) (Silica dust, crystalline)	14808-60-7
	Group 2B: Possibly carcinogenic to humans	
	Titanium dioxide	13463-67-7
OSHA	OSHA specifically regulated carcinogen Quartz (SiO ₂) (crystalline silica)	14808-60-7

NTP Known to be human carcinogen

MasterProtect HB 200 Sandewood Beige

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2021
1.1	07/06/2021	000000875248	Date of first issue: 07/06/2021

Quartz (SiO₂) 14808-60-7
(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information**Product:**

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:****Ecotoxicology Assessment**

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:**diuron:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

3-iodo-2-propynyl butylcarbamate:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

Persistence and degradability

No data available

MasterProtect HB 200 Sandlewood Beige

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2021
1.1	07/06/2021	000000875248	Date of first issue: 07/06/2021

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
carbendazim	10605-21-7	10	*

MasterProtect HB 200 Sandlewood Beige

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2021
1.1	07/06/2021	000000875248	Date of first issue: 07/06/2021

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

ethylene glycol 107-21-1

US State Regulations**Pennsylvania Right To Know**

water	7732-18-5
Limestone	1317-65-3
Titanium dioxide	13463-67-7
ethylene glycol	107-21-1
Mica group minerals	12001-26-2
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
diuron	330-54-1
ammonia	7664-41-7
acetaldehyde	75-07-0
1,4-dioxane	123-91-1
ethylene oxide	75-21-8
propylene oxide	75-56-9
ammonia, aqueous solution	1336-21-6

New Jersey Right To Know

water	7732-18-5
Limestone	1317-65-3
Titanium dioxide	13463-67-7
Feldspar-group minerals	68476-25-5
ethylene glycol	107-21-1
Mica group minerals	12001-26-2
Quartz (SiO ₂)	14808-60-7
Quartz (SiO ₂)	14808-60-7

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL


TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

SECTION 16. OTHER INFORMATION**Further information**


MasterProtect HB 200 Sandlewood Beige

Version 1.1 Revision Date: 07/06/2021 SDS Number: 000000875248 Date of last issue: 07/06/2021
 Date of first issue: 07/06/2021

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- 29 CFR 1910.1000 (Table Z-3) : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
- 29 CFR 1910.1000 (Table Z-3) / TWA value : Time Weighted Average (TWA):
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- ACGIHTLV / TWA value : Time Weighted Average (TWA):
- NIOSH / REL value : Recommended exposure limit (REL):
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA P0 / C : Ceiling limit
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-3 / TWA : 8-hour time weighted average

MasterProtect HB 200 Sandewood Beige

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2021
1.1	07/06/2021	000000875248	Date of first issue: 07/06/2021

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/06/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN