

Product Description	R-value	Thickness	L	W	Location
ROXUL SAFE™ Firestop and Head of Wall Applications Semi-rigid, mineral wool insulation approved for use in fire rated joints, through penetrations and perimeter fire containment systems.	N/A*	<input type="checkbox"/> 2"	<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
		<input type="checkbox"/> 3"	<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
		<input type="checkbox"/> 4"	<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
COMFORTBATT® SS Exterior Steel Stud Batt Stone wool batt insulation designed for thermal resistance in exterior steel stud wall applications. It's special flexible characteristic at the insulation edge ensures the expected R-value is achieved.	10	<input type="checkbox"/> 2.5"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16.25"	
	14	<input type="checkbox"/> 3.5"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16.25"	
				<input type="checkbox"/> 24.25"	
	22.5	<input type="checkbox"/> 6"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16.25"	
				<input type="checkbox"/> 24.25"	
	24	<input type="checkbox"/> 6"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16.25"	
				<input type="checkbox"/> 24.25"	

Notes: