

Safety Data Sheet


according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 15, 2020

1 Identification

- **Product identifier**
- **Trade name:** XL Perm Ultra NP
- **Other means of identification:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Non-asphaltic non-permeable air barrier.
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Pecora Corporation
165 Wambold Road
Harleysville, PA 19438
215-723-6051
- **Emergency telephone number:**
CHEMTREC
1-800-424-9300 (US/Canada)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Skin Irrit. 2 H315 Causes skin irritation.
Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 2 H351 Suspected of causing cancer.
Repr. 1B H360 May damage fertility or the unborn child.
- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**

GHS08
- **Signal word:** Danger
- **Hazard statements:**
H315 Causes skin irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H360 May damage fertility or the unborn child.
- **Precautionary statements:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash thoroughly after handling.
P272 Contaminated work clothing must not be allowed out of the workplace.

(Cont'd. on page 2)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 15, 2020

Trade name: XL Perm Ultra NP

(Cont'd. of page 1)

- P280 Wear protective gloves/protective clothing/eye protection/face protection.
P284 [In case of inadequate ventilation] wear respiratory protection.
P302+P352 If on skin: Wash with plenty of soap and water.
P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.
P362+P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

556-67-2	Octamethylcyclotetrasiloxane ⚠ Flam. Liq. 3, H226 ⚠ Repr. 2, H361	<20%
9003-29-6	Butene, homopolymer (products derived from either/or But-1-ene/But-2-ene) ⚠ Asp. Tox. 1, H304 ⚠ Skin Irrit. 2, H315 Flam. Liq. 4, H227	<15%
14807-96-6	Talc	<15%
1317-65-3	Limestone	<10%
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic (Nota L, -R45, <3% dimethyl sulfoxide) ⚠ Asp. Tox. 1, H304	<10%
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic ⚠ Asp. Tox. 1, H304	<5%
64742-94-5	Solvent naphtha (petroleum), heavy arom. ⚠ Asp. Tox. 1, H304 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 Flam. Liq. 4, H227	<2.5%
111-92-2	di-n-butylamine ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	<2.5%
1330-20-7	Xylene ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	<2.5%
4083-64-1	4-isocyanatosulphonyltoluene ⚠ Resp. Sens. 1, H334 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	<2.5%

(Cont'd. on page 3)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 15, 2020

Trade name: XL Perm Ultra NP

(Cont'd. of page 2)

41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ⚠ Skin Sens. 1, H317	<1%
14808-60-7	Quartz	<1%
	Trade Secret Reaction product of decanoic acid, 12-hydroxystearic acid and 1,2-ethanediamine ⚠ Skin Sens. 1, H317	<1%
25973-55-1	2-(2H-benzotriazol-2-yl)-4,6-ditertpentylphenol PBT; vPvB ⚠ STOT RE 2, H373 Combustible Dust	<1%
82919-37-7	Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ⚠ Skin Sens. 1, H317	<1%
1333-86-4	Carbon black	<1%
22673-19-4	dibutylbis(pentane-2,4-dionato-O,O')tin ⚠ Muta. 2, H341; Repr. 1B, H360; STOT SE 1, H370; STOT RE 1, H372 ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	<1%
100-41-4	Ethylbenzene ⚠ Flam. Liq. 2, H225 ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332 Eye Irrit. 2B, H320	<1%

• **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

• **Description of first aid measures**

• **After inhalation:** Supply fresh air; consult doctor in case of complaints.

• **After skin contact:**

Wash with soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

• **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

• **Most important symptoms and effects, both acute and delayed:**

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Causes skin irritation.

Allergic reactions

• **Danger:**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Suspected of causing cancer.

May damage fertility or the unborn child.

(Cont'd. on page 4)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 15, 2020

Trade name: XL Perm Ultra NP

(Cont'd. of page 3)

· **Indication of any immediate medical attention and special treatment needed:**

Contains 4-isocyanatosulphonyltoluene, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Trade Secret Reaction product of decanoic acid, 12-hydroxystearic acid and 1,2-ethanediamine, Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate, dibutylbis(pentane-2,4-dionato-O,O')tin. May produce an allergic reaction.

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Carbon dioxide

Fire-extinguishing powder

Foam

Gaseous extinguishing agents

Water fog / haze

· **For safety reasons unsuitable extinguishing agents:** Water stream.

· **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation.

Use personal protective equipment as required.

Particular danger of slipping on leaked/spilled product.

· **Environmental precautions** Avoid release to the environment.

· **Methods and material for containment and cleaning up**

Towel or mop up material and collect in a suitable container.

For larger spills, add sawdust, chalk or other inert binding material, then sweep up and discard.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling**

· **Precautions for safe handling:**

Open and handle receptacle with care.

Keep out of reach of children.

Avoid contact with the eyes and skin.

(Cont'd. on page 5)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 15, 2020

Trade name: XL Perm Ultra NP

(Cont'd. of page 4)

Avoid breathing mist, vapors, or spray.
Keep away from open flame or other ignition sources.

- **Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:**
Store in cool, dry conditions in well sealed receptacles.
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidizing agents.
- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

556-67-2 Octamethylcyclotetrasiloxane

WEEL (USA)	Long-term value: 10* ppm *OARS WEEL
------------	--

14807-96-6 Talc

PEL (USA)	Long-term value: 20 mppcf ppm (containing <1% Quartz)
REL (USA)	Long-term value: 2* mg/m ³ *respirable dust; and <1% Quartz
TLV (USA)	Long-term value: 2* mg/m ³ *as respirable fraction; E
EL (Canada)	Long-term value: 2 *0.1 f/cc mg/m ³ resp. *if contains asbestos : ACGIH A1, IARC 1
EV (Canada)	Long-term value: 2* mg/m ³ , 2 f/cc ppm *respirable
LMPE (Mexico)	Long-term value: 2* mg/m ³ A4, *fracción respirable

1317-65-3 Limestone

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn

111-92-2 di-n-butylamine

WEEL (USA)	Ceiling limit value: 5 ppm Skin
------------	------------------------------------

1330-20-7 Xylene

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm

(Cont'd. on page 6)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 15, 2020

Trade name: XL Perm Ultra NP

(Cont'd. of page 5)

TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm
EV (Canada)	Short-term value: 650 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
LMPE (Mexico)	Short-term value: 150 ppm Long-term value: 100 ppm A4, IBE

14808-60-7 Quartz

PEL (USA)	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL (USA)	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV (USA)	Long-term value: 0.025* mg/m ³ *as respirable fraction
EL (Canada)	Long-term value: 0.025 mg/m ³ ACGIH A2; IARC 1
EV (Canada)	Long-term value: 0.10* mg/m ³ *respirable fraction
LMPE (Mexico)	Long-term value: 0.025* mg/m ³ A2, *fracción respirable

1333-86-4 Carbon black

PEL (USA)	Long-term value: 3.5 mg/m ³
REL (USA)	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV (USA)	Long-term value: 3* mg/m ³ *inhalable fraction
EL (Canada)	Long-term value: 3 mg/m ³ IARC 2B
EV (Canada)	Long-term value: 3.5 mg/m ³
LMPE (Mexico)	Long-term value: 3* mg/m ³ A3, *fracción inhalable

100-41-4 Ethylbenzene

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 87 mg/m ³ , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm IARC 2B
EV (Canada)	Short-term value: 540 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
LMPE (Mexico)	Long-term value: 20 ppm

(Cont'd. on page 7)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 15, 2020

Trade name: XL Perm Ultra NP

(Cont'd. of page 6)

· **Ingredients with biological limit values:**

1330-20-7 Xylene

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

100-41-4 Ethylbenzene

BEI (USA)	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

· **Exposure controls**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.
 Keep away from foodstuffs, beverages and feed.
 Avoid contact with the eyes and skin.
 Avoid breathing mist, vapors, or spray.

· **Engineering controls:** No relevant information available.

· **Breathing equipment:** Suitable respiratory protective device recommended.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:**



Safety glasses

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment**

Avoid release to the environment.

· **Risk management measures** No special requirements.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **Appearance:**

Form:	Liquid
Color:	According to product specification
Odor:	Not determined.

(Cont'd. on page 8)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 15, 2020

Trade name: XL Perm Ultra NP

(Cont'd. of page 6)

· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	Not determined.
· Flash point:	58.9 °C (138 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits	
· Lower:	Not determined.
· Upper:	Not determined.
· Oxidizing properties:	Non-oxidizing.
· Vapor pressure:	Not determined.
· Density:	
· Relative density:	1.14
· Vapor density:	Not determined.
· Evaporation rate:	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity	
· Dynamic:	Not determined.
· Kinematic at 40 °C (104 °F):	>20.5 mm ² /s
· VOC content:	<50 g/L
· Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Reacts with strong acids and alkali.
Reacts with oxidizing agents.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidizers, strong bases, strong acids
- **Hazardous decomposition products**
Under fire conditions only:
Sulfur oxides (SO_x)

(Cont'd. on page 9)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 15, 2020

Trade name: XL Perm Ultra NP

Carbon monoxide and carbon dioxide

(Cont'd. of page 6)

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

9003-29-6 Butene, homopolymer (products derived from either/or But-1-ene/But-2-ene)

Oral	LD50	>34600 mg/kg (rat)
Dermal	LD50	>10250 mg/kg (rabbit)
Inhalative	LC50/4h	>17300 mg/l (rat)

64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (Nota L, -R45, <3% dimethyl sulfoxide)

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)

64742-94-5 Solvent naphtha (petroleum), heavy arom.

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

111-92-2 di-n-butylamine

Oral	LD50	189 mg/kg (rat)
Dermal	LD50	1010 mg/kg (rabbit)

1330-20-7 Xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

· **Primary irritant effect:**

· **On the skin:** Irritant to skin and mucous membranes.

· **On the eye:** Based on available data, the classification criteria are not met.

· **Sensitization:** May cause sensitization by inhalation and skin contact.

· **IARC (International Agency for Research on Cancer):**

14808-60-7	Quartz	1
1333-86-4	Carbon black	2B
100-41-4	Ethylbenzene	2B

· **NTP (National Toxicology Program):**

14808-60-7	Quartz
------------	--------

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

Ingestion.
Inhalation.
Eye contact.
Skin contact.

· **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

· **Carcinogenicity:** Suspected of causing cancer.

· **Reproductive toxicity:** May damage fertility or the unborn child.

(Cont'd. on page 10)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 15, 2020

Trade name: XL Perm Ultra NP

(Cont'd. of page 9)

- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity**
Harmful to aquatic life with long lasting effects.

556-67-2 Octamethylcyclotetrasiloxane

LC50 >22 mg/l (Oncorhynchus mykiss)

EC50 >15 mg/l (daphnia)

64742-94-5 Solvent naphtha (petroleum), heavy arom.

LC50 3.6 mg/l (Oncorhynchus mykiss)

1330-20-7 Xylene

LC50 13.4 mg/l (pimephales promelas)

41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

LC50 0.97 mg/l (Iepomis macrochirus)

- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Smaller quantities can be disposed of with household waste.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR/RID/ADN, IMDG, IATA** Not regulated.
- **UN proper shipping name**
- **DOT, ADR/RID/ADN, IMDG, IATA** Not regulated.
- **Transport hazard class(es)**

(Cont'd. on page 11)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 15, 2020

Trade name: XL Perm Ultra NP

(Cont'd. of page 10)

· DOT, ADR/RID/ADN, IMDG, IATA	
· Class	Not regulated.
· Packing group	
· DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.
· Environmental hazards	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 | Xylene

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed or exempt.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

14807-96-6 | Talc

14808-60-7 | Quartz

1333-86-4 | Carbon black

100-41-4 | Ethylbenzene

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **EPA (Environmental Protection Agency):**

1330-20-7 | Xylene

100-41-4 | Ethylbenzene

I

D

· **IARC (International Agency for Research on Cancer):**

14808-60-7 | Quartz

1

(Cont'd. on page 12)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 15, 2020

Trade name: XL Perm Ultra NP

(Cont'd. of page 10)

1333-86-4	Carbon black	2B
100-41-4	Ethylbenzene	2B
· Canadian Domestic Substances List (DSL):		
All ingredients are listed or exempt.		

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 2: Germ cell mutagenicity – Category 2

Carc. 2: Carcinogenicity – Category 2

Repr. 1B: Reproductive toxicity – Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtel.com