

MasterTop TC 693 LIGHT TB PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/24/2021 000000969888 Date of first issue: 05/24/2021

SECTION 1. IDENTIFICATION

Product name : MasterTop TC 693 LIGHT TB PTA

Product code : 00000000050683237 00000000050683237

Other means of identification : MTop TC 693 Light Tint Base Part A

Manufacturer or supplier's details

Company name of supplier : Colorbiotics, LLC

Address : 23700 CHAGRIN BLVD

Beachwood OH 44122

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : floor coating

Restrictions on use : Reserved for industrial and professional use.

National Emergency

Telephone Number

USA: +1-800-255-3924 ChemTel contract no. MIS9240420

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Eye irritation : Category 2A

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation. H350 May cause cancer by inhalation.



MasterTop TC 693 LIGHT TB PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/24/2021 000000969888 Date of first issue: 05/24/2021

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester	136210-30-5	>= 30 - < 50
Limestone	1317-65-3	>= 20 - < 30
Titanium dioxide	13463-67-7	>= 10 - < 20
calcium oxide	1305-78-8	>= 1 - < 5
Diethyl fumarate	623-91-6	>= 1 - < 5
bis(1,2,2,6,6-pentamethyl-4- piperidyl)sebacate	41556-26-7	>= 0.1 - < 1



MasterTop TC 693 LIGHT TB PTA

Version **Revision Date:** SDS Number: Date of last issue: -

05/24/2021 000000969888 Date of first issue: 05/24/2021 1.0

Methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	82919-37-7	>= 0.1 - < 1
Quartz (SiO2)	14808-60-7	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

After contact with skin, wash immediately with plenty of water In case of skin contact

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact Hold eyes open and rinse slowly and gently with water for 15

to 20 minutes. Remove contact lenses, if present, after first 5

minutes, then continue rinsing.

If eye irritation persists, consult a specialist.

If swallowed Immediately rinse mouth and then drink 200-300 ml of water,

> seek medical attention. Do NOT induce vomiting.

Most important symptoms

and effects, both acute and

delayed

May cause an allergic skin reaction.

Causes serious eye irritation. May cause cancer by inhalation.

Notes to physician Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Foam

> Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides

fumes/smoke carbon black carbon oxides

Further information The degree of risk is governed by the burning substance and



MasterTop TC 693 LIGHT TB PTA

Version **Revision Date:** SDS Number: Date of last issue: -

05/24/2021 000000969888 Date of first issue: 05/24/2021 1.0

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

for fire-fighters

Special protective equipment : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Do not breathe vapour/aerosol/spray mists.

Wear eye/face protection.

If exposed to high vapour concentration, leave area immedi-

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Contain contaminated water/firefighting water. **Environmental precautions**

Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up Large spills should be collected mechanically (remove by

pumping) for disposal.

Pick up with inert absorbent material (e.g. sand, earth etc.). Spilled product should be disposed in accordance with all

applicable government regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling Avoid aerosol formation.

Avoid inhalation of mists/vapours.

Avoid skin contact. Avoid contact with eyes.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, wellventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Further information on stor-

age stability

Stable under recommended storage conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
Limestone	1317-65-3	REL value	5 mg/m3	NIOSH
		(Respirable)		
		REL value	10 mg/m3	NIOSH



MasterTop TC 693 LIGHT TB PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/24/2021 000000969888 Date of first issue: 05/24/2021

	ſ	/T-4-I)	I	1
		(Total)	5 / 0	00.055
		PEL (Respir-	5 mg/m3	29 CFR
		able fraction)		1910.1000
		DEL /T-(-)	45 0	(Table Z-1)
		PEL (Total	15 mg/m3	29 CFR
		dust)		1910.1000
			- / 0	(Table Z-1)
		TWA value	5 mg/m3	29 CFR
		(Respirable		1910.1000
		fraction)	15 / 0	(Table Z-1-A)
		TWA value	15 mg/m3	29 CFR
		(Total dust)		1910.1000
				(Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total	15 mg/m3	OSHA P0
		dust)		
		TWA (respir-	5 mg/m3	OSHA P0
		able dust	_	
		fraction)		
		TWA (Res-	5 mg/m3	NIOSH REL
		pirable)	(Calcium car-	
		<u> </u>	bonate)	
		TWA (total)	10 mg/m3	NIOSH REL
			(Calcium car-	
			bonate)	
Titanium dioxide	13463-67-7	TWA (total	15 mg/m3	OSHA Z-1
		dust)		
		TWA (Total	10 mg/m3	OSHA P0
		dust)		
		TWA	10 mg/m3	ACGIH
			(Titanium dioxide)	
calcium oxide	1305-78-8	TWA	2 mg/m3	ACGIH
		TWA	2 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
O (C:O2)				
Quartz (SIOZ)	14808-60-7			
Quartz (SiO2)	14808-60-7	TWA value (Respirable	0.025 mg/m3	ACGIHTLV
Quartz (SIO2)	14808-60-7	TWA value (Respirable		
Quartz (SIO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
Quartz (SIO2)	14808-60-7	TWA value (Respirable	0.025 mg/m3 0.05 mg/m3	
Quartz (SIO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV 29 CFR
Quartz (SIO2)	14808-60-7	TWA value (Respirable fraction) TWA value	0.025 mg/m3 0.05 mg/m3 (Respirable dust)	ACGIHTLV 29 CFR 1910.1001-
Quartz (SIO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3 0.05 mg/m3 (Respirable dust) 0.025 mg/m3	ACGIHTLV 29 CFR 1910.1001- 1050
Quartz (SIO2)	14808-60-7	TWA value (Respirable fraction) TWA value	0.025 mg/m3 0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050 29 CFR
Quartz (SIO2)	14808-60-7	TWA value (Respirable fraction) TWA value OSHA Action level	0.025 mg/m3 0.05 mg/m3 (Respirable dust) 0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050 29 CFR 1910.1001- 1050
Quartz (SIO2)	14808-60-7	TWA value (Respirable fraction) TWA value OSHA Action level REL value	0.025 mg/m3 0.05 mg/m3 (Respirable dust) 0.025 mg/m3	29 CFR 1910.1001- 1050 29 CFR 1910.1001-
Quartz (SIO2)	14808-60-7	TWA value (Respirable fraction) TWA value OSHA Action level REL value (Respirable	0.025 mg/m3 0.05 mg/m3 (Respirable dust) 0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050 29 CFR 1910.1001- 1050
Quartz (SIO2)	14808-60-7	TWA value (Respirable fraction) TWA value OSHA Action level REL value (Respirable dust)	0.025 mg/m3 0.05 mg/m3 (Respirable dust) 0.025 mg/m3 (Respirable dust) 0.05 mg/m3	29 CFR 1910.1001- 1050 29 CFR 1910.1001- 1050 NIOSH
Quanz (SIO2)	14808-60-7	TWA value (Respirable fraction) TWA value OSHA Action level REL value (Respirable dust) TWA (Res-	0.025 mg/m3 0.05 mg/m3 (Respirable dust) 0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050 29 CFR 1910.1001- 1050
Quanz (SIO2)	14808-60-7	TWA value (Respirable fraction) TWA value OSHA Action level REL value (Respirable dust)	0.025 mg/m3 0.05 mg/m3 (Respirable dust) 0.025 mg/m3 (Respirable dust) 0.05 mg/m3	29 CFR 1910.1001- 1050 29 CFR 1910.1001- 1050 NIOSH



MasterTop TC 693 LIGHT TB PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/24/2021 000000969888 Date of first issue: 05/24/2021

TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
PEL (respir- able)	0.05 mg/m3	OSHA CARC
TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupa-

tional exposure limits they must use appropriate certified

respirators.

Wear a NIOSH-certified (or equivalent) respirator as neces-

sary.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Tightly fitting safety goggles (chemical goggles).

Skin and body protection : Body protection must be chosen based on level of activity

and exposure.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid



MasterTop TC 693 LIGHT TB PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/24/2021 000000969888 Date of first issue: 05/24/2021

Color : off-white

Odor : faint odour

Odor Threshold : not determined

pH : No data available

Melting point : No data available

Boiling point : No data available

Flash point : 324 °F / 162 °C

Evaporation rate : No data available

Flammability (liquids) : The product is not flammable.

Self-ignition : not self-igniting

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 1.58 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No decomposition if correctly stored and handled.

Viscosity

Viscosity, dynamic : No data available



MasterTop TC 693 LIGHT TB PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/24/2021 000000969888 Date of first issue: 05/24/2021

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation point : No data available

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.



MasterTop TC 693 LIGHT TB PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/24/2021 000000969888 Date of first issue: 05/24/2021

Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

(Silica dust, crystalline)

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

OSHA specifically regulated carcinogen

Quartz (SiO2) 14808-60-7

(crystalline silica)

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

M-Factor (Acute aquatic tox- : 1

icity)



MasterTop TC 693 LIGHT TB PTA

Version Revision Date: SDS Number: Date of last issue: -

: 1

1.0 05/24/2021 000000969888 Date of first issue: 05/24/2021

M-Factor (Chronic aquatic

toxicity)

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possi-

ble; then it can be passed on for recycling after being thor-

oughly cleaned.

Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good



MasterTop TC 693 LIGHT TB PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/24/2021 000000969888 Date of first issue: 05/24/2021

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

Limestone 1317-65-3
Titanium dioxide 13463-67-7
calcium oxide 1305-78-8

New Jersey Right To Know

 Limestone
 1317-65-3

 Titanium dioxide
 13463-67-7

 calcium oxide
 1305-78-8

 Quartz (SiO2)
 14808-60-7

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and

methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed as


active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations



MasterTop TC 693 LIGHT TB PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/24/2021 000000969888 Date of first issue: 05/24/2021

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1001-1050 / : OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):

TWA value

ACGIH / TWA : 8-hour, time-weighted average ACGIHTLV / TWA value : Time Weighted Average (TWA): NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC



MasterTop TC 693 LIGHT TB PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/24/2021 000000969888 Date of first issue: 05/24/2021

- No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/24/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN