

**SECTION 1. IDENTIFICATION**

Product name : Sikagard® 550W Elastocolor

Company name : Sika Corporation  
201 Polito Avenue  
Lyndhurst, NJ 07071  
USA  
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300  
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

**Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Mixtures****Components**

Chemical name	CAS-No.	Classification	Concentration (% w/w)
zinc oxide	1314-13-2		$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

General advice : No hazards which require special first aid measures.



- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : No known significant effects or hazards.  
No information available.
- Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Environmental precautions : Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).  
Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : For personal protection see section 8.  
No special handling advice required.  
Follow standard hygiene measures when handling chemical products.



Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Store in accordance with local regulations.

Materials to avoid : No special restrictions on storage with other products.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
zinc oxide	1314-13-2	TWA (Respirable particulate matter)	2 mg/m <sup>3</sup>	ACGIH
		STEL (Respirable particulate matter)	10 mg/m <sup>3</sup>	ACGIH
		TWA (Fumes)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total dust)	10 mg/m <sup>3</sup>	OSHA P0
		TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Fumes)	5 mg/m <sup>3</sup>	OSHA P0
		STEL (Fumes)	10 mg/m <sup>3</sup>	OSHA P0
		TWA (Dust)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (Fumes)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Fumes)	10 mg/m <sup>3</sup>	NIOSH REL
		C (Dust)	15 mg/m <sup>3</sup>	NIOSH REL

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

**Personal protective equipment**

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Wash hands before breaks and immediately after handling the product.  
Remove contaminated clothing and protective equipment before entering eating areas.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : viscous liquid
- Color : various
- Odor : like acrylic
- Odor Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 212 °F / > 100 °C  
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available



Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	23 hpa
Relative vapor density	:	No data available
Density	:	ca. 1.37 g/cm <sup>3</sup> (73 °F / 23 °C)
Solubility(ies)		
Water solubility	:	slightly soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	77 g/l

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Components:****zinc oxide:**

Acute oral toxicity : LD50 Oral (Rat): > 15,000 mg/kg  
 Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**IARC** Group 2B: Possibly carcinogenic to humans  
 titanium dioxide 13463-67-7

**OSHA** Not applicable

**NTP** Not applicable

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks : Titanium dioxide (13463-67-7)  
 In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload



and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### **zinc oxide:**

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 0.17 mg/l

##### **Persistence and degradability**

No data available

##### **Bioaccumulative potential**

No data available

##### **Mobility in soil**

No data available

##### **Other adverse effects**

#### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.  
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
May be harmful to the environment if released in large quantities.  
Water polluting material.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.



Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### IATA-DGR

UN/ID No. : UN 3082  
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
(2-octyl-2H-isothiazole-3-one (OIT))  
Class : 9  
Packing group : III  
Labels : Miscellaneous  
Packing instruction (cargo aircraft) : 964  
Packing instruction (passenger aircraft) : 964

#### IMDG-Code

UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(2-octyl-2H-isothiazole-3-one (OIT))  
Class : 9  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Marine pollutant : yes

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

**TSCA list** : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

### EPCRA - Emergency Planning and Community Right-to-Know

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.





**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards


**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

zinc oxide                      1314-13-2                      >= 1 - < 5 %

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

**California Prop 65**

 **WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**SECTION 16. OTHER INFORMATION**

**Full text of other abbreviations**

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
- NIOSH REL / C : Ceiling value not be exceeded at any time.
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA P0 / STEL : Short-term exposure limit
- OSHA Z-1 / TWA : 8-hour time weighted average

**Notes to Reader**

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE

**Sikagard® 550W Elastocolor**



Revision Date 06/15/2021

Print Date 06/15/2021

---

RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 06/15/2021

000000604479  
US / Z8