



Sika[®] Level SkimCoat

FAST SETTING, SMOOTHING AND FINISHING COMPOUND

- Levels new and old floors
- Re-workable up to 30 minutes after mixing; No additional water needed
- No MVER (Moisture Vapor Emission Rate) limits
- For Interior use only

Packaging available

10 lb. Bag



BUILDING TRUST



Sika® Level SkimCoat

FAST SETTING, SMOOTHING AND FINISHING COMPOUND

WHERE TO USE

- For Interior use only
- Concrete, wood subfloors, ceramic and quarry tiles
- Minor defects, holes, and cracks in concrete and wood subfloors
- Pre-fill non-moving joints and seams
- Radiant heating systems

FEATURES AND BENEFITS

- Easy to prepare and quick to apply
- True feather edge material
- Zero VOC's
- Levels new and old floors
- Adhesion to substrates, subfloors and stable adhesive residue.
- Rapid Setting
- Excellent standard of finish can be achieved to allow direct application of floor coverings

NOTE: Always refer to current PDS and SDS for detailed performance specifications prior to use.

TYPICAL DATA (Material and curing conditions @ 73°F (23°C) and 50% R.H.)

Color	Gray
Application Thickness	Feather edge - 1/2". (13 mm)
Working Time	10 to 20 min.
Set Times	Initial: 20 to 30 min. Final: 30 to 60 min.
Compressive Strength (ASTM C109)	3,700 psi (25 MPa) at 28 days
Flexural Strength (ASTM C348)	1,300 psi (9 MPa) at 28 days
Flammability (ASTM E84)	Flame Spread 0; Smoke Development 0
VOC (EPA METHOD 24)	0 g/l

Sika® Classification Table

Strength					
Smoothness					
Depth					
Speed					



FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.sikasecure.com

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225



BUILDING TRUST

