

SBS-MODIFIED BITUMEN MEMBRANES
COLPHENE®



COLPHENE FLAM 180 FR GR

PRODUCT CODE

01226

Scan QR code with
the SOPREMA toolbox
app for more information.



COLPHENE®

FLAM 180 FR GR

COLPHENE Flam 180 FR GR (fire retardant, granulated) is an SBS-modified bitumen cap ply for use in approved multi-ply waterproofing assemblies. COLPHENE Flam 180 FR GR is composed of a proprietary formulation of elastomeric styrene-butadiene-styrene (SBS) polymer modified bitumen and is reinforced with tough, dimensionally stable non-woven polyester mat. The topside is surfaced with ceramic coated granules and underside is surfaced with polyolefin burn-off film to optimize heat welding.

INSTALLATION

Prior to installation, unroll COLPHENE Flam 180 FR GR onto the surface and allow to relax. Position COLPHENE Flam 180 FR GR in desired position and back roll the product. COLPHENE Flam 180 FR GR is then heat welded to approved substrates.

PRODUCT PROPERTIES

REINFORCEMENT	Polyester
THICKNESS	157 mils (4.0 mm)
TOPSIDE	Granules
UNDERSIDE	Burn-off Film

APPLICATION



HEAT WELDED

RELATED PRODUCTS

COLPHENE 180 PS
COLPHENE FLAM 180
COLPHENE FLAM 250 FR GR