



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

1 Identification

- · Product identifier
- · Trade name: Pecora Deck 804 Intermediate Coat
- · Other means of identification: No other identifiers
- · Recommended use and restriction on use
- · Recommended use: Pedestrian and Vehicular Deck Coating System
- · Restrictions on use: No relevant information available.
- · Details of the supplier of the Safety Data Sheet
- Manufacturer/Supplier: Pecora Corporation 165 Wambold Road Harleysville, PA 19438 215-723-6051
- Emergency telephone number: CHEMTREC

1-800-424-9300 (US/Canada)

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapor.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



- · Signal word: Warning
- · Hazard statements:

H226 Flammable liquid and vapor.

- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Useexplosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.

(Cont'd. on page 2)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 804 Intermediate Coat

| | | (Cont'd. of page 1) |
|-----------|---|---------------------|
| P261 | Avoid breathing dust/fume/gas/mist/vapors/spray | |
| P272 | Contaminated work clothing must not be allowed out of the workplace. | |
| P280 | Wear protective gloves/protective clothing/eye protection. | |
| | If on skin (or hair): Take off immediately all contaminated clothing. Rinse water/shower. | e skin with |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. | |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. | |
| P363 | Wash contaminated clothing before reuse. | |
| P370+P378 | In case of fire: Use foam, powder, or carbon dioxide for extinction. | |
| P403+P235 | Store in a well-ventilated place. Keep cool. | |
| P405 | Store locked up. | |
| P501 | Dispose of contents/container in accordance with local/regional/national regulations. | /international |

· Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

| 1332-58-7 | Kaolin | <20 |
|------------|--|-----|
| 556-67-2 | Octamethylcyclotetrasiloxane | <20 |
| | Flam. Liq. 3, H226 Repr. 2, H361 | |
| 14807-96-6 | Talc | <10 |
| 64742-95-6 | Solvent naphtha (petroleum), light arom. | <1(|
| | Flam. Liq. 3, H226 Asp. Tox. 1, H304 | |
| 13463-67-7 | Titanium dioxide | <3 |
| 95-63-6 | 1,2,4-trimethylbenzene | <3 |
| | Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 | |
| 25551-13-7 | trimethylbenzene | <3 |
| | Flam. Liq. 3, H226 Skin Irrit. 2, H315; Eye Irrit. 2A, H319 | |
| 108-67-8 | mesitylene | <1 |
| | Flam. Liq. 3, H226 STOT SE 3, H335 | |
| 98-56-6 | 4-chloro-α,α,α-trifluorotoluene | <1 |
| | ♦ Flam. Liq. 3, H226 ♦ Carc. 2, H351 | |
| | Skin Sens. 1B, H317 | |
| | Eye Irrit. 2B, H320 | |
| 14808-60-7 | Quartz | <1 |
| 128-37-0 | 2,6-di-tert-butyl-p-cresol | <1 |
| 11161 16 1 | Cristobalite | <1 |



(Cont'd. of page 2)

<1%



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 804 Intermediate Coat

41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate Skin Sens. 1, H317

4 First-aid measures

Description of first aid measures · After inhalation: Supply fresh air; consult doctor in case of complaints. Provide oxygen treatment if affected person has difficulty breathing. · After skin contact: Wash with soap and water. If skin irritation or rash occurs: Get medical advice/attention. After eye contact: Remove contact lenses if worn. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: Do not induce vomiting; immediately call for medical help. · Most important symptoms and effects, both acute and delayed: Gastric or intestinal disorders when ingested. Nausea in case of ingestion. Slight irritant effect on eyes. Allergic reactions Danger: Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Indication of any immediate medical attention and special treatment needed: Treat symptomatically. Contains 4-chloro- α , α , α -trifluorotoluene, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate. May produce an allergic reaction. Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

· Extinguishing media · Suitable extinguishing agents: Foam Sand Carbon dioxide Fire-extinguishing powder Gaseous extinguishing agents Water fog / haze · For safety reasons unsuitable extinguishing agents: Water stream. · Special hazards arising from the substance or mixture Flammable liquid and vapor. Formation of toxic gases is possible during heating or in case of fire. · Advice for firefighters · Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit.



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 804 Intermediate Coat

(Cont'd. of page 3)

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Ensure adequate ventilation.
 Use personal protective equipment as required.
 Keep away from ignition sources.
 Take precautionary measures against static discharge.

 Environmental precautions
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

 Methods and material for containment and cleaning up
- Towel or mop up material and collect in a suitable container. For larger spills, add non-combustible inert binding material, then sweep up and discard.
- **Reference to other sections** See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling

- Precautions for safe handling:
- Open and handle receptacle with care.
- Keep out of reach of children.

Avoid contact with the eyes and skin.

- Keep away from open flame or other ignition souces.
- · Information about protection against explosions and fires:
- Flammable liquid and vapor.

Protect against electrostatic charges.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

- · Conditions for safe storage, including any incompatibilities
- **Requirements to be met by storerooms and receptacles:** Store in cool, dry conditions in well-sealed receptacles.
- Avoid storage near extreme heat, ignition sources or open flame. • Information about storage in one common storage facility: Store away from foodstuffs.
- Store away from oxidizing agents.
- Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

Control parameters

| · Components with limit values that require monitoring at the workplace: | | | | |
|--|---|--|--|--|
| 1332-58-7 Ka | 1332-58-7 Kaolin | | | |
| PEL (USA) | Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction | | | |
| | (Cont'd on page 5) | | | |

(Cont'd. on page 5)



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

| Trade name: Pec | ora Deck 804 Intermediate Coat | |
|----------------------------|--|---------------------|
| | | (Cont'd. of page 4) |
| REL (USA) | Long-term value: 10* 5** mg/m ³ | |
| | *total dust **respirable fraction | |
| TLV (USA) | Long-term value: 2* mg/m ³ E; as respirable fraction | |
| EL (Canada) | Long-term value: 2 mg/m ³ | |
| EL (Canada) EV (Canada) | Long-term value: 2(D) mg/m ³ | |
| | respirable | |
| LMPE (Mexico) | Long-term value: 2* mg/m ³ A4, *fracción respirable | |
| 556-67-2 Octai | nethylcyclotetrasiloxane | |
| WEEL (USA) | Long-term value: 10* ppm | |
| | *OARS WEEL | |
| 14807-96-6 Ta | c | |
| PEL (USA) | Long-term value: 20 mppcf ppm | |
| | (containing <1% Quartz) | |
| REL (USA) | Long-term value: 2* mg/m ³ | |
| | *respirable dust; and <1% Quartz | |
| TLV (USA) | Long-term value: 2* mg/m ³ *as respirable fraction; E | |
| EL (Canada) | Long-term value: 2 *0.1 f/cc mg/m ³ | |
| | resp. *if contains asbestos : ACGIH A1, IARC 1 | |
| EV (Canada) | Long-term value: 2* mg/m ³ , 2 f/cc ppm *respirable | |
| LMPE (Mexico) | Long-term value: 2* mg/m ³ A4, *fracción respirable | |
| 13463-67-7 Tit | anium dioxide | |
| PEL (USA) | Long-term value: 15* mg/m ³ *total dust | |
| REL (USA) | See Pocket Guide App. A | |
| TLV (USA) | Long-term value: 10 mg/m ³ | |
| EL (Canada) | Long-term value: 10* 3** mg/m ³ *total dust;**respirable fraction; IARC 2B | |
| EV (Canada) | Long-term value: 10 mg/m³ total dust | |
| LMPE (Mexico) | Long-term value: 10 mg/m³ A4 | |
| 95-63-6 1,2,4-t | rimethylbenzene | |
| REL (USA) | Long-term value: 125 mg/m ³ , 25 ppm | |
| TLV (USA) | Long-term value: 123 mg/m ³ , 25 ppm | |
| 108-67-8 mesit | lylene | |
| REL (USA) | Long-term value: 125 mg/m³, 25 ppm | |
| TLV (USA) | Long-term value: 123 mg/m ³ , 25 ppm | |
| 14808-60-7 Qu | | |
| PEL (USA) | Long-term value: 0.05* mg/m ³ | |
| | | (Cont'd. on page 6) |





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 804 Intermediate Coat

| | | (Cont'd. of page 5) |
|--|---|---------------------|
| | *resp. dust; 30mg/m3/%SiO2+2 | (contral of page of |
| REL (USA) | Long-term value: 0.05* mg/m ³ | |
| | *respirable dust; See Pocket Guide App. A | |
| TLV (USA) | Long-term value: 0.025* mg/m ³ | |
| | *as respirable fraction | |
| EL (Canada) | Long-term value: 0.025 mg/m ³ ACGIH A2; IARC 1 | |
| EV (Canada) | Long-term value: 0.10* mg/m ³ | |
| | *respirable fraction | |
| LMPE (Mexico) | Long-term value: 0.025* mg/m ³ | |
| | A2, *fracción respirable | |
| | -tert-butyl-p-cresol | |
| REL (USA) | Long-term value: 10 mg/m ³ | |
| TLV (USA) | Long-term value: 2* mg/m ³ | |
| FL (Canada) | *as inhalable fraction and vapor | |
| EL (Canada) | Long-term value: 2 mg/m ³ vapour and inhalable aerosol | |
| EV (Canada) | Long-term value: 2 mg/m ³ | |
| _ ((• • • • • • • • • • • • • • • • • | inhalable, vapour and aerosol | |
| LMPE (Mexico) | Long-term value: 2 mg/m ³ | |
| | A4, IFV | |
| 14464-46-1 Cris | | |
| PEL (USA) | Long-term value: 0.05* mg/m ³ *resp. dust;1⁄2 value from resp.dust formulae Quartz | |
| REL (USA) | Long-term value: 0.05* mg/m ³ | |
| | *respirable dust; See Pocket Guide App. A | |
| TLV (USA) | Long-term value: 0.025* mg/m ³ *as respirable fraction | |
| EL (Canada) | Long-term value: 0.025 mg/m ³ | |
| | respirable, ACGIH A2; IARC 1 | |
| EV (Canada) | Long-term value: 0.05* mg/m ³ | |
| · · · · | *respirable fraction | |
| LMPE (Mexico) | Long-term value: 0.025* mg/m ³ | |
| | A2, *fracción respirable | |
| · Exposure cor | ntrols | |
| | tive and hygienic measures: | |
| | nutionary measures for handling chemicals should be followed. In foodstuffs, beverages and feed. | |
| | ith the eyes and skin. | |
| Avoid breathing | mist, vapors, or spray. | |
| | n should strictly avoid inhalation or skin contact. | |
| Engineering co Breathing equi | ontrols: No relevant information available. | |
| | der normal conditions of use. | |
| Use suitable res | piratory protective device in case of insufficient ventilation. | |
| A NIOSH approv | ved dust respirator should be used for operations generating dust. | |
| | | (Cont'd. on page 7 |

PECORA CORPORATION® Architectural Weatherproofing Products U.S.A. + since 1862

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 804 Intermediate Coat

(Cont'd. of page 6)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- \cdot Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment Avoid release to the environment.

· Risk management measures No special requirements.

9 Physical and chemical properties

| Information on basic physical and chemical properties | | |
|---|---|---------------------|
| · Appearance: Form: | Viscous liquid. | |
| Color: | According to product specification | |
| · Odor: | Not determined. | |
| · Odor threshold: | Not determined. | |
| · pH-value: | Not determined. | |
| Melting point/Melting range: | Not determined. | |
| Boiling point/Boiling range: | Not determined. | |
| · Flash point: | 42.2 °C (108 °F) | |
| · Flammability (solid, gaseous): | Not applicable. | |
| · Auto-ignition temperature: | Not determined. | |
| · Decomposition temperature: | Not determined. | |
| · Danger of explosion: | Product does not present an explosion hazard. | |
| · Explosion limits | | |
| Lower: | Not determined. | |
| Upper: | Not determined. | |
| Oxidizing properties: | Non-oxidizing. | |
| · Vapor pressure: | Not determined. | |
| · Density: | | |
| Relative density: | 1.22 | |
| Vapor density: | Not determined. | |
| Evaporation rate: | Not determined. | |
| · Solubility in / Miscibility with | | |
| | | (Cont'd. on page 8) |



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 804 Intermediate Coat

| | | (Cont'd. of page 7 |
|-----------------------------------|------------------------------------|--------------------|
| Water: | Not determined. | |
| · Partition coefficient (n-octane | ol/water): Not determined. | |
| · Viscosity | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| · VOC content: | <100 g/L | |
| · Other information | No relevant information available. | |

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Flammable liquid and vapor. Reacts with oxidizing agents.
- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers
- Hazardous decomposition products Under fire conditions only: Carbon monoxide and carbon dioxide Hydrocarbons Silicon oxides.

11 Toxicological information

Information on toxicological effects

• Acute toxicity: Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6800 mg/kg (rat)

Dermal LD50 >3400 mg/kg (rab)

95-63-6 1,2,4-trimethylbenzene

Oral LD50 5000 mg/kg (rat)

128-37-0 2,6-di-tert-butyl-p-cresol

- Oral LD50 >6000 mg/kg (rat)
- Dermal LD50 >2000 mg/kg (rat)

Primary irritant effect:

- · On the skin: Based on available data, the classification criteria are not met.
- \cdot On the eye: Based on available data, the classification criteria are not met.
- · Sensitization:

Contains 4-chloro- α , α , α -trifluorotoluene, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate. May produce an (Cont'd. on page 9)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

| | | (Cont'd. of page |
|--|---|------------------|
| allergic read | xtion. | |
| · IARC (Inter | national Agency for Research on Cancer): | |
| 13463-67-7 | Titanium dioxide | 2 |
| 98-56-6 | 4-chloro-α,α,α-trifluorotoluene | 2 |
| 14808-60-7 | Quartz | 1 |
| 14464-46-1 | Cristobalite | 1 |
| · NTP (Natio | nal Toxicology Program): | |
| 14808-60-7 | Quartz | |
| 14464-46-1 | Cristobalite | |
| | Occupational Safety & Health Administration): | |
| Ingestion. Eye contact Skin contact Germ cell r Carcinoger | | |

- Aquatic toxicity
- Harmful to aquatic life with long lasting effects.

556-67-2 Octamethylcyclotetrasiloxane

- LC50 >22 mg/l (Oncorhynchus mykiss)
- EC50 >15 mg/l (daphnia)

128-37-0 2,6-di-tert-butyl-p-cresol

LC50 1.1 mg/l (fish)

EC50 0.48 mg/l (daphnia)

41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

LC50 0.97 mg/l (lepomis macrochirus)

- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- · Other adverse effects No relevant information available.

13 Disposal considerations

· Waste treatment methods

(Cont'd. on page 10)



(Cont'd. of page 9)



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 804 Intermediate Coat

· Recommendation:

Smaller quantities can be disposed of with household waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

· Uncleaned packagings

• Recommendation: Disposal must be made according to official regulations.

| UN-Number | |
|------------------------------|--|
| DOT | NA1993 |
| ADR/RID/ADN, IMDG, IATA | UN1263 |
| UN proper shipping name | |
| DOT | Combustible liquid, n.o.s. |
| | (Octamethylcyclotetrasiloxane, Solvent naphtha |
| | (petroleum), light arom.) |
| ADR/RID/ADN, IMDG, IATA | PAINT |
| Transport hazard class(es) | |
| DOT | |
| | |
| | |
| 2 | |
| Class | 3 |
| Label | 3 |
| ADR/RID/ADN | ~ |
| | |
| | |
| | |
| | 0 (54) |
| Class Label | 3 (F1) 3 |
| | J |
| IMDG, IATA | |
| | |
| | |
| | • |
| Class | 3 |
| Label | 3 |
| Packing group | |
| DOT, ADR/RID/ADN, IMDG, IATA | III |
| Environmental hazards | |
| Marine pollutant: | No |



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

| | (Cont'd. of page |
|---|---|
| Special precautions for user Hazard identification number (Kemler | Warning: Flammable liquids r code): 30 |
| EMS Number: | F-E, <u>S-E</u> |
| Transport in bulk according to An | nnex II of |
| MARPOL73/78 and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| DOT | Classified as combustible under US DOT regulatior |
| ADR/RID/ADN | Labeling is only required for single packages ≥119 L gal / 450 L. ess than 30 kg gross and inner packagings less than 5 L each. |
| ADR/RID/ADN | Labeling is only required for single packages ≥119 l gal / 450 L. |
| ADR/RID/ADN Limited Quantity for packages I | Labeling is only required for single packages ≥119 L gal / 450 L. |
| ADR/RID/ADN Limited Quantity for packages I IMDG Limited Quantity for packages I IATA | Labeling is only required for single packages ≥119 L gal / 450 L. ess than 30 kg gross and inner packagings less than 5 L each. |

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- · SARA

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

95-63-6 1,2,4-trimethylbenzene

· TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

· Proposition 65 (California)

· Chemicals known to cause cancer:

Reference to talc not applicable to product, as product contains no asbestiform fibers. Reference to cristobalite, quartz and titanium dioxide is based on unbound respirable particles and is not generally applicable to product as supplied.

(Cont'd. on page 12)



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 804 Intermediate Coat

| | (C | Cont'd. of page 11) |
|---------------|--|---------------------|
| 14807-96-6 | Talc | |
| 13463-67-7 | Titanium dioxide | |
| 98-56-6 | 4-chloro-α,α,α-trifluorotoluene | |
| 14808-60-7 | Quartz | |
| 14464-46-1 | Cristobalite | |
| · Chemicals | known to cause developmental toxicity for females: | |
| None of the | ingredients are listed. | |
| · Chemicals | known to cause developmental toxicity for males: | |
| None of the | ingredients are listed. | |
| · Chemicals | known to cause developmental toxicity: | |
| None of the | ingredients are listed. | |
| · EPA (Envir | onmental Protection Agency): | |
| 95-63-6 1 | ,2,4-trimethylbenzene | 11 |
| 108-67-8 m | nesitylene | |
| IARC (Inter | national Agency for Research on Cancer): | i |
| 13463-67-7 | Titanium dioxide | 2B |
| 98-56-6 | 4-chloro-α,α,α-trifluorotoluene | 2B |
| 14808-60-7 | Quartz | 1 |
| 14464-46-1 | Cristobalite | 1 |
| · Canadian D | Domestic Substances List (DSL): | |
| All ingredier | nts are listed or exempt. | |

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent OSHA: Occupational Safety & Health Administration Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B Carc. 2: Carcinogenicity - Category 2 Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Sources Website, European Chemicals Agency (echa.europa.eu)

(Cont'd. on page 13)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: Pecora Deck 804 Intermediate Coat

(Cont'd. of page 12) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel 1305 North Elorida Avenue

1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtel.com