


Sealants and Packing Material

3M™ Fire Barrier Sealant FD 150+ (RED)

3M™ Fire Barrier Sealant FD 150+ is a ready to use, gun-grade, elastomeric sealant that dries to form a monolithic flexible seal. 3M™ Fire Barrier Sealant FD 150+ firestops joints and through penetrations through floor slabs, walls and other fire-rated building partitions and assemblies. 3M™ Fire Barrier Sealant FD 150+, when properly installed, helps control the spread of fire, smoke and noxious gases before, during and after exposure to a fire. 3M™ Fire Barrier Sealant FD 150+ remains elastomeric and exhibits excellent adhesion to a full range of construction substrates.

Description	Water Based Sealant
Properties	Elastomeric Based
Application Temperature Range	40–122°F (4–50°C)
RoHS 2011/65/EU	Yes
Specifications	Fire Barrier up to 4 Hr; Smoke Seal L Rated; STC Rating 56; Elastometric +- 19%; LEED® VOC environmental regulations; IBC
Agency Approvals	 IBC; IRC; IFC; IPC; IMC; NFPA 5000; NEC (NFPA 70); NFPA 101



Order No.	UPC	Product Name	Color	Size	Case Quantity
FD150+RED(10.1OZ)	051115-18812	3M™ Fire Barrier Sealant FD 150+, Red, 10.1 fl. oz., Cartridge	Red	10.1 fl oz (298 ml)	12
FD150+RED(20OZ)	051115-18810	3M™ Fire Barrier Sealant FD 150+, Red, 20 fl. oz., Sausage	Red	20 fl oz (591 ml)	12
FD150+RED(28OZ)	051115-18811	3M™ Fire Barrier Sealant FD 150+, Red, 28 fl. oz., Cartridge	Red	28 fl oz (828 ml)	6
FD150+RED(4.5GAL)	051115-18813	3M™ Fire Barrier Sealant FD 150+, Red, 4.5 gal, Pail	Red	4.5 gal (15,1 l)	1